



CONTRACT

State of Oklahoma

DUPLICATE

Dispatch via Print

Supplier 0000501011
SUMMIT TRUCK GROUP LLC
SUMMIT TRUCK GROUP
DALLAS TX 75320-7006
USA

Contract ID			Page	
000000000000000000000005727			1 of 1	
Contract Dates		Currency	Rate Type	Rate Date
01/28/2020 to 02/06/2021		USD	CRRNT	PO Date
Description:			Contract Maximum	
SW0035T Heavy Duty Trucks			0.00	
Allow Open Item Reference				
TYPE: STATEWIDE				

Tax Exempt? Y Tax Exempt ID:736017987

Contract Lines:

Line #	Cat CD / Item ID / Item Desc	UOM	Minimum Order Qty	Amt	Maximum / Open Qty	Amt
1	25101611 / 2020 International MV607 25,500 GVW See the vendor's pricing documents for pricing for options.	EA	1.00	0.00	0.00	0.00
	Contract Base Pricing		1.00000			
		EA		0001		
2	25101611 / 2020 International HV607 33,000 GVW See the vendor's pricing documents for pricing for options.	EA	1.00	0.00	0.00	0.00
	Contract Base Pricing		1.00000			
		EA		0001		
3	25101611 / 2020 International HV607 54,000 GVW See vendor's pricing documents for pricing for options.	EA	1.00	0.00	0.00	0.00
	Contract Base Pricing		1.00000			
		EA		0001		
4	25101611 / 2020 International HV613 66,000 GVW See vendor's pricing documents for pricing for options.	EA	1.00	0.00	0.00	0.00
	Contract Base Pricing		1.00000			
		EA		0001		

COMMENTS:

SW0035T Heavy Duty Trucks

Contract Period: 02/07/2020 - 02/06/2021

Agreement Period: 02/07/2017 - 02/06/2021

Final = The price is final after adjustments
Hard = Apply adjustments regardless of other adjustments
Skip = Skip adjustments if any other adjustments have been applied

Authorized Signature

Contact Information

Website:

Company Name	Summit Truck Group
Doing Business as (if applicable)	
Contact Person for Solicitation Response	Ronnie Watson
Phone	405 365 1432
Email	ronnie.watson@summittruckgroup.com
Fax	405 235 2541
Address For Purchase Orders-Number & Street-Post Office Box (some companies have ordering addresses that are different than the payment address)	1735 W Reno
City, State, Zip	Oklahoma City Oklahoma 73106
Contact Person for Contract/Ordering/Price Information/Equipment Additions/Changes/Discontinuations	
Contact Name	Ronnie Watson
Phone	405 365 1432
Fax	405 235 2541
Email	ronnie.watson@summittruckgroup.com
Secondary Contact for Contract/Ordering	David Carney
Phone	405 850 5498
Fax	405 235 2541
Email	david.carney@summittruckgroup.com
Address For Payment-Number & Street-Post Office Box (some companies have a different Payment/remittance address than the ordering address)	1735 W Reno
City, State, Zip	Oklahoma City Oklahoma 73106
Contact Person/Department for payment	Michelle Ball Sales
Phone	405 236 2792
Fax	405 235 2541
Email	michelle.ball@summittruckgroup.com
Counties You can provide products/warranty service/repair parts to	<u> X </u> All counties in Oklahoma OR just these counties: _____
(include any special conditions, such as territory or district maps on a separate sheet)	
Payment Discount (i.e. 15 days)	Net <u> N/A </u> days
Supplier will be responsible for notifying the contracting officer when the contact information changes.	Notes: (Special ordering instructions-please attach any special instructions on a separate sheet)



TRUCK GROUP

A HIGHER STANDARD OF VALUE

1735 W RENO AVENUE • OKLAHOMA CITY, OK 73106 • 405-236-2792 • FAX 405-235-2541

Exceptions / Classifications to Solicitation # SW035T

- C,1,4 Vehicles delivered will have over 175 miles on the odometer. Warranty will start at the delivered mileage
- C,10,1 Summit Truck Group does not except P-Card payments on vehicle purchases
- C,13,1 All delivery date quoted or expressed are approximate. Approximate dates does not include body builder time.

A handwritten signature in black ink, appearing to read "R. Watson", is positioned above the printed name.

Rennie Watson
Governmental Sales



TRUCK GROUP

A HIGHER STANDARD OF VALUE

1735 W RENO AVENUE • OKLAHOMA CITY, OK 73106 • 405-236-2792 • FAX 405-235-2541

Summit Truck Group Training Policy

Summit Truck Group will provide 8 hours of training to cover operation and service aspects of the unit. This will be conducted by a certified sale and or service technician at the time of delivery.

A handwritten signature in black ink, appearing to read "Ronnie Watson", with a long, sweeping horizontal line extending to the right.

Ronnie Watson
Governmental Sales



Navistar, Inc.
2701 Navistar Drive
Lisle, IL 60532 USA

P: 331-332-5000
W: www.navistar.com

Virgen Perez-Dormann
Direct: (331) 332-2925
DealerAdmin@Navistar.com

December 20, 2016

RE: Summit Truck Group

To whom it may concern:

This letter certifies that Navistar, Inc. has a current Dealer Sales and Maintenance Agreement with Summit Truck Group. They are authorized to sell and service International brand motor vehicles at the following locations:

Account Name	Location	City	ST	Zip
SUMMIT TRUCK GROUP - Ard	621 Interstate Drive	Ardmore	OK	73401
SUMMIT TRUCK GROUP - End	2401 N. Grand St.	Enid	OK	73701
SUMMIT TRUCK GROUP - Okc	1735 W. Reno Avenue	Oklahoma City	OK	73106
SUMMIT TRUCK GROUP - TUL	1023 N. Garnett Rd	Tulsa	OK	74116

Please contact DealerAdmin@Navistar.com if you have questions or need additional information.

Sincerely,

Virgen Perez-Dormann
Dealer Administration and Licensing Specialist.

LIMITED WARRANTY FOR MODELS

WORKSTAR® SERIES, 7300/7400 (4x2, 6x4, 4x4, 6x6)

*Effective with vehicles built January 02, 2015 or later

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or RENEWED® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE		
Feature Code 40010) (See exceptions listed below)	Months	Miles/Km (000)
Basic Vehicle Warranty (WorkStar Only-Feature 40013)	12	Unlimited
Towing (Vehicles with MaxxFord®7 engine failures only)	24	Unlimited
Towing (Vehicles with MaxxFord®9 engine failures only)	24	250/400
Towing (Vehicles with Navistar® N 9 engine failures only)	24	250/400
Towing (Vehicles with MaxxFord®10 engine failures only)	24	250/400
Towing (Vehicles with Navistar® N 10 engine failures only)	24	250/400
Towing (Vehicles with MaxxFord®DT standard torque engine failures only)	24	Unlimited
Towing (Vehicles with MaxxFord®DT high torque engine failures only)	24	250/400
Towing (First 90 days see below) (Vehicle Down Situations Only)		
(See exceptions listed below)		
Note: Items not listed in warranty exceptions follow base warranty.		
WARRANTY EXCEPTIONS		
CHASSIS COVERAGE	Months	Miles/Km (000)
Frame side rails	84	Unlimited
Cab/cowl structure	60	Unlimited
Cab/cowl perforation corrosion	60	Unlimited
ENGINE COVERAGE	Months	Miles/Km (000)
Non-Rescue Applications		
MaxxFord® 7 Engine	24	Unlimited
MaxxFord® 9 Engine	24	250/400
Navistar® N 9 Engine	24	250/400
MaxxFord® 10 Engine	24	250/400
Navistar® N 10 Engine	24	Unlimited
MaxxFord® DT Engine Standard Torque	24	250/400
MaxxFord® DT Engine High Torque	24	250/400
Rescue Application Only (Fire Truck, Ambulance, Emergency)		
MaxxFord® 7 Engine	60	100/160
MaxxFord® 9 Engine	60	100/160
Navistar® N 9 Engine	60	100/160
MaxxFord® 10 Engine	60	100/160
Navistar® N 10 Engine	60	100/160
MaxxFord® DT Engine Standard Torque	60	100/160
MaxxFord® DT Engine High Torque	60	100/160
DRIVE/TRAIN COVERAGE	Months	Miles/Km (000)
Spicer axles, Propeller shaft, Eaton clutch, TTC Transmission	24	Unlimited

Eaton/Fuller 6206/6306 Transmission	24	Unlimited
Meritor Axles	24	Unlimited
MISCELLANEOUS COVERAGE		
	Months	Miles/Km (000)
Batteries	12	Unlimited
Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited
FIRST 90 DAYS FROM DELIVERY TO USER (DTU)		
Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless coverage is stated above).		
Adjustments and Maintenance (such as aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).		

Navistar Diesel Engine Coverage Includes:

Engine block, cylinder heads, internally lubricated components fuel pump, high pressure pump, air compressor, injectors/nozzles; electronic engine modules, engine relays, engine sensors and regulators required for electronic engine operation, and certain aftertreatment components. Excluding: attaching accessories (e.g., fan clutch, alternator, starter, etc.), and externally mounted electrical and filtration systems.

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Components warranted by their respective manufacturers (such as, non-International® brand engines, tires, Allison Transmissions, lubricants, etc.)
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments.

Repairs & Maintenance

- Maintenance-related items/repairs, or those needed as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension.

Other

- Vehicles sold and/or operated outside the United States and Canada
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note: The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:

I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

Customer Signature

Date

Owner's Address

City

State/Prov

Postal Code

Truck Model

Vehicle Identification Number

Engine Number

Engine Serial Number

Date Delivered to User (DTU)

Odometer Reading at Delivery

IMPORTANT: The information contained in this Warranty Policy explains the coverage provided on your new International[®] vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.

LIMITED WARRANTY FOR MODELS

5000 PAYSTAR®, 7500/7600, WORKSTAR®

*Effective with vehicles built January 02, 2015 or later

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or RENEWED® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE		Months	Miles/Km (000)
Basic Vehicle Warranty (See exceptions listed below)		12	Unlimited
Towing (Vehicles with MaxxFord® 10 engine failures only)		24	250/400
Towing (Vehicles with N10 engine failures only)		24	250/400
Towing (Vehicles with N13 engine failures only)		24	Unlimited
Towing (First 90 days see below) (Vehicle Down Situations Only)			
Note: Items not listed in warranty exceptions follow base warranty.			
WARRANTY EXCEPTIONS			
CHASSIS COVERAGE		Months	Miles/Km (000)
Frame side rails		60	Unlimited
Frame side rails (7500 only)		84	Unlimited
Cab/cowl structure		60	Unlimited
Cab/cowl perforation corrosion		60	Unlimited
ENGINE COVERAGE		Months	Miles/Km (000)
Non-Rescue Applications			
MaxxFord® 10 Engine		24	250/400
Navistar® N10 Engine		24	250/400
Navistar® N13 Engine		24	Unlimited
Navistar® N13 Major Components		60	500/800
Major Components are cylinder block, main bearing bolts, cylinder head castings and cap screws, crankshaft, camshaft, cam follower, connecting rods/caps/bolts, intake manifold castings, and gear train gears.			
Rescue Application Only (Fire Truck, Ambulance, Emergency)			
MaxxFord® 10 Engine		60	100/160
Navistar® N10 Engine		60	100/160
Navistar® N13 Engine		60	100/160
DRIVETRAIN COVERAGE		Months	Miles/Km (000)
Rear Axle Weight Ratings Greater than 52,000 lb			
Front Axle Assembly		12	Unlimited
Rear Axle and Differential		12	Unlimited
Transmission		12	Unlimited
Rear Axle Weight Ratings of 52,000 lb and Less			
Front Axle Assembly		36	300/480
Rear Axle and Differential		36	300/480
Transmission		36	300/480
MISCELLANEOUS COVERAGE		Months	Miles/Km (000)

Brightwork, Chassis Paint and Corrosion (other than Cab)	6	Unlimited
Hood/Cab Paint	12	Unlimited
FIRST 90 DAYS FROM DELIVERY TO USER (DTU)		
Correction of loose fasteners, squeaks, rattles and unusual noises. Towing (unless specific coverage is stated above). Adjustments and Maintenance (such as aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).		

Navistar Diesel Engine Coverage Includes:

Engine block, cylinder heads, internally lubricated components fuel pump, high pressure pump, turbocharger, water pump, air compressor, injectors/nozzles, electronic engine modules, engine relays, engine sensors and regulators required for electronic engine operation, and certain aftertreatment components. Excluding: attaching accessories (e.g., fan clutch, alternator, starter, etc.), and externally mounted electrical and filtration systems.

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Components warranted by their respective manufacturers (such as non-International® brand engines, tires, Allison Transmissions, lubricants,
- Bodies, equipment, and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments

Repairs & Maintenance

- Maintenance-related items/repairs, or those needed as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension

Other

- Vehicles sold and/or operated outside the United States and Canada
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note: The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:

I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

Customer Signature

Date

Owner's Address

City

State/Prov

Postal Code

Truck Model

Vehicle Identification Number

Engine Number

Engine Serial Number

Date Delivered to User (DTU)

Odometer Reading at Delivery

IMPORTANT: The information contained in this Warranty Policy explains the coverage provided on your new International[®] vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.

LIMITED WARRANTY FOR MODELS

1000, 4000, DURASTAR® SERIES

*Effective with vehicles built January 02, 2015 or later

BASIC VEHICLE

Navistar, Inc., at its option, will repair or replace any part of this vehicle that proves defective in material or workmanship, in normal use and service, with new or RENEWED® parts, based on the Component Coverages below. Exceptions are listed below:

BASIC VEHICLE COVERAGE		Months	Miles/Km (000)
Basic Vehicle Warranty (Feature Code 40024) (See exceptions listed below)		24	Unlimited
Towing (Vehicles with MaxxForce® 7 engine failures only)		24	Unlimited
Towing (Vehicles with MaxxForce® 9 engine failures only)		24	250/400
Towing (Vehicles with Navistar® N 9 engine failures only)		24	250/400
Towing (Vehicles with MaxxForce® DT standard torque engine failures only)		24	Unlimited
Towing (Vehicles with MaxxForce® DT high torque engine failures only)		24	250/400
Towing (First 90 days see below) (Vehicle Down Situations Only)			
(See exceptions listed below)			
Note: Items not listed in warranty exceptions follow base warranty.			
WARRANTY EXCEPTIONS			
CHASSIS COVERAGE		Months	Miles/Km (000)
Frame side rails		84	Unlimited
Cab/cowl structure		60	Unlimited
Cab/cowl perforation corrosion		60	Unlimited
ENGINE COVERAGE		Months	Miles/Km (000)
Non-Rescue Applications			
MaxxForce® 7 Engine		24	Unlimited
MaxxForce® 9 Engine		24	250/400
Navistar® N 9		24	Unlimited
MaxxForce® DT Engine Standard Torque		24	250/400
MaxxForce® DT Engine High Torque		24	250/400
Rescue Application Only (Fire Truck, Ambulance, Emergency)			
MaxxForce® 7 Engine		60	100/160
MaxxForce® 9 Engine		60	100/160
Navistar® N 9		60	100/160
MaxxForce® DT Engine Standard Torque		60	100/160
MaxxForce® DT Engine High Torque		60	100/160
DRIVE TRAIN COVERAGE		Months	Miles/Km (000)
Meritor Axles (DuraStar model)		36	Unlimited
MISCELLANEOUS COVERAGE		Months	Miles/Km (000)
Batteries		12	Unlimited
Brightwork, Chassis Paint and Corrosion (other than Cab)		6	Unlimited
Hood/Cab Paint		12	Unlimited

FIRST 90 DAYS FROM DELIVERY TO USER (DTU)
Correction of loose fasteners, squeaks, rattles and unusual noises; Towing (unless specific coverage is stated above); Adjustments and Maintenance (e.g., aim headlights, adjust brakes/clutch, adjust steering system, check and fill coolant levels).

Navistar Diesel Engine Coverage includes:

Engine block, cylinder heads, internally lubricated components fuel pump, high pressure pump, turbocharger, water pump, air compressor, injectors/nozzles; electronic engine modules; engine relays, engine sensors and regulators required for electronic engine operation, and certain aftertreatment components. Excluding: attaching accessories (e.g., fan clutch, alternator, starter, etc.), and externally mounted electrical and filtration systems.

WHAT IS NOT INCLUDED UNDER BASIC COVERAGE

Components/Items

- Warranted by their respective manufacturers (e.g., non-International® brand engines, tires, Allison Transmissions, Eaton Hybrid components, lubricants, etc.)
- Bodies, equipment and accessories installed by other than authorized International® Truck employees at International® Truck manufacturing plants
- Front and rear axle alignment
- Front & Rear axle coverage excludes brakes, wheel ends, axle shafts, controls & attachments

Repairs & Maintenance

- Maintenance-related items/repairs, or those, as a result of normal wear and tear, including tune-ups, brake/clutch linings, windshield wiper blades, tire balancing, lubrication, and other similar procedures/parts required to keep vehicle in good working condition
- Failures that are the result of poor fuel quality, water in fuel, rust, etc.
- Repairs needed as a result of vehicle misuse, negligent care, improper maintenance, improper operation, or the result of accident or collision
- Fade, runs, mismatch or damage to paint, trim items, upholstery, chrome, polished surfaces, etc., resulting from environmental causes such as improper polishes, cleaners or washing solutions, or chemical and industrial fallout
- Failure to observe published capacity or load specifications for engine, transmission, propeller shaft, axles (powertrain) and suspension

Other

- Vehicles sold and/or operated outside the United States and Canada
- Vehicles/components that have had unauthorized alterations or modifications
- Vehicles on which the odometer reading has been altered
- Loss of time or use of the vehicle, loss of profits, inconvenience, or other consequential or incidental damages or expenses
- Replacement of defective parts with parts other than those provided by Navistar, Inc

OBTAINING SERVICE

Return this vehicle to any International Truck Dealer authorized to service this model vehicle and engine.

This warranty is automatically transferred to subsequent owners at no charge. Visit your local Authorized International Truck Dealer for name and address change information.

Note: The customer has 365 days and up to a maximum of 100,000 miles (160,000 km) from DTU to purchase an extended warranty on the unit. For extended warranty purchases between 181 and 365 days from DTU and <100,000 miles (160,000 km) an additional fee will be assessed. See your local International dealer for details.

DISCLAIMER

NO WARRANTIES ARE GIVEN BEYOND THOSE DESCRIBED HEREIN. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. THE COMPANY SPECIFICALLY DISCLAIMS WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. ALL OTHER REPRESENTATIONS TO THE USER/PURCHASER, AND ALL OTHER OBLIGATIONS OR LIABILITIES. THE COMPANY FURTHER EXCLUDES LIABILITY FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES, ON THE PART OF THE COMPANY OR SELLER. No person is authorized to give any other warranties or to assume any liabilities on the Company's behalf unless made or assumed in writing by the Company, and no other person is authorized to give any warranties or to assume any liabilities on the seller's behalf unless made or assumed in writing by the seller.

Remedies Under State or Provincial Law: Some States and Provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to the owner. This warranty gives the owner specific legal rights, and he may also have other legal rights which may vary by state or province.

RECORD OF OWNERSHIP

Upon receipt of new vehicle by original owner, complete the following:
I have read this Warranty Brochure and fully understand the warranty coverage. I acknowledge that I have received a copy of the Owner's Limited Warranty and I accept the terms described herein.

Customer Signature	Date		
Owner's Address	City	State/Prov	Postal Code
Truck Model	Vehicle Identification Number		
Engine Number	Engine Serial Number		
Date Delivered to User (DTU)	Odometer Reading at Delivery		

IMPORTANT: The information contained in this Warranty Policy explains the coverage provided on your new International® vehicle. This policy should be kept in the vehicle for presentation to the Dealer when you request warranty services.



A HIGHER STANDARD OF VALUE

1735 W RENO AVENUE • OKLAHOMA CITY, OK 73106 • 405-236-2792 • FAX 405-235-2541

December 19th 2016

Summit Truck Group Buy Back, Trade-In and Exchange Policy for Parts

- Dealer stocked items that have been purchased and returned are subject to a \$35% restocking fee
- Non-stocking items that can be returned to the manufacture are subject to a restocking fee. This fee will be determined by the manufacturer.
- Parts that are stocked items can be returned to the manufacture, but have already been installed on the truck, may be returnable. These will be handled on a case by case review
- Any part ordered in error by Summit Truck Group may be returned

Brian Hilton
Assistant Parts Manager

A handwritten signature in black ink, appearing to read "B. Hilton", with a large, sweeping flourish underneath.



TRUCK GROUP

A HIGHER STANDARD OF VALUE

1735 W RENO AVENUE • OKLAHOMA CITY, OK 73106 • 405-236-2792 • FAX 405-235-2541

Summit Truck Group Sales and Service Facilities

Sales, Parts and Service

Summit Truck Group
1735 W Reno
Oklahoma City, Oklahoma, 73106
405 365-1432

Parts and Service

Summit Truck Group
1023 Garrett Road
Tulsa, Oklahoma, 74116
918 438-2000

Summit Truck Group
2401 N Grand
Enid, Oklahoma 73701
580 237 5571

Summit Truck Group
601 Interstate Dr.
Ardmore, Oklahoma 73401
580 223-8896

Summit Truck Group
1701 N 20th
Muskogee, Oklahoma 74401
918 683-5621

Webers Diesel Service LLC
1433 SE 1st
Lawton Oklahoma 73501
580 353-1837



A HIGHER STANDARD OF VALUE

1735 W RENO AVENUE • OKLAHOMA CITY, OK 73106 • 405-236-2792 • FAX 405-235-2541

Summit Truck Group Web Page

www.summittruckgroup.com

Prepared For:

Oklahoma Office Of Public Affairs
 Florian Giza JOYCE
 PO Box 460 LEIVAS
 Duncan, OK 73534-0460
 (405)236 - 2792
 Reference ID: 25.5 Under 163"

Presented By:

Summit Truck Group
 Ronnie Watson
 1735 W. RENO
 OKLAHOMA CITY OK 73106 -
 (405)236-2792

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2017 4300 SBA 4X2 (MA025)

APPLICATION:	Construction Dump
MISSION:	Requested GVWR: 25500. Calc. GVWR: 25500 Calc. Start / Grade Ability: 24.09% / 1.56% @ 55 MPH Calc. Geared Speed: 81.2 MPH
DIMENSION:	Wheelbase: 152.00, CA: 84.90, Axle to Frame: 75.00
ENGINE, DIESEL:	{Cummins B6.7 220} EPA 2017, 220 HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 220 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 2500_RDS_P} 5th Generation Controls; Wide Ratio, 5-Speed, With Overdrive; On/Off Hwy; 33,000 lb GVW & GCW Max., With PTO Provision, Less Retarder
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Navistar Select} I-Beam Type, 8,000-lb Capacity
AXLE, REAR, SINGLE:	{Navistar Select} Single Reduction, 17,500-lb Capacity, With 190 Wheel Ends Gear Ratio: 5.29
CAB:	Conventional
TIRE, FRONT:	(2) 11R22.5 Load Range G ECO PLUS HS3 (CONTINENTAL), 495 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 11R22.5 Load Range G HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, RR, SPRING, SINGLE:	Vari-Rate; 18,500-lb Capacity, With 4500 lb Auxiliary Rubber Spring
PAINT:	Cab schematic 100GA Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model 4300 SBA 4X2 with 152.00 Wheelbase, 84.90 CA, and 75.00 Axle to Frame.
 TOW HOOK, FRONT (2) Frame Mounted
 FRAME RAILS High Strength Low Alloy Steel (80,000 PSI Yield); 9.125" x 3.062" x 0.312" (231.8mm x 77.8mm x 8.0mm); 394.3" (10014mm) Maximum OAL
 BUMPER, FRONT Full Width, Aerodynamic, Steel; 0.142" Material Thickness
 WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)
 AXLE, FRONT NON-DRIVING {Navistar Select} I-Beam Type, 8,000-lb Capacity
 SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 8,000-lb Capacity; With Shock Absorbers
 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
 DRAIN VALVE {Berg} with Pull Chain, for Air Tank
 AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)
 AIR DRYER {Bendix AD-9} With Heater
 BRAKE CHAMBERS, SPRING Relocated To Rear Of Rear Axle For Maximum Ground Clearance
 BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 Sqn
 BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
 BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
 BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
 AIR COMPRESSOR {Cummins} 18.7 CFM Capacity
 STEERING COLUMN Tilting
 STEERING WHEEL 2-Spoke, 18" Dia., Black
 STEERING GEAR {TRW (Ross) TAS40} Power
 EXHAUST SYSTEM Single Vertical Aftertreatment Device, Frame Mounted Right Side Back of Day Cab, for Single Vertical Tail Pipe
 EXHAUST HEIGHT 10'
 MUFFLER/TAIL PIPE GUARD (1) Non-Bright Aluminum
 TAIL PIPE (1) Straight Type, Non-Bright, for Single Exhaust
 ELECTRICAL SYSTEM 12-Volt, Standard Equipment
 CIGAR LIGHTER Includes Ash Cup
 ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense
 BODY BUILDER WIRING To Rear of Frame, With Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket
 BATTERY SYSTEM {International} Maintenance-Free, (2) 12-Volt 1850CCA Total
 2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
 RADIO {Panasonic CQ120} AM/FM, Includes Multiple Speakers, Includes Auxiliary Input
 BATTERY DISCONNECT SWITCH {Cole-Hersee 75920-06} 300 Amp; Battery Box Mounted, Disconnects Charging Circuits, Locks with Padlock
 BACK-UP ALARM Electric, 102 dBA
 HORN, ELECTRIC Disc Style
 BATTERY BOX Steel With Plastic Cover, 18" Wide, 2, 3, or 4 Battery Capacity, Mounted Left Side Back of Cab
 JUMP START STUD Remote Mounted
 HORN, AIR Black, Single Trumpet, Air Solenoid Operated
 WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time
 TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
 HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
 STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection
 COURTESY LIGHT (2) Mounted In Front Map Pocket Left and Right Side
 INDICATOR, LOW COOLANT LEVEL With Audible Alarm
 ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, With Ignition "OFF" and any Door Opened
 HEADLIGHTS Halogen; Composite Aero Design for Two Light System
 GRILLE Chrome
 BUG SCREEN Mounted Behind Grille
 FRONT END Tilting, Fiberglass, With Three Piece Construction
 PAINT SCHEMATIC, PT-1 Single Color, Design 100
 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

Description

PROMOTIONAL PACKAGE Government and Municipal Silver Package; Two Year Limited Subscription of On-Command Service Information (Formerly Fleet ISIS), and On-Command Parts Information (Formerly Fleet Parts Catalog), Requires Specific Feature Combinations

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines

ENGINE, DIESEL {Cummins B6.7 220} EPA 2017, 220 HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 220 Peak HP (Max)

VENDOR WARRANTY, ENGINE {Cummins} B6.7 Engine, 3-Year Unlimited Miles Standard Warranty

FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On

RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, With 313 SqIn Charge Air Cooler. With In-Tank Transmission Cooler

AIR CLEANER With Service Protection Element

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines

EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Idle Regulations

ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; With Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines

FEDERAL EMISSIONS {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2017

TRANSMISSION, AUTOMATIC {Allison 2500_RDS_P} 5th Generation Controls; Wide Ratio, 5-Speed, With Overdrive; On/Off Hwy; 33,000 lb GVW & GCW Max., With PTO Provision, Less Retarder

TRANSMISSION OIL Synthetic; 20 thru 28 Pints

SHIFT CONTROL PARAMETERS Allison 1000 or 2000 Series Transmissions, 5th Generation Controls, Performance Programming

PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring

PTO LOCATION Left Side of Transmission

AXLE, REAR, SINGLE {Navistar Select} Single Reduction, 17,500-lb Capacity, With 190 Wheel Ends . Gear Ratio: 5.29

SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 18,500-lb Capacity, With 4500 lb Auxiliary Rubber Spring

FUEL/WATER SEPARATOR Cummins Supplied on Engine, with 12 Volt DC Heater, with Water-in-Fuel Sensor

FUEL TANK Top Draw; D-Style, Non-Polished Aluminum, 16" Tank Depth, 50 U.S. Gal., 189 L Capacity, with Quick Connect Outlet, Mounted Left Side, Under Cab

DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab

CAB Conventional

GRAB HANDLE, CAB INTERIOR (2) Safety Yellow

GAUGE CLUSTER English With English Electronic Speedometer

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

GAUGE, DEF FLUID LEVEL

SEAT, DRIVER {National 2000} Air Suspension, Mid Back, Vinyl, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Angle Adjust

SEAT, PASSENGER {National 2000} Air Suspension, Mid Back, Vinyl, Less Isolator, Less Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Angle Adjustment

GRAB HANDLE (2) Chrome Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry, Mounted Left and Right, Each Side at "B" Pillar

MIRRORS (2) {Lang Mekra} Styled; Rectangular, Power Both Sides Flat Glass Only, Thermostatically Controlled Heated Heads, Clearance

Lights LED, Black Heads, Brackets and Arms, Breakaway Type, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing

SEAT BELT All Orange; 1 to 3

CAB MOUNTING HEIGHT EFFECTS Mid Cab in Lieu of Low Cab Mounting Height (Approx. 4") With Cab Air Suspension

ARM REST, RIGHT, DRIVER SEAT

ARM REST, LEFT, PASSENGER SEAT

AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster

INSTRUMENT PANEL Center Section, Flat Panel

STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door

CAB INTERIOR TRIM Deluxe

WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEEL SEALS, FRONT {International} Oil-Lubricated Wheel Bearings

PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; With Vendor Applied White Powder Coat Paint

PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; With Vendor Applied White Powder Coat Paint

Description

(4) TIRE, REAR 11R22.5 Load Range G HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
(2) TIRE, FRONT 11R22.5 Load Range G ECO PLUS HS3 (CONTINENTAL), 495 rev/mile, 75 MPH, All-Position

Services Section:

WARRANTY Standard for Durastar 1000/4000 Series, Effective with Vehicles Built January 2, 2015 or Later, CTS-2475P
SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable
Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA)
Maximum Benefit per Incident

Prepared For:

Oklahoma Office Of Public Affairs
 Florian Giza JOYCE
 315 SW 5th STEIVAS
 Lawton, OK 73501-4337
 (405)236 - 2792
 Reference ID: 33K

Presented By:

Summit Truck Group
 Ronnie Watson
 1735 W. RENO
 OKLAHOMA CITY OK 73106 -
 (405)236-2792

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2017 7400 SBA 4X2 (SA625)

APPLICATION:	Construction Dump
MISSION:	Requested GVWR: 33000. Calc. GVWR: 33000 Calc. Start / Grade Ability: 35.50% / 3.56% @ 55 MPH Calc. Geared Speed: 78.2 MPH
DIMENSION:	Wheelbase: 169.00, CA: 101.90, Axle to Frame: 63.00
ENGINE, DIESEL:	{Cummins ISL9 350} EPA 2010, 350 HP @ 2000 RPM, 1000 lb-ft Torque @ 1400 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 3000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
AXLE, REAR, SINGLE:	{Meritor MS-21-14X-4DFR} Single Reduction, 21,000-lb Capacity, R Wheel Ends Gear Ratio: 5.29
CAB:	Conventional
TIRE, FRONT:	(2) 11R22.5 Load Range G ECO PLUS HS3 (CONTINENTAL), 495 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 11R22.5 Load Range G HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, RR, SPRING, SINGLE:	Vari-Rate; 23,500-lb Capacity
PAINT:	Cab schematic 100GN Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model 7400 SBA 4X2 with 169.00 Wheelbase, 101.90 CA, and 63.00 Axle to Frame.
 TOW HOOK, FRONT (2) Frame Mounted
 FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL
 BUMPER, FRONT Steel, Swept Back
 WHEELBASE RANGE 138" (350cm) Through and Including 187" (475cm)
 AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,000-lb Capacity
 SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 12,000-lb Capacity; With Shock Absorbers
 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
 DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
 AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel) With Automatic Traction Control
 AIR DRYER {Bendix AD-9} With Heater
 BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn
 BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
 BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
 BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
 AIR COMPRESSOR {Cummins} 18.7 CFM Capacity
 STEERING COLUMN Stationary
 STEERING WHEEL 2-Spoke, 18" Dia., Black
 STEERING GEAR {Sheppard M100} Power
 EXHAUST SYSTEM Switchback Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab; Includes Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab
 ELECTRICAL SYSTEM 12-Volt, Standard Equipment
 POWER SOURCE Cigar Type Receptacle without Plug and Cord
 ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense
 BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn
 BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total
 2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
 RADIO {Panasonic CQ120} AM/FM, Includes Multiple Speakers, Includes Auxiliary Input
 BACK-UP ALARM Electric, 102 dBA
 HORN, ELECTRIC Disc Style
 BATTERY BOX Steel With Plastic Cover, 18" Wide, 2, 3, or 4 Battery Capacity, Mounted Left Side Back of Cab
 JUMP START STUD Remote Mounted
 HORN, AIR Black, Single Trumpet, Air Solenoid Operated
 WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time
 CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
 TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
 HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
 STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection
 COURTESY LIGHT (2) Mounted In Front Map Pocket Left and Right Side
 INDICATOR, LOW COOLANT LEVEL With Audible Alarm
 ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, With Ignition "OFF" and any Door Opened
 TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
 BATTERY DISCONNECT SWITCH 300 Amp; Cab Mounted, Disconnects Charging Circuits; Locks with Padlock
 INSULATION, UNDER HOOD for Sound Abatement
 GRILLE Stationary, Chrome
 INSULATION, SPLASH PANELS for Sound Abatement
 BUG SCREEN Mounted Behind Grille
 FRONT END Tilting, Fiberglass, With Three Piece Construction; for WorkStar
 PAINT SCHEMATIC, PT-1 Single Color, Design 100
 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
 PROMOTIONAL PACKAGE Government and Municipal Silver Package; Two Year Limited Subscription of On-Command Service Information (Formerly Fleet ISIS), and On-Command Parts Information (Formerly Fleet Parts Catalog), Requires Specific Feature Combinations

Description

CLUTCH Omit Item (Clutch & Control)
 ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
 BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines
 ENGINE, DIESEL {Cummins ISL9 350} EPA 2010, 350 HP @ 2000 RPM, 1000 lb-ft Torque @ 1400 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)
 FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed
 FEDERAL EMISSIONS {Cummins ISL9} EPA, OBD and GHG Certified for Calendar Year 2017
 RADIATOR Cross Flow, Series System; 1228 SqIn Aluminum Radiator Core and 1167 SqIn Charge Air Cooler
 AIR CLEANER Single Element
 THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel
 EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Idle Regulations
 ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; With Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines
 TRANSMISSION, AUTOMATIC {Allison 3000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.
 OIL COOLER, AUTO TRANSMISSION {Modine} Water to Oil Type
 TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission
 TRANSMISSION OIL Synthetic; 29 thru 42 Pints
 ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction
 TRANSMISSION TCM LOCATION Located Inside Cab
 SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming
 PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring
 PTO LOCATION Dual, Left and Right Side of Transmission
 AXLE, REAR, SINGLE {Meritor MS-21-14X-4DFR} Single Reduction, 21,000-lb Capacity, R Wheel Ends . Gear Ratio: 5.29
 SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 23,500-lb Capacity
 FUEL/WATER SEPARATOR {Racor 400 Series,} 12 Volt Pre-Heater, with Primer Pump, and WIF Sensor
 LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail 34" Back of Cab
 FUEL TANK Top Draw; D-Style, Non-Polished Aluminum, 19" Deep, 70 U.S. Gal., 265 L Capacity, with Quick Connect Outlet, Mounted Left Side, Under Cab
 DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab
 CAB Conventional
 GAUGE CLUSTER English With English Electronic Speedometer
 IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
 GAUGE, DEF FLUID LEVEL
 SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, With 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust
 SEAT, PASSENGER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolated, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Adjust
 GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar
 MIRRORS (2) {Lang Mekra} Rectangular, Thermostatically Controlled Heated Heads, Black Heads, Brackets and Arms, Breakaway Type, 7.55" x 14.1" Integral Convex Both Sides, 102" Inside Spacing
 AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster
 INSTRUMENT PANEL Center Section, Flat Panel
 HVAC FRESH AIR FILTER
 STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door
 CAB INTERIOR TRIM Deluxe
 CAB REAR SUSPENSION Air Bag Type
 WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
 WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
 PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; With Vendor Applied White Powder Coat Paint
 PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; With Vendor Applied White Powder Coat Paint
 (4) TIRE, REAR 11R22.5 Load Range G HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
 (2) TIRE, FRONT 11R22.5 Load Range G ECO PLUS HS3 (CONTINENTAL), 495 rev/mile, 75 MPH, All-Position

Services Section:

Description

WARRANTY Standard for WorkStar 7300/7400 (4x2, 4x4, 6x4, 6x6), Effective with Vehicles Built January 2, 2015 or Later, CTS-2002U SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA) Maximum Benefit per Incident

Prepared For:

Oklahoma Office Of Public Affairs
Florian Giza JOYCE LEIVAS
PO Box 460
Duncan, OK 73534-0460
(405)236 - 2792
Reference ID: STATE-54K

Presented By:

Summit Truck Group
Ronnie Watson
1735 W. RENO
OKLAHOMA CITY OK 73106 -
(405)236-2792

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile**2017 7400 SBA 6X4 (SF625)****APPLICATION:**

Construction Dump

MISSION:

Requested GVWR: 54000. Calc. GVWR: 54000
Calc. Start / Grade Ability: 20.59% / 1.90% @ 55 MPH
Calc. Geared Speed: 78.2 MPH

DIMENSION:

Wheelbase: 195.00, CA: 127.90, Axle to Frame: 75.00

ENGINE, DIESEL:

{Cummins ISL9 350} EPA 2010, 350 HP @ 2000 RPM, 1000 lb-ft Torque @ 1400 RPM, 2200
RPM Governed Speed, 350 Peak HP (Max)

TRANSMISSION, AUTOMATIC:

{Allison 3000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive;
On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW
& GCW Max.

CLUTCH:

Omit Item (Clutch & Control)

AXLE, FRONT NON-DRIVING:

{Meritor MFS-14-143A} Wide Track, I-Beam Type, 14,000-lb Capacity

AXLE, REAR, TANDEM:

{Meritor MT-40-14X-4DFR} Single Reduction, 0.433"(11mm) Wall Housing Thickness, 40,000-lb
Capacity, R Wheel Ends Gear Ratio: 5.29

CAB:

Conventional

TIRE, FRONT:

(2) 12R22.5 Load Range H HSR2 (CONTINENTAL), 483 rev/mile, 75 MPH, All-Position

TIRE, REAR:

(8) 11R22.5 Load Range H HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

SUSPENSION, REAR, TANDEM:

{Hendrickson RT-403} Walking Beam Type 54" Axle Spacing; 40,000-lb Capacity With Rubber
Center Bushings

FRAME REINFORCEMENT:

Outer "C" Channel, Heat Treated Alloy Steel (120,000 PSI Yield); 10.813" x 3.892" x 0.312";
(274.6mm x 98.9mm x 8.0mm); 480.0" (12192mm) Maximum OAL

PAINT:

Cab schematic 100GN

Location 1: 9219, Winter White (Std)

Chassis schematic N/A

Description

Base Chassis, Model 7400 SBA 6X4 with 195.00 Wheelbase, 127.90 CA, and 75.00 Axle to Frame.
TOW HOOK, FRONT (2) Frame Mounted
FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL
FRAME REINFORCEMENT Outer "C" Channel, Heat Treated Alloy Steel (120,000 PSI Yield); 10.813" x 3.892" x 0.312"; (274.6mm x 98.9mm x 8.0mm); 480.0" (12192mm) Maximum OAL
BUMPER, FRONT Steel, Swept Back
FRAME EXTENSION, FRONT Integral; 20" In Front of Grille, With Outer "C" Channel Reinforcement
CROSSMEMBER, FRONT for Hydraulic Pump, Mounting Flange to Accommodate Pump
WHEELBASE RANGE 169" (430cm) Through and Including 219" (555cm)
AXLE, FRONT NON-DRIVING {Meritor MFS-14-143A} Wide Track, I-Beam Type, 14,000-lb Capacity
SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 14,000-lb Capacity; With Shock Absorbers
BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
DRAIN VALVE {Berg} with Pull Chain, for Air Tank
AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)
AIR DRYER {Bendix AD-9} With Heater
BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn
BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. Long Stroke Brake Chambers
BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
AIR COMPRESSOR {Cummins} 18.7 CFM Capacity
STEERING COLUMN Tilting
STEERING WHEEL 2-Spoke, 18" Dia., Black
STEERING GEAR {Sheppard M100} Power
EXHAUST SYSTEM Switchback Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab; Includes Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab
ENGINE COMPRESSION BRAKE {Jacobs} for Cummins ISL/L9 Engines; with Selector Switch and On/Off Switch
ELECTRICAL SYSTEM 12-Volt, Standard Equipment
POWER SOURCE Cigar Type Receptacle without Plug and Cord
ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense
BODY BUILDER WIRING To Rear of Frame, With Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket
BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total
2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
RADIO {Panasonic CQ120} AM/FM, Includes Multiple Speakers, Includes Auxiliary Input
BACK-UP ALARM Electric, 102 dBA
AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications
HORN, ELECTRIC Disc Style
BATTERY BOX Steel With Plastic Cover, 18" Wide, 2, 3, or 4 Battery Capacity, Mounted Right Side Back of Cab
JUMP START STUD Remote Mounted
HORN, AIR Black, Single Trumpet, Air Solenoid Operated
WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time
CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on
STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection
COURTESY LIGHT (2) Mounted In Front Map Pocket Left and Right Side
INDICATOR, LOW COOLANT LEVEL With Audible Alarm
ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, With Ignition "OFF" and any Door Opened
TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
INSULATION, UNDER HOOD for Sound Abatement
GRILLE Stationary, Chrome
INSULATION, SPLASH PANELS for Sound Abatement
BUG SCREEN Mounted Behind Grille
FRONT END Tilting, Fiberglass, With Three Piece Construction; for WorkStar

Description

PAINT SCHEMATIC, PT-1 Single Color, Design 100
 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
 PROMOTIONAL PACKAGE Government and Municipal Silver Package; Two Year Limited Subscription of On-Command Service Information (Formerly Fleet ISIS), and On-Command Parts Information (Formerly Fleet Parts Catalog), Requires Specific Feature Combinations
 CLUTCH Omit Item (Clutch & Control)
 ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
 BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines
 PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted
 ENGINE, DIESEL {Cummins ISL9 350} EPA 2010, 350 HP @ 2000 RPM, 1000 lb-ft Torque @ 1400 RPM, 2200 RPM Governed Speed, 350 Peak HP (Max)
 FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed
 FEDERAL EMISSIONS {Cummins ISL9} EPA, OBD and GHG Certified for Calendar Year 2017
 RADIATOR Cross Flow, Series System; 1228 SqIn Aluminum Radiator Core and 1167 SqIn Charge Air Cooler
 AIR CLEANER Single Element
 THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel
 EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Idle Regulations
 ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; With Ignition Switch Control for Cummins ISB/B6.7 or ISL/L9 Engines
 TRANSMISSION, AUTOMATIC {Allison 3000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.
 OIL COOLER, AUTO TRANSMISSION {Modine} Water to Oil Type
 TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission
 TRANSMISSION OIL Synthetic; 29 thru 42 Pints
 ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction
 TRANSMISSION TCM LOCATION Located Inside Cab
 SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming
 PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring
 PTO LOCATION Dual, Left and Right Side of Transmission
 AXLE, REAR, TANDEM {Meritor MT-40-14X-4DFR} Single Reduction, 0.433"(11mm) Wall Housing Thickness, 40,000-lb Capacity, R Wheel Ends . Gear Ratio: 5.29
 SUSPENSION, REAR, TANDEM {Hendrickson RT-403} Walking Beam Type 54" Axle Spacing; 40,000-lb Capacity With Rubber Center Bushings
 SUSPENSION/REAR-AXLE IDENTITY for Meritor Tandem Rear Axles With Bar-Pin Beam Attachment Type Suspensions
 LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail 41" Back of Cab
 FUEL/WATER SEPARATOR {Racor 400 Series,} Unheated, with Primer Pump, and W/F Sensor
 FUEL TANK Top Draw; D-Style, Non-Polished Aluminum, 19.0" Tank Depth, 100 U.S. Gal., 378.5 L Capacity, Mounted Left Side Under Cab
 DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab
 CAB Conventional
 GAUGE CLUSTER English With English Electronic Speedometer
 IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
 GAUGE, DEF FLUID LEVEL
 SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, With 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust
 SEAT, PASSENGER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolated, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Adjust
 MIRRORS (2) {Lang Mekra} Styled; Rectangular, Power Both Sides Flat Glass Only, Thermostatically Controlled Heated Heads, Clearance Lights LED, Black Heads, Brackets and Arms, Breakaway Type, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing
 GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar
 SEAT BELT All Orange; 1 to 3
 AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster
 INSTRUMENT PANEL Center Section, Flat Panel
 HVAC FRESH AIR FILTER
 STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door
 CAB INTERIOR TRIM Deluxe
 CAB REAR SUSPENSION Air Bag Type

Description

WHEELS, FRONT {Maxion 90541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; With Vendor Applied White Powder Coat Paint

PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; With Vendor Applied White Powder Coat Paint

(8) TIRE, REAR 11R22.5 Load Range H HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

(2) TIRE, FRONT 12R22.5 Load Range H HSR2 (CONTINENTAL), 483 rev/mile, 75 MPH, All-Position

Services Section:

WARRANTY Standard for WorkStar 7300/7400 (4x2, 4x4, 6x4, 6x6), Effective with Vehicles Built January 2, 2015 or Later, CTS-2002U

SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable

Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA)

Maximum Benefit per Incident

Prepared For:
Oklahoma Office Of Public Affairs

Presented By:
Summit Truck Group
Ronnie Watson
1735 W. RENO
OKLAHOMA CITY OK 73106 -
(405)236-2792

Reference ID: STATE-66K N13

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile

2017 7600 SBA 6X4 2010 (SF667)

APPLICATION:	Front Plow and Underbelly Scraper No Spreader
MISSION:	Requested GVWR: 66000. Calc. GVWR: 66000 Calc. Start / Grade Ability: 29.16% / 2.05% @ 55 MPH Calc. Geared Speed: 68.0 MPH
DIMENSION:	Wheelbase: 262.00, CA: 194.90, Axle to Frame: 53.00
ENGINE, DIESEL:	{Navistar N13} EPA 2010, SCR, 370 HP @ 1700 RPM, 1350 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 370 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 4500_RDS_P} 5th Generation Controls; Wide Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-160} Single Reduction 46,000-lb Capacity, 200 Wheel Ends Gear Ratio: 5.63
CAB:	Conventional
TIRE, FRONT:	(2) 315/80R22.5 Load Range L HSC1 (CONTINENTAL), 484 rev/mile, 68 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, TANDEM:	{Hendrickson RT-463} Walking Beam Type 54" Axle Spacing; 46,000-lb Capacity With Bronze Center Bushings
FRAME REINFORCEMENT:	Outer "C" Channel, Heat Treated Alloy Steel (120,000 PSI Yield); 10.813" x 3.892" x 0.312"; (274.6mm x 98.9mm x 8.0mm); 480.0" (12192mm) Maximum OAL
PAINT:	Cab schematic 100GS Location 1: 9219, Winter White (Std) Chassis schematic 932GS Wheel: 0001, Canyon Black (Std)

Description

Base Chassis, Model 7600 SBA 6X4 2010 with 262.00 Wheelbase, 194.90 CA, and 53.00 Axle to Frame.
 FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL
 FRAME REINFORCEMENT Outer "C" Channel, Heat Treated Alloy Steel (120,000 PSI Yield); 10.813" x 3.892" x 0.312"; (274.6mm x 98.9mm x 8.0mm); 480.0" (12192mm) Maximum OAL
 BUMPER, FRONT Steel, Swept Back
 FRAME EXTENSION, FRONT Integral; 20" In Front of Grille, With Outer "C" Channel Reinforcement
 CROSSMEMBER, FRONT for Hydraulic Pump, Mounting Flange to Accommodate Pump
 WHEELBASE RANGE 250" (635cm) Through and Including 311" (790cm)
 CROSSMEMBER, INTERMEDIATE (1) 5-Piece ilo Each Single Dogbone With 4x2, 4x4 Chassis and Each Double Dogbone With 6x4, 6x6 and 8x6 Tridem Chassis
 AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
 SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 20,000-lb Capacity; With Shock Absorbers
 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
 BRAKES, FRONT, AIR CAM 16.5" x 6", Includes 24 SqIn Long Stroke Brake Chambers
 DRAIN VALVE {Berg} with Pull Chain, for Air Tank
 AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)
 AIR DRYER {Bendix AD-9} With Heater
 BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
 BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn
 BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake
 AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM Capacity, Single Cylinder
 STEERING COLUMN Tilting
 STEERING WHEEL 2-Spoke, 18" Dia., Black
 STEERING GEAR (2) {Sheppard M100/M80} Dual Power
 EXHAUST SYSTEM Switchback Vertical Aftertreatment Device, Dual Cans, Frame Mounted Left & Right Side; Includes Single Vertical Tail Pipe & Dual Guards
 ELECTRICAL SYSTEM 12-Volt, Standard Equipment
 CIGAR LIGHTER Includes Ash Cup
 POWER SOURCE Cigar Type Receptacle without Plug and Cord
 ALTERNATOR {Leece-Neville AV160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount
 BODY BUILDER WIRING To Rear of Frame, With Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket
 WIRING, SPECIAL Includes Wires Installed Through the Dash Panel and End in Engine Compartment, In Cab Wire Ends Will Have ESC Input Terminals, Engine Compartment Wire Ends will have Sealed Connectors
 BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total
 2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
 RADIO {Panasonic CQ120} AM/FM, Includes Multiple Speakers, Includes Auxiliary Input
 BATTERY DISCONNECT SWITCH {Cole-Hersee 75920-06} 300 Amp; Battery Box Mounted, Disconnects Cab Power, Does Not Disconnect Charging Circuits, Locks with Padlock
 BACK-UP ALARM Electric, 102 dBA
 AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications
 HORN, ELECTRIC Disc Style
 BATTERY BOX Steel With Plastic Cover, 18" Wide, 2, 3, or 4 Battery Capacity, Mounted Left Side Back of Cab
 JUMP START STUD Remote Mounted
 HORN, AIR Black, Single Trumpet, Air Solenoid Operated
 CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
 COURTESY LIGHT (2) Mounted In Front Map Pocket Left and Right Side
 STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start
 TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
 FENDER EXTENSIONS Rubber
 GRILLE Stationary, Chrome
 INSULATION, SPLASH PANELS for Sound Abatement
 BUG SCREEN Mounted Behind Grille
 FRONT END Tilting, Fiberglass, With Three Piece Construction Includes Long Hood
 PAINT SCHEMATIC, PT-1 Single Color, Design 100
 PAINT IDENTITY, PT-2 Single Color, Instruction No. 932. Wheels

Description

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
 VEHICLE REGISTRATION IDENTITY ID for the State of California
 CLUTCH Omit Item (Clutch & Control)
 ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection, for N13 Engines
 PTO EFFECTS, ENGINE FRONT for N13 Engines, Less PTO Unit, Includes Adapter Plate on Engine Front Mounted
 BLOCK HEATER, ENGINE {Phillips} 120V/1500W
 ENGINE, DIESEL {Navistar N13} EPA 2010, SCR, 370 HP @ 1700 RPM, 1350 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 370 Peak HP (Max)
 FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed
 FEDERAL EMISSIONS {Navistar N13} EPA, OBD and GHG Certified for Calendar Year 2017
 AIR CLEANER Single Element
 ENGINE CONTROL, REMOTE MOUNTED for PTO with N13 Engines
 COLD STARTING EQUIPMENT Automatic; With Engine ECM Control
 EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Idle Regulations
 RADIATOR Aluminum; Welded, Front to Back CrossFlow System, 1593 SqIn, 1012 SqIn CAC, 1543 SqIn 3 Core LTR
 TRANSMISSION, AUTOMATIC {Allison 4500_RDS_P} 5th Generation Controls; Wide Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder
 OIL COOLER, AUTO TRANSMISSION {Modine} Water to Oil Type
 TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission
 SHIFT CONTROL PARAMETERS Allison S-1 Performance Programming in Primary and Allison Fixed Programming in Secondary
 TRANSMISSION OIL Synthetic; 63 thru 76 Pints
 ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction
 TRANSMISSION TCM LOCATION Located Inside Cab
 PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring
 PTO LOCATION Dual, Left Side and Top of Transmission
 AXLE, REAR, TANDEM {Meritor RT-46-160} Single Reduction 46,000-lb Capacity, 200 Wheel Ends . Gear Ratio: 5.63
 SUSPENSION, REAR, TANDEM {Hendrickson RT-463} Walking Beam Type 54" Axle Spacing; 46,000-lb Capacity With Bronze Center Bushings
 SUSPENSION/REAR-AXLE IDENTITY for Meritor Tandem Rear Axles With Bar-Pin Beam Attachment Type Suspensions
 DEF TANK 9.5 U.S. Gal. 35.9L Capacity, Frame Mounted Outside Left Rail, Under Cab
 FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor
 FUEL TANK Top Draw; Non-Polished Aluminum, 26" Diam., 80 U.S. Gal., 302 L Capacity Mounted Left Side, Under Cab
 CAB Conventional
 GAUGE CLUSTER English With English Electronic Speedometer
 IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
 GAUGE, DEF FLUID LEVEL
 SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, With 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust
 SEAT, PASSENGER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolated, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Adjust
 GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar
 MIRRORS (2) {Lang Mekra} Rectangular, Thermostatically Controlled Heated Heads, Black Heads, Brackets and Arms, Breakaway Type, 7.55" x 14.1" Integral Convex Both Sides, 102" Inside Spacing
 SEAT BELT All Orange; 1 to 3
 AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster
 INSTRUMENT PANEL Center Section, Flat Panel
 HVAC FRESH AIR FILTER
 STORAGE POCKET, DOOR Molded Plastic, Full Width; Mounted on Passenger Door
 CAB INTERIOR TRIM Deluxe
 CAB REAR SUSPENSION Air Bag Type
 WHEELS, FRONT {Accuride 29300} DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
 WHEELS, REAR {Maxion 90541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
 (8) TIRE, REAR 11R22.5 Load Range G HDR2 (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
 (2) TIRE, FRONT 315/80R22.5 Load Range L HSC1 (CONTINENTAL), 484 rev/mile, 68 MPH, All-Position

Services Section:

Description

WARRANTY Standard for Paystar 5000, and Workstar 7500/7600, Effective with Vehicles Built January 2, 2015 or Later, CTS-2003Z SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA) Maximum Benefit per Incident

Contact Information

Website:

Company Name	ROBERTS TRUCK CENTER OF OKLA LLC. DBA AS SUMMIT TRUCK GROUP - TULSA
Doing Business as (if applicable)	
Contact Person for Solicitation Response	Jim Patchen
Phone	918-438-2000
Email	jim.patchen@summittruckgroup.com
Fax	918-234-6151
Address For Purchase Orders-Number & Street-Post Office Box (some companies have ordering addresses that are are different than the payment address)	1023 NO. GARNETT RD.
City, State, Zip	TULSA,OKLA 74116
Contact Person for Contract/Ordering/Price Information/Equipment Additions/Changes/Discontinuations	
Contact Name	
Phone	Jim Patchen
Fax	918-234-6151
Email	jim.patchen@summittruckgroup.com
Secondary Contact for Contract/Ordering	Tim Owens
Phone	918-438-2000
Fax	918-234-6151
Email	tim.owens@summittruckgroup.com
Address For Payment-Number & Street-Post Office Box (some companies have a different Payment/remittance address than the ordering address)	1023 NO. GARNETT RD.
City, State, Zip	TULSA,OKLA 74116
Contact Person/Department for payment	DIANE BATES
Phone	918-438-2000
Fax	918-234-6151
Email	diane.bates@summittruckgroup.com
Counties You can provide products/warranty service/repair parts to	<input checked="" type="checkbox"/> All counties in Oklahoma OR just these counties: _____
(include any special conditions, such as territory or district maps on a separate sheet)	
Payment Discount (i.e. 15 days)	Net <u>N/A</u> days
Supplier will be responsible for notifying the contracting officer when the contact information changes.	Notes: (Special ordering instructions-please attach any special instructions on a separate sheet)

SUMMIT TRUCK GROUP

www.summittruckgroup/tulsa.com

LOCATIONS FOR SERVICE

1. SUMMIT TRUCK GROUP-TULSA

1023 NO. GARNETT RD.

TULSA,OKLA 74116

918-438-2000

2. SUMMIT TRUCK GROUP-OKC

1735 WEST RENO

OK CITY,OKLA 73106

405-236-2792

3. SUMMIT TRUCK GROUP

621 INTERSTATE DRIVE

ARDMORE,OKLA 73401

580-223-8896



Chassis Warranty Statement

CRANE CARRIER COMPANY ("Manufacturer") warrants each new Crane Carrier sold by it or any of its authorized distributors to be free from defects in material or workmanship under normal use, and in Crane Carrier Company approved service, as follows: Its obligation under this warranty is limited to the repairing or replacing, as hereinafter provided, at its option, any part or parts of said carrier found to the Manufacturer's satisfaction to be defective upon examination by the Manufacturer, provided that such part or parts shall be returned freight prepaid to the Manufacturer's factory upon request and providing:

1. Such parts are other than Major Component Parts, and have failed within twelve (12) months or 12,000 miles or 2,000 hours, whichever first occurs after delivery of such carrier,
- or
2. Such parts are Major Component Parts that have failed within the time and mileage period after delivery specified in the Major Components Parts Warranty Schedule.

The repair or replacement of defective parts other than Major Component Parts will be made without charge for parts or labor when made at a Crane Carrier authorized Warranty Repair Station. Before any claim for the cost of replacement parts installed elsewhere than at an authorized Warranty Repair Station may be made under this warranty, prior notification of the need for the repairs must be given to the Manufacturer's Service Department in Tulsa, Oklahoma, and prior approval given by said Service Department. The repair or replacement of Major Component Parts will be made in accordance with the Major Component Warranty Schedule herein. The term "Major Component Parts," as used above, means clutches, (except facings), steering gears, radiators, frame rails and cross members. The Warranty shall not apply to any carrier which has been subjected to misuse, negligence, accident, or which shall have been altered or repaired outside the factory, without prior Factory Service Department approval, which alteration or repair in the Manufacturer's judgment, affected the carrier's stability or reliability. Nor does it apply to normal maintenance services (such as engine tune-up, fuel system cleaning, adjustments, wheel alignment and balancing, brake and clutch adjustments) or the replacement of service items (filter elements, fluids or lubricants, and friction facings) made in connection with such maintenance services.

The Manufacturer makes no warranty whatever with respect to engines, transmissions, axles, tires, starting devices, alternators, batteries, power take-offs, hoists, mixers, bodies, winches or other such trade accessories by other manufacturers, and passes on to the purchaser any and all separate warranties made by the respective manufacturers thereof.

THIS WARRANTY IS MADE EXPRESSLY IN LIEU OF ANY OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION OR LIABILITY ON THE PART OF THE MANUFACTURER. MANUFACTURER SHALL IN NO EVENT BE LIABLE FOR CONSEQUENTIAL DAMAGES. THE MANUFACTURER NEITHER ASSUMES NOR AUTHORIZES ANY PERSON TO ASSUME FOR IT ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF A NEW CRANE CARRIER. THE WARRANTY SHALL NOT APPLY TO USED CARRIERS IN ANY WAY.

Exclusion of Design Improvements

Crane Carrier Company has a continuous testing, evaluation and design improvement program which periodically results in design changes and improvements. Crane Carrier Company reserves the right to make design changes or improvements without imposing any obligation to install these changes on the carrier vehicles previously delivered.

Engine and Transmission Controls and Settings

You are cautioned about the hazards of tampering with the engine controls, transmission controls, and related systems in your new carrier, as such tampering is a violation of Federal and State laws. The Manufacturer's standard specifications are set to meet current emission laws. In the event that engine controls/settings, transmission controls/settings, or related systems are changed or required emission decals are removed, you may be subject to legal penalties and denial of warranty coverage as provided in each manufacturer's warranty. Your new Crane Carrier has been built with components such as engines, transmissions and axles which have been manufactured by suppliers for Crane Carrier Company. You have the assurance of Crane Carrier Company, as a carrier vehicle manufacturer, that the design and installation of these components and their related combinations have been thoroughly reviewed and approved by each component manufacturer.



In-Service Inspection

The new Crane Carrier just delivered to you has been thoroughly inspected and adjusted by the Crane Carrier Factory prior to shipment. To assure your complete satisfaction and long life of your new carrier a Pre-Delivery In-Service Inspection is required, that will be performed by your Crane Carrier Distributor. Any other arrangements for a Pre-Delivery In-Service Inspection must be pre-approved and authorized by the Crane Carrier Service Department. The Pre-Delivery In-Service Inspection will be performed for you at no charge to you.

After Completion of the "Pre-Delivery In-Service Inspection"

Your new carrier should be inspected daily by the operator and monthly by service technicians as outlined in the Crane Carrier Company Operation and Maintenance Manual to assure reliable service and to protect your warranty coverage. Crane Carriers are designed to give a long life of reliable service when operated properly and recommended maintenance schedules are followed. The life of vehicle components is directly dependent upon correct operation and timely maintenance inspections tailored to the work environment of your carrier. The recommended operating procedures are covered in the Operation and Maintenance Manual. If you have not received an Operation and Maintenance Manual with your new carrier, please contact the Crane Carrier Company Service Department. Service and Parts Manuals are provided for each carrier and should be received within six weeks of receiving the new carrier. It is the owners responsibility to fill out, sign and return the Warranty Registration card found on the inside back cover of the Warranty Registration booklet within 30 days receipt of the carrier. The registration card is pre-addressed and pre-paid postage is provided for your convenience. Failure to return the warranty registration card within 30 days will cause the warranty to start automatically 60 days from the date of shipment from Crane Carrier Company.

Items Not Covered by Warranty

Changes in adjustment resulting from normal use. This includes brakes and clutches, drive belts, wheel balance and axle alignment, clamps and controls.

- Changes in adjustment resulting from normal use. This includes brakes, drive belts, wheel balance, clamps and controls.
- Brake and clutch lining replacement for normal wear or noise.
- Bulbs, fuses, mud flaps, reflectors or wiper blades.
- Vibration, squeaks, fitting and hose leaks, unusual noises, loose bolts and hose and electrical connections are the result of use and are not warrantable after 90 days from date carrier is delivered by Crane Carrier.
- Wear out determined by manufacturer to not be premature.
- Damage from improper cleaning, storage or atmospheric contamination.
- Deterioration of cab trim or paint including chipping or fading.
- Required maintenance and maintenance items.
- Downtime and driver layover expense or other downtime liabilities.
- Filter elements, including oil, fuel and water conditioner.
- Contamination in the air, hydraulic or fuel systems.
- Oil and grease for refill or make-up.
- Premium transportation costs for obtaining replacement parts.
- Telephone, telegraph, teletype and other communication expense.
- Carrier towing charges or road service charges.
- Unauthorized repairs (When Field Service Representative is not available, contact the Crane Carrier Salesman, Distributor, or the Crane Carrier Service Department).

Noise Emissions Warranty

Crane Carrier Company warrants to the first person who purchases this vehicle for purposes other than resale and to each subsequent purchaser that this vehicle as manufactured by Crane Carrier Company, was designed, built and equipped to conform at the time it left Crane Carrier Company's control with all applicable U.S. EPA noise control regulations.

This warranty covers the vehicle as designed, built and equipped by Crane Carrier Company, and is not limited to any particular part, component or system of the vehicle manufactured by Crane Carrier Company. Defects in the design, assembly or in any part, component, or system of the vehicle as manufactured by Crane Carrier Company, which, at the time it left Crane Carrier Company's control, caused noise emissions to exceed Federal standards, are covered by this warranty for the life of this vehicle.


CCC STANDARD WARRANTY COVERAGE OF REFUSE PRODUCTS

Vehicle Coverage		Warranty Limitations (Time, Mileage or Hours, Whichever Comes First)			Percent Of Repair Paid By Owner
		Time (Months)	Mileage	Hours	
Basic Coverage		0-12	12,000	2,000	No Charge
Frame Rails and Crossmembers		0-36	0-30,000	Unlimited	0
		37-48	30,001-50,000		25
		49-60	50,001-75,000		50
		49-60	75,001-100,000		75
		Over 60	Over 100,000		100
Steering, Radiator, Drivelines, Major Fabrications and Cab Sheet Metal		0-12	0-12,000	Unlimited	0
		0-12	12,001-30,000		25
		0-12	30,001-40,000		50
		0-12	40,001-50,000		75
		0-12	Over 50,000		100
ISB6.7		24	Unlimited	Unlimited	No Charge
ISL9, ISX12, ISL G, ISX12 G		24	250,000	6,250	No Charge
(Warranty thru Cummins)					
Allison	2500 RDS, 3000 RDS, 3500 RDS, 4000 RDS, 4500 RDS (Warranty thru Allison)	36	Unlimited	Unlimited	No Charge
Bendix	ABS	36	350,000	10,800	Parts Only After 12 Months
	Air Dryer	12	100,000	3,600	
	Automatic Slack Adjusters (Parts Only)	24	200,000	7,200	
	Spring Brake Chambers	12	100,000	3,600	
	S Cam Brakes	36	Unlimited	10,800	
	Brake Friction Material	12	12,000	360	
Dana-Spicer	Non-Driving Steering Axles: E-1322, E-1462, D2000	24	Unlimited	Unlimited	No Charge
	Single Drive Axles: S23-190, S26-190 S30-190	24	Unlimited	Unlimited	No Charge
	Tandem Drive Axles: DSH44(P), D46-170(P)	36	Unlimited	Unlimited	No Charge
	DS405(P), DT463P, D52-190P, D52-590P	24	Unlimited	Unlimited	No Charge
Meritor	Steer Axle FL941	24	Unlimited	Unlimited	No Charge
	Single Drive Axles: RS-23-186, RS-26-185, RS-30-185	24	Unlimited	Unlimited	No Charge
	Tandem Drive Axles: RT-40-160P, RT-46-160P	24	Unlimited	Unlimited	No Charge
	ABS	36	300,000	Unlimited	No Charge
	Brakes	12	Unlimited	Unlimited	Parts Only
Paint, Piping, Exhaust Systems, Air Cleaner System and Wiring		0-12	0-12,000	Unlimited	0
		0-12	12,001-15,000		25
		0-12	15,001-20,000		50
		0-12	20,001-25,000		75
		0-12	Over 25,000		100

CCC 12-MONTH WARRANTY, Unlimited Mileage / Unlimited Hours ILS \$ 350

- [Contacts](#)
 - [Return Policy](#)
 - [Warranty Policy](#)
 - [Parts Pricebook](#)
- [HR](#)
 - [Contacts](#)
 - [Careers](#)
- [Home](#)
- [Parts](#)
- Parts Warranty

Parts

Phone: 918-832-7327 Fax: 918-832-7399 Email: parts@cranecarrier.com

Parts Warranty Policy

Vendor Items

All vendor items are covered by the original manufacturer's warranty policies. Items submitted for warranty consideration will be forwarded to the original manufacturer, and any warranty applied will be at the vendor's discretion.

Captive Parts - Manufactured by CCC

CCC manufactured parts are warranted for a period of 12 months from the date of shipment from our plant to be free from defects in material and workmanship, under correct use, normal operating conditions, and proper application.

Our obligation under this warranty shall be limited to the repair or exchange, at our option, F.O.B. our factory, of any part which proves to be thus defective. We reserve the right to either inspect the product at the buyer's location or require it to be returned to the factory for inspection.

The above warranty does not extend to goods damaged or subjected to accident, abuse, or misuse after shipment from our factory, nor to goods altered or repaired by anyone other than an authorized CCC representative.

This warranty states our entire and exclusive liability. CCC will in no event be liable for any special or consequential damage whatsoever, nor any sum in excess of the price received for the goods for which liability is claimed.

This policy is subject to change without notice.

[Back to Parts](#)

Item # 100009333
Medium Duty, 33,000 #
Truck

Dealer Name: Summit Truck Group

Make Bidding: Crane Carrier

Model Bidding: LET2-26 Year 2017

Model Code: LET2-33

Can this Vehicle come ALT Fuel Equipped?? YES/NO: Yes

Body & Chassis	Standard Specification	
GVWR	33,000	33,000 GVWR
Curb Weight/Payload	Mfg. Std. List Size	14,692 lbs. Chassis weight / 18,308 lbs. Payload
Chassis CA	102" CA, Clear Frame Rail	Yes, additional CA available - see option page
Style, Cab/Tilt Hood	Tilt Hood	Yes, low entry 18" step in height, tilt cab
Axle, Min Front Rating/lb/seals	12,000 lbs w/ springs	13,000 lbs
Axle, Min Rear Rating/lb/spd/seals	21,000 lbs, Oil, Walking Beam Type	26,000 lbs
Suspension, Front/Rear, lb	12,000/21,000	14,000/26,000
Frame, RBM, Min, in-lb	120,000 PSI	120,000 PSI / 2,233,200 RBM
Cab Mounts	Air Ride Cab	Not available on low entry models
Engine		
Engine Type	Diesel Turbocharged, Wet Sleeve Type	Yes, Diesel
Engine Cyl/GHP/Gross Torque, Min	Inline 6 Cyl/270 HP/800 Torque	Yes, inline 6 cylinder / 270 HP / 800 torque
Electronic Shutdown	High Water Temp/Low Oil Press	Yes
Governor	Electronic Control PTO Provision	Yes
Air Cleaner System	List Capacity	Echo XL 13-S
Transmission		
Trans, Type/Speeds, Min.	Allison 3500 RDS 6 Speed	Allison 3500 RDS 6 speed
Transmission ECU	Mounted in Cab	Mounted at transmission
PTO	Rt/Lt Side 10 Bolt	Right/Left side - 10 bolt
Electrical		
Alternator/Rating CapMin (amps)	12 Volt/ 130 Amp	12V / 150 amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CCA	Two / 1850 CCA
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Radio Wiring Harness	Two Way Radio Wiring Harness in Headler Console	Yes
Body Builder wiring/Rear of frame		Yes
Block Heater Min.	1000 Watt	Yes, 1000 Watt
Fuel		
Fuel Tank Capacity, L (gal) Min	70 Gallon minimum	80 gallon
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes, 12V heated
Exterior		
Paint	Cab-White Base Coat Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Horizontal	Vertical
Horn	Air, Electric	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes, power and heated, right and left
Handles	Grab Handles Both Sides	Yes, one interior & one exterior on both sides of cab
Grill	Chrome Grill Mount Bug Screen	Not required, remote mounted radiator behind cab
Courtesy Lights	Mounted Below Each Door	Not required on low entry
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Yes
Keys	3 Additional Keys	Yes
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Req.	Yes, integral
Radio	AM/FM	Yes, AM/FM
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Power Supply	12 Volt Power Supply in Cab	Yes, 12V power supply in cab
Seats		
Seating Capacity min	2 Passenger	Yes
Seats	Air Suspension Driver & Passenger	Yes, air suspension driver & passenger / black vinyl
Safety		
Brakes	Air Brakes with 13.2 cfm Compressor, Air Dryer, Air Horn, Auto Drain Valve	Yes, 18.7 cfm compressor w/ air dryer & drain valve
Restraint System All Pass	Req.	Yes
Alarm	Back-Up Alarm	Yes, 107 dba
Tires & Wheels		
Wheels, Type	Disc	Yes
Tires, Tubeless, Size/Tread Front	11R/22.5, 14 Ply Load G	11R/22.5, 16 ply, Load G
Tires, Tubeless, Size/Tread Rear	11R/22.5, 14 Ply Load G, Mud/Snow Tread	11R/22.5, 16 ply, Load G, Mud/Snow tread
Warranty		
2 Yr/Unlimited Mile Warranty	includes towing for warrantable failure	1 year/unlimited, towing covered under engine & transmission warranty
PURCHASE PRICE:		\$125,273
3 YR LEASE/MO		N/A
4 YR LEASE/MO		N/A
5 YR LEASE/MO		N/A
MSRP FOR PURCHASE PRICE:		\$193,955

Item # 1000009333
Medium Duty, 33,000 #
Truck

Dealer Name: Summit Truck Group

Make Bidding: Crane Carrier
Model Bidding: LET2-26 Year 2017
Model Code: LET2-33

Engines	Options		Purchase	3 YR Lease	4 YR Lease	5 YR Lease
Engine Diagnostic Reader Software/Cable	Software/Cable	Cummins Insite	\$3,000	N/A	N/A	N/A
Air Filter	Increase Capacity			N/A	N/A	N/A
Diesel Engine	300HP/860LBFT	Cummins 300hp in lieu of ISL9 270hp	\$1,290	N/A	N/A	N/A
Gas Engine	List Specs	Not available		N/A	N/A	N/A
CNG Engine	BiFuel - List Capacities	Not available		N/A	N/A	N/A
CNG Engine	Dedicated - List Capacity	ISLG 320 HP in lieu of ISL9 270HP	\$4,630	N/A	N/A	N/A
Air Cleaner System	Higher Capacity - List Additional Capacity			N/A	N/A	N/A
Dust Shield	Dust Shield for Snow Removal Operations	Not available		N/A	N/A	N/A
Transmission						
PTO Front	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille. Factory install Cannot be bolt on.	PTO crossmember sets under cab not requiring a front bumper extension	STD	N/A	N/A	N/A
Transmission	6 Speed, Manual, Direct Drive	Not available		N/A	N/A	N/A
Rear Axle						
Rear Axle	23,000 LB. 2-Spd Rear Axle with 23,000 LB Springs. Includes 4500 LB Auxiliary Springs.	Not available. Quoted with 26,000 lb axle		N/A	N/A	N/A
Electrical						
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	Leece Neville 210 Amp	\$140	N/A	N/A	N/A
Worklights	Worklight Accomodation Package, List Specs	2 Spare Rocker Switches in Dash	STD	N/A	N/A	N/A
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Electrical switch and wiring	\$430	N/A	N/A	N/A
Body & Chassis						
CA	Decrease To 84" CA, clear frame	Not available		N/A	N/A	N/A
CA	Increase to 120" CA, clear frame	122" CA	No Charge	N/A	N/A	N/A
CA	Increase to 138" CA w/120,000 PSI	140" CA	\$630	N/A	N/A	N/A
CA	Increase to 156" CA w/120,000 PSI	158"	\$630	N/A	N/A	N/A
Body	4 Door Crew Cab	2-door. 4 man seating all facing forward, all with seat belts	\$6,235	N/A	N/A	N/A
Reinforcement	Increase frame to 120,000 PSI With "C" Channel Reinforcement	120,000 PSI is Standard	STD	N/A	N/A	N/A
Suspension	Air Ride Rear Suspension	PAX-262 26K	\$2,430	N/A	N/A	N/A
Frame	Front Frame Extension With/Out PTO Adaptation	Swept Back Bumper	\$510	N/A	N/A	N/A
Front Extension	"C" Channel Reinforcement to Front of Frame	Full Liner from front to rear	\$1,350	N/A	N/A	N/A
Exterior						
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Any custom color excluding metallic	\$470	N/A	N/A	N/A
Mirrors	Heated Mirrors	Included in spec		N/A	N/A	N/A
Exhaust	Vertical	Vertical	STD	N/A	N/A	N/A
Screen	Grille Mounted Bug Screen	Not required with remote mtd radiator		N/A	N/A	N/A
Interior						
Tire Inflator	List Specs	Not available		N/A	N/A	N/A
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	2-door. 4 man seating all facing forward, all with seat belts		N/A	N/A	N/A
Tilt & Cruise	Tilt Wheel & Cruise Control	Tilt Wheel & Cruise Control	STD	N/A	N/A	N/A
Safety	Air Bags Both Sides	Not available		N/A	N/A	N/A
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	Not available		N/A	N/A	N/A
Visor	Visor over Windshield	Steel	\$2,000	N/A	N/A	N/A
Fuel						
Larger Fuel Capacity	100 Gallon Minimum	CA required to accept larger tank	\$500	N/A	N/A	N/A
Safety						
Alarm	Park Brake Alarm	Standard	STD	N/A	N/A	N/A
Hydraulic Brakes	Deduct for Hydraulic Brakes	Not available		N/A	N/A	N/A
Tires & Wheels						
Tires	Highway Tread Rear Tires	Bridgestone R250 H/16	-\$380	N/A	N/A	N/A
Towing						
Hooks	Front Tow Hooks	Tow Pins	\$110	N/A	N/A	N/A
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring		\$1,100	N/A	N/A	N/A
Delivery						
Delivery Cost	Price to Deliver Truck more than 150 miles	\$3.00 Per Mile	\$3.00 per mile			
Other						
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	2% for 5 or more				
Options not listed	Discount off MSRP for options not listed	40%				

Item # 100009383
Medium Duty, 46,000 -
54,000 # Truck

Dealer Name: Summit Truck Group
Make Bidding: Crane Carrier
Model Bidding: LET2-40 Year 2017
Model Code: LET2 46-54K
Yes

LT Fuel Equipped?? YES/NO:

Body & Chassis	Standard Specification	
GVWR	54,000	46,000 - 54,000
Curb Weight/Payload	Mfg. Std. List Size	18,057 lbs. Chassis / 35,943 lbs. Payload
Chassis CA	102" CA, Clear Frame Rail	Yes, additional CA available, see options page
Style, Cab/Tilt Hood	Tilt Hood	Yes, low entry 18" step in height, tilt cab
Axle, Min Front Rating/lb/seals	14,000/ LB with Springs	20,000 lbs
Axle, Min Rear Rating/lb/spd/seals	40,000 LBS/Oil, with Walking Beam Type	40,000 lbs
Frame, RBM, Min, in-lb	3,200,000 Double Frame "C" Channel Reinforcement	Yes, 3,369,600 w/ "C" channel reinforcement
Cab Mounts	Air Ride Cab	Not available on low entry models
Engine		
Engine Type	Diesel Turbocharged	Diesel
Engine Cyl/GHP/Gross Torque, Min	Inline 6 Cyl / 8 Liter or Larger / 850LBFT	Inline 6 cylinder / ISL9-300 HP / 860 torque
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press.	Yes
Air Cleaner System	List Capacity	Echo XL 13-S
Transmission		
Trans, Type/Speeds, Min.	Allison 3000RDS 6 Spd.	Allison 3000RDS 6 speed
Transmission ECU	Mounted in Cab	Mounted at transmission
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory Install. Include "C" Reinforcement to front	Yes, front bumper extension not required
PTO	R/L Side 10 bolt	Yes, right/left side - 10 bolt
Electrical		
Alternator/Rating Cap/Min (amps)	12 Volt/ 130 Amp	Yes, 12V / 160 amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	Yes, Two - 1850 CCA total
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Block Heater Min	1000 Watt	Yes, 1000 watt
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		Yes, HD steel header console
Body Builder Wiring to Rear of Frame		Yes
Power Supply	12 Volt Power Supply in Dash	Yes, 12V in dash
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Yes
Fuel		
Fuel Tank Capacity	100 Gallon Minimum	80 gallon
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes, 12V heated
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 2 Electric Horn	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes, power and heated, right and left
Grill	Chrome Grille Mount Bug Screen	Not required, remote mounted radiator behind cab
Courtesy Lights	Mounted Below Each Door	Not required on low entry
Handles	Grab Handles Both Sides	Yes, one interior and one exterior on both sides of cab
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Yes
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes, integral
Radio	AM/FM	Yes, AM/FM
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes, air suspension driver and passenger / black vinyl
Safety		
Brakes	Air Brakes W/ 12 cu ft. Compressor W/ Air Dryer & Drain Valve	Yes, air brake w/ 18.7 cfm compressor w/ air dryer and drain valve
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	HMX 400 w/shocks
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	12R/22 5/14 Ply/ Load G	315/80R22.5 / 16 ply / load H
Tires, Tubeless, Size/Tread Rear	11R/22 5/14 Ply/ Load G, Mud/Snow Tread	11R22.5 / 20 ply / load L, mud and snow tread
Warranty		
2 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	1 year / unlimited mileage, towing covered under engine and transmission warranty
PURCHASE PRICE:		\$156,934.00
3 YR LEASE/MO		N/A
4 YR LEASE/MO		N/A
5 YR LEASE/MO		N/A
MSRP FOR PURCHASE PRICE:		\$244,522.00

Item # 1000009383
Medium Duty, 46,000 -
54,000 # Truck

Dealer Name: Summit Truck Group

Make Bidding: Crane Carrier

Model Bidding: LET2 40 Year 2017

Model Code: LET2 46-54K

Engines	Options		Purchase	3 YR Lease	4 YR Lease	5 YR Lease
Gas Engine	List Specs	Not Available		N/A	N/A	N/A
Diesel Engine	330HP/900 LBFT	Cummins 330HP in lieu of ISL9 300HP	N/A	N/A	N/A	
Software/Cable	Software/Cable	Cummins insite	N/A	N/A	N/A	
CNG Engine	BiFuel - List Capacities	Not Available	N/A	N/A	N/A	
CNG Engine	Dedicated - List Capacity	ISLG 320HP in lieu of ISL9 300HP	N/A	N/A	N/A	
Air Cleaner System	Higher Capacity - List Additional Capacity	Not Available	N/A	N/A	N/A	
Dust Shield	Dust Shield for Snow Removal Operations	Not Available	N/A	N/A	N/A	
Transmission						
Delete Front PTO	Delete Front PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille	PTO crossmember sets under cab not requiring a front bumper extension.	N/A	N/A	N/A	
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Not available	N/A	N/A	N/A	
Front Axle						
Front Axle	12000 lb W/ 12000 Springs	Not available	N/A	N/A	N/A	
Front Axle	16000 lb w/ 16,000 Springs	Not available	N/A	N/A	N/A	
Front Axle	18000 lb with 18000 Springs	20,000 lb with 17,000 Springs	N/A	N/A	N/A	
Body & Chassis						
CA	Increase to 120" CA, Clear		N/A	N/A	N/A	
CA	Increase to 138" CA, Clear	140" CA	N/A	N/A	N/A	
CA	Increase to 150" CA, Clear	152" CA	N/A	N/A	N/A	
CA	Increase to 186" CA, Clear	188"	N/A	N/A	N/A	
Body	4 Door Crew Cab	2-door. 4 man seating all facing forward, all with seat belts	N/A	N/A	N/A	
Frame	Delete Frame Reinforcement C Channel Type. 120,000 PSI	120,000 PSI is Standard	N/A	N/A	N/A	
Frame	Front Frame Extension W/O PTO Adaptor	Swept Back Bumper	N/A	N/A	N/A	
Axle, Min Front Rating/lb/seals	12,000/Oil,with Springs	20,000, with springs on spec	N/A	N/A	N/A	
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil, with Articulating Susp.	Dana DS 405P with HN Suspension	N/A	N/A	N/A	
Electrical						
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	Leece Neville 210 Amp	N/A	N/A	N/A	
Worklights	Worklight Accomodation Package, List Specs	2 Spare Rocker Switches in Dash	N/A	N/A	N/A	
Exterior						
Screen	Grille Mounted Bug Screen	Not required with remote mounted radiator behind the cab.	N/A	N/A	N/A	
Mirrors	Heated Mirrors	Included in spec	N/A	N/A	N/A	
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Any custom color excluding metallic	N/A	N/A	N/A	
Exhaust	Horizontal	Vertical Only	N/A	N/A	N/A	
Grille	Stationary Grille	No grille required with remote mounted radiator behind the cab.	N/A	N/A	N/A	
Interior						
AC	Delete AC	No A/C	N/A	N/A	N/A	
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	2-door. 4 man seating all facing forward, all with seat belts	N/A	N/A	N/A	
Tilt & Cruise	Tilt Wheel & Cruise Control	Tilt Wheel & Cruise Control	N/A	N/A	N/A	
Safety	Air Bag Both Sides	Not available	N/A	N/A	N/A	
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	Not available	N/A	N/A	N/A	
Keys	3 Additional Keys Per Truck	Included in spec	N/A	N/A	N/A	
Visor	Visor over Windshield	Steel	N/A	N/A	N/A	
Tire Inflator Tool	Air Cab Blower with Tire Inflator Tool	Not available	N/A	N/A	N/A	
Safety						
Alarm	Park Brake Alarm	Standard	N/A	N/A	N/A	
Hydraulic Brakes	Deduct for Hydraulic Brakes	Not available	N/A	N/A	N/A	
Tires & Wheels						
Tires	Rear Tires, Highway tread	Bridgestone R250 H/16	N/A	N/A	N/A	
Spare Wheel	Steel Spare Wheel	22.5X9" Steel Disc	N/A	N/A	N/A	
Tires for 14,000 lb Axle	List Specs	Not available	N/A	N/A	N/A	
Tires for 16,000 lb Axle	List Specs	Not available	N/A	N/A	N/A	
Tires for 18,000 lb Axle	List Specs	Not available	N/A	N/A	N/A	
Towing						
Hooks	Front Tow Hooks	Tow Pins	N/A	N/A	N/A	
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring		N/A	N/A	N/A	
Delivery						
Delivery Cost	Price to Deliver Truck more than 150 miles	\$3.00 Per Mile	\$3.00 per mile			
Other						
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	2% for 5 or more				
Options not listed	Discount off MSRP for options not listed	40%				

Item # 1000029768
Medium Duty, 54,000 -
66,000 # Truck

Summit Truck Group

Make Bidding: Crane Carrier
Model Bidding: LET2-46 Year 2017
Model Code: LET2 54-66K

Can this Vehicle come ALT
Fuel Equipped?? YES/NO:

Yes

Body & Chassis	Minimum Specification	
GVWR	66,000	66,000# GVWR
Curb Weight/Payload	Mfg. Std. List Size	18,973 lbs. Chassis / 47,027 lbs. Payload
Chassis CA	194" CA, Clear Frame Rail	Yes, additional CA available, see option page
Style, Cab/Tilt Hood	Tilt Hood or Low Cab Forward, List	Yes, low entry 18" step in height, tilt cab
Axle, Min Front Rating/lb/seals	20,000/LB with Springs	20,000lb
Axle, Min Rear Rating/lb/spd/seals	46,000 LBS/Oil, with Walking Beam Type	46,000lb
Frame, RBM, Min, in-lb	3,200,000 Double Frame "C" Channel Reinforcement	Yes, 3,389,600 w/ "C" channel reinforcement
Cab Mounts	Air Ride Cab	Not available on low entry models
Engine		
Engine Type	Diesel Turbocharged	Yes, Diesel
Engine Cyl/GHP/Gross Torque, Min	Inline 6 Cyl / 8 Liter or Larger / 1350 LBFT	Inline 6 cylinder / 9 liter / 370 / 1250lb ft. @ 1,400 rpm
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press	Yes
Air Cleaner System	List Capacity	Echo XL 13-S
Transmission		
Trans. Type/Speeds, Min	Allison 4500RDS 6 Spd	Yes, Allison 4500RDS 6-speed
Transmission ECU	Mounted in Cab	Mounted at transmission
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory Install. Include "C" Reinforcement to front	Yes, front bumper extension not required
PTO	R/Lt Side 10 bolt	Yes, right/left side - 10 bolt
Electrical		
Alternator/Rating Cap/Min (amps)	12 Volt/ 130 Amp	Yes, 12V / 160 amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	Yes, Two - 1850 CCA total
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Block Heater Min.	1000 Watt	Yes, 1,000 watt
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		Yes, HD steel header console
Body Builder Wiring to Rear of Frame		Yes
Power Supply	12 Volt Power Supply in Dash	Yes, 12V in dash
Fuel		
Fuel Tank Capacity	80 Gallon Minimum	Yes, 80 gallon
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes, 12V heated
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 1 Electric Horn	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes, power and heated, both sides
Grill	Chrome Grille Mount Bug Screen	Not required, remote mounted radiator behind cab
Courtesy Lights	Mounted Below Each Door	Not required on low entry
Handles	Grab Handles Both Sides	Yes, one interior and one exterior on both sides of cab
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Yes
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes, integral
Radio	AM/FM	Yes, AM/FM
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min.	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes, air suspension driver and passenger / black vinyl
Safety		
Brakes	Air Brakes W/ Compressor W/ Air Dryer & Drain Valve, 16.5 in x 5 in	Yes, air brakes w/ 18.7 cfm compressor w/ air dryer and drain valve
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	HN-460 w/ shocks
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	20 Ply, 315/80R 22.5	315/80R22.5 / 20 ply / load L / Bridgestone M860
Tires, Tubeless, Size/Tread Rear	11R22.5/14 Ply/ Load G, Mud/Snow Tread	11R22.5 / 16 ply / load H / Bridgestone L320 mud and snow tread
Warranty		
2 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	1 year / unlimited mileage, towing covered under engine and transmission warranty
PURCHASE PRICE:		\$156,934.00
3 YR LEASE/MO		N/A
4 YR LEASE/MO		N/A
5 YR LEASE/MO		N/A
MSRP FOR PURCHASE PRICE:		\$244,522.00

Item # 1000029768

Dealer Name: Summit Truck GroupMedium Duty, 54,000
- 66,000 # TruckMake Bidding: Crane CarrierModel Bidding: LET2-46 Year 2017Model Code: LET2 54-66K

Engines	Options		Purchase	3 YR Lease	4 YR Lease
Gas Engine	List Specs	Not Available		N/A	N/A
Diesel Engine	330HP/900 LBFT	Cummins 330 HP in lieu of ISL9 370 HP	-\$4,553	N/A	N/A
Software/Cable	Software/Cable	Cummins insite	\$3,000	N/A	N/A
CNG Engine	BiFuel - List Capacities	Not Available		N/A	N/A
CNG Engine	Dedicated - List Capacity	ISLG 320 HP in lieu of ISL9 370 HP	-\$2,732	N/A	N/A
Air Cleaner System	Higher Capacity - List Additional Capacity	Not Available		N/A	N/A
Dust Shield	Dust Shield for Snow Removal Operations	Not Available		N/A	N/A
Transmission					
Front PTO	Front Mounted PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille. Factory Install Include "C" Reinforcement to Front	PTO crossmember sets under cab not requiring a front bumper extension	STD	N/A	N/A
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Not Available		N/A	N/A
Front Axle					
Front Axle	16000 lb w/ 16,000 Springs	Not Available		N/A	N/A
Front Axle	18000 lb with 18000 Springs	20,000 lb with 20,000 lb springs	STD	N/A	N/A
Body & Chassis					
CA	Decrease to 120" CA, Clear	Not Available		N/A	N/A
CA	Decrease to 138" CA, Clear	140" CA	No Charge	N/A	N/A
CA	Decrease to 150" CA, Clear	152" CA	\$490	N/A	N/A
CA	Decrease to 186" CA, Clear	188" CA	\$1,080	N/A	N/A
Body	4 Door Crew Cab	2-door, 4 man seating all facing forward, all with seat belts	\$6,235	N/A	N/A
Frame	Delete Frame Reinforcement C Channel Type. 120,000 PSI	120,000 psi is standard	STD	N/A	N/A
Frame	Front Frame Extension W/O PTO Adaptor	Swept back bumper	\$510	N/A	N/A
Axle, Min Front Rating/lb/seals	12,000/Oil,with Springs	20,000 lb with springs on spec		N/A	N/A
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil, with Articulating Susp.	D46-170P with HN suspension	STD	N/A	N/A
Electrical					
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	Leece Neville 210 amp	\$140	N/A	N/A
Worklights	Worklight Accomodation Package, List Specs	2 spare rocker switches in dash	STD	N/A	N/A
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Electrical switch and wiring	\$430	N/A	N/A
Exterior					
Screen	Grille Mounted Bug Screen	Not required with remote mounted radiator behind the cab		N/A	N/A
Mirrors	Heated Mirrors	Included in spec		N/A	N/A
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Any custom color excluding metallic	\$470	N/A	N/A
Exhaust	Horizontal	Vertical only		N/A	N/A
Grille	Stationary Grille	No grille required with remoute mounted radiator behind the cab		N/A	N/A
Interior					
AC	Delete AC	No A/C	\$1,590	N/A	N/A
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	2-door, 4 man seating all facing forward, all with seat belts		N/A	N/A
Tilt & Cruise	Tilt Wheel & Cruise Control	Tilt wheel & Cruise control	STD	N/A	N/A
Safety	Air Bag Both Sides	Not Available		N/A	N/A

Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	Not Available		N/A	N/A
Keys	3 Additional Keys Per Truck	Included in spec		N/A	N/A
Visor	Visor over Windshield	Steel	\$2,000	N/A	N/A
Tire Inflator Tool	Air Cab Blower with Tire Inflator Tool	Not Available		N/A	N/A
Windows	Power Windows	Electric windows (each)	\$455	N/A	N/A
Refuse Electronics Package	All items necessary for Refuse Package	Included in spec		N/A	N/A
Safety					
Alarm	Park Brake Alarm	Standard	STD	N/A	N/A
Hydraulic Brakes	Deduct for Hydraulic Brakes	Not Available		N/A	N/A
Tires & Wheels					
Tires	Rear Tires, Highway tread	Bridgestone R250 H/16	-\$691	N/A	N/A
Spare Wheel	Steel Spare Wheel	22.5x9 steel disc	\$195	N/A	N/A
Tires for 14,000 lb Axle	List Specs	Not Available		N/A	N/A
Tires for 16,000 lb Axle	List Specs	Not Available		N/A	N/A
Tires for 18,000 lb Axle	List Specs	Not Available		N/A	N/A
Towing					
Hooks	Front Tow Hooks	Tow pins	\$110	N/A	N/A
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring		\$1,100	N/A	N/A
Delivery					
Delivery Cost	Price to Deliver Truck more than 150 miles	\$ 3.00 per mile	\$ 3.00 per mile		
Other					
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	2% for 5 or more			
Options not listed	Discount off MSRP for options not listed	40%			

Item # 100009383
Medium Duty, 46,000 -
54,000 # Truck

Dealer Name: Summit Truck Group
Make Bidding: Crane Carrier
Model Bidding: COE2-40 Year 2017
Model Code: COE2 46-54K
Yes

LT Fuel Equipped?? YES/NO:

Body & Chassis	Standard Specification	
GWR	54,000	46,000 - 54,000
Curb Weight/Payload	Mfg. Std. List Size	17,157 lbs. Chassis / 36,843 lbs. Payload
Chassis CA	102" CA, Clear Frame Rail	Yes, additional CA available, see options page
Style, Cab/Tilt Hood	Tilt Hood	Yes, cab over, tilt cab
Axle, Min Front Rating/lb/seals	14,000/ LB, with Springs	20,000 lbs.
Axle, Min Rear Rating/lb/spd/seals	40,000 LBS/Oil, with Walking Beam Type	40,000 lbs.
Frame, RBM, Min, in-lb	3,200,000 Double Frame "C" Channel Reinforcement	Yes, 3,369,600 w/ "C" channel reinforcement
Cab Mounts	Air Ride Cab	Not available on cab over models
Engine		
Engine Type	Diesel Turbocharged	Diesel
Engine Cyl/GHP/Gross Torque, Min	Inline 6 Cyl / 8 Liter or Larger / 850LBFT	Inline 6 cylinder / ISL9-300 HP / 860 torque
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press.	Yes
Air Cleaner System	List Capacity	Echo XL 13-S
Transmission		
Trans. Type/Speeds, Min.	Allison 3000RDS 6 Spd.	Allison 3000RDS 6 speed
Transmission ECU	Mounted in Cab	Mounted at transmission
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory install. Include "C" Reinforcement to front	No. Front PTO mount not available.
PTO	Rt/Lt Side 10 bolt	Yes, right/left side - 10 bolt
Electrical		
Alternator/Rating Cap Min (amps)	12 Volt/ 130 Amp	Yes, 12V / 160 amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	Yes, Two - 1850 CCA total
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Block Heater Min.	1000 Watt	Yes, 1000 watt
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		Yes, HD steel header console
Body Builder Wiring to Rear of Frame		Yes
Power Supply	12 Volt Power Supply in Dash	Yes, 12V in dash
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Yes
Fuel		
Fuel Tank Capacity	100 Gallon Minimum	80 gallon
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes, 12V heated
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 2 Electric Horn	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes, power and heated, right and left
Grill	Chrome Grille Mount Bug Screen	Not required, remote mounted radiator behind cab
Courtesy Lights	Mounted Below Each Door	Yes
Handles	Grab Handles Both Sides	Yes, one interior and one exterior on both sides of cab
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Yes
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes, integral
Radio	AM/FM	Yes, AM/FM
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes, air suspension driver and passenger / black vinyl
Safety		
Brakes	Air Brakes W/ 12 cu ft. Compressor W/ Air Dryer & Drain Valve	Yes, air brake w/ 18.7 cfm compressor w/ air dryer and drain valve
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	HMX 400 w/shocks
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	12R/22.5/14 Ply/ Load G	315/80R22.5 / 16 ply / load H
Tires, Tubeless, Size/Tread Rear	11R/22.5/14 Ply/ Load G, Mud/Snow Tread	11R22.5 / 20 ply / load L, mud and snow tread
Warranty		
2 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	1 year / unlimited mileage, towing covered under engine and transmission warranty
PURCHASE PRICE:		\$137,351.00
3 YR LEASE/MO		N/A
4 YR LEASE/MO		N/A
5 YR LEASE/MO		N/A
MSRP FOR PURCHASE PRICE:		\$213,190.00

Item # 100009383
Medium Duty, 46,000 -
54,000 # Truck

Dealer Name: Summit Truck Group

Make Bidding: Crane Carrier

Model Bidding: COE2 40 Year 2017

Model Code: COE2 46-54K

Engines	Options		Purchase	3 YR Lease	4 YR Lease	5 YR Lease
Gas Engine	List Specs	Not Available		N/A	N/A	N/A
Diesel Engine	330HP/900 LBFT	Cummins 330HP in lieu of ISL9 300HP	\$1,520	N/A	N/A	N/A
Software/Cable	Software/Cable	Cummins insite	\$3,000	N/A	N/A	N/A
CNG Engine	BIFuel - List Capacities	Not Available		N/A	N/A	N/A
CNG Engine	Dedicated - List Capacity	ISLG 320HP in lieu of ISL9 300HP	\$3,350	N/A	N/A	N/A
Air Cleaner System	Higher Capacity - List Additional Capacity	Not Available		N/A	N/A	N/A
Dust Shield	Dust Shield for Snow Removal Operations	Not Available		N/A	N/A	N/A
Transmission						
Delete Front PTO	Delete Front PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille	Front mounted PTO not available with Cab Over Chassis		N/A	N/A	N/A
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Not available		N/A	N/A	N/A
Front Axle						
Front Axle	12000 lb W/ 12000 Springs	Not available		N/A	N/A	N/A
Front Axle	16000 lb w/ 16,000 Springs	Not available		N/A	N/A	N/A
Front Axle	18000 lb with 18000 Springs	20,000 lb with 17,000 Springs	STD	N/A	N/A	N/A
Body & Chassis						
CA	Increase to 120" CA, Clear	120" CA	NC	N/A	N/A	N/A
CA	Increase to 138" CA, Clear	138" CA	NC	N/A	N/A	N/A
CA	Increase to 150" CA, Clear	150" CA	\$490	N/A	N/A	N/A
CA	Increase to 186" CA, Clear	186" CA	\$1,218	N/A	N/A	N/A
Body	4 Door Crew Cab	2 Man Only in Cab Over		N/A	N/A	N/A
Frame	Delete Frame Reinforcement C Channel Type. 120,000 PSI	120,000 PSI is Standard	STD	N/A	N/A	N/A
Frame	Front Frame Extension W/O PTO Adaptor	Front mounted PTO not available with Cab Over Chassis		N/A	N/A	N/A
Axle, Min Front Rating/lb/seals	12,000/Oil, with Springs	20,000, with springs on spec		N/A	N/A	N/A
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil, with Articulating Susp.	Dana DS 405P with HN Suspension	STD	N/A	N/A	N/A
Electrical						
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	Leece Neville 210 Amp	\$140	N/A	N/A	N/A
Worklights	Worklight Accomodation Package, List Specs	2 Spare Rocker Switches in Dash	STD	N/A	N/A	N/A
Exterior						
Screen	Grille Mounted Bug Screen	Not Available		N/A	N/A	N/A
Mirrors	Heated Mirrors	Included in spec		N/A	N/A	N/A
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Any custom color excluding metallic	\$470	N/A	N/A	N/A
Exhaust	Horizontal	Vertical Only		N/A	N/A	N/A
Grille	Stationary Grille	Standard with Cab Over	STD	N/A	N/A	N/A
Interior						
AC	Delete AC	No A/C	\$1,590	N/A	N/A	N/A
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	2 Man Only in Cab Over		N/A	N/A	N/A
Tilt & Cruise	Tilt Wheel & Cruise Control	Tilt Wheel & Cruise Control	STD	N/A	N/A	N/A
Safety	Air Bag Both Sides	Not available		N/A	N/A	N/A
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	Not available		N/A	N/A	N/A
Keys	3 Additional Keys Per Truck	Included in spec		N/A	N/A	N/A
Visor	Visor over Windshield	Steel	\$2,000	N/A	N/A	N/A
Tire Inflator Tool	Air Cab Blower with Tire Inflator Tool	Not available		N/A	N/A	N/A
Safety						
Alarm	Park Brake Alarm	Standard	STD	N/A	N/A	N/A
Hydraulic Brakes	Deduct for Hydraulic Brakes	Not available		N/A	N/A	N/A
Tires & Wheels						
Tires	Rear Tires, Highway tread	Bridgestone R250 H/16	-\$691	N/A	N/A	N/A
Spare Wheel	Steel Spare Wheel	22.5X9" Steel Disc	\$195	N/A	N/A	N/A
Tires for 14,000 lb Axle	List Specs	Not available		N/A	N/A	N/A
Tires for 16,000 lb Axle	List Specs	Not available		N/A	N/A	N/A
Tires for 18,000 lb Axle	List Specs	Not available		N/A	N/A	N/A
Towing						
Hooks	Front Tow Hooks	Tow Loops	STD	N/A	N/A	N/A
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring		\$1,100	N/A	N/A	N/A
Delivery						
Delivery Cost	Price to Deliver Truck more than 150 miles	\$3.00 Per Mile	\$3.00 per mile			
Other						
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	2% for 5 or more				
Options not listed	Discount off MSRP for options not listed	40%				

Item # 1000029768
Medium Duty, 54,000 -
66,000 # Truck

Summit Truck Group

Make Bidding: Crane Carrier
Model Bidding: COE2-46 Year 2017
Model Code: COE2-54-66K

Can this Vehicle come ALT?
Fuel Equipped?? YES/NO:

Yes

Body & Chassis	Minimum Specification	
GVWR	66,000	66,000# GVWR
Curb Weight/Payload	Mfg. Std. List Size	18,073 lbs. Chassis / 47,927 lbs. Payload
Chassis CA	194" CA, Clear Frame Rail	Yes, additional CA available, see option page
Style, Cab/Tilt Hood	Tilt Hood or Low Cab Forward, List	Yes, cab over / tilt cab
Axle, Min Front Rating/lb/seals	20,000/ LB,with Springs	20,000lb
Axle, Min Rear Rating/lb/spd/seals	46,000 LBS/Oil, with Walking Beam Type	46,000lb
Frame, RBM, Min, in-lb	3,200,000 Double Frame "C" Channel Reinforcement	Yes, 3,369,600 w/ "C" channel reinforcement
Cab Mounts	Air Ride Cab	Not available on cab over models
Engine		
Engine Type	Diesel Turbocharged	Yes, Diesel
Engine Cyl/GHP/Gross Torque, Min	Inline 6 Cyl / 8 Liter or Larger / 1350 LBFT	Inline 6 cylinder / 9 liter / 370 / 1250lb ft. @ 1,400 rpm
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press	Yes
Air Cleaner System	List Capacity	Echo XL 13-S
Transmission		
Trans, Type/Speeds, Min	Allison 4500RDS 6 Spd	Yes, Allison 4500RDS 6-speed
Transmission ECU	Mounted in Cab	Mounted at transmission
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory Install. Include "C" Reinforcement to front	No. Front PTO mount not available.
PTO	Rt/Lt Side 10 bolt	Yes, right/left side - 10 bolt
Electrical		
Alternator/Rating CapMin (amps)	12 Volt/ 130 Amp	Yes, 12V / 160 amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	Yes, Two - 1850 CCA total
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Block Heater Min	1000 Watt	Yes, 1,000 watt
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		Yes, HD steel header console
Body Builder Wiring to Rear of Frame		Yes
Power Supply	12 Volt Power Supply in Dash	Yes, 12V in dash
Fuel		
Fuel Tank Capacity	80 Gallon Minimum	Yes, 80 gallon
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes, 12V heated
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 1 Electric Horn	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes, power and heated, both sides
Grill	Chrome Grille Mount Bug Screen	Yes
Courtesy Lights	Mounted Below Each Door	Yes
Handles	Grab Handles Both Sides	Yes, one interior and one exterior on both sides of cab
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Yes
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes, Integral
Radio	AM/FM	Yes, AM/FM
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min.	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes, air suspension driver and passenger / black vinyl
Safety		
Brakes	Air Brakes W/ Compressor W/ Air Dryer & Drain Valve, 16.5 x 5 in	Yes, air brakes w/ 18.7 cfm compressor w/ air dryer and drain valve
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	HMX-460 w/ shocks
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	20 Ply, 315/80R 22.5	315/80R22.5 / 20 ply / load L / Bridgestone M860
Tires, Tubeless, Size/Tread Rear	11R/22.5/14 Ply/ Load G, Mud/Snow Tread	11R22.5 / 16 ply / load H / Bridgestone L320 mud and snow tread
Warranty		
2 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	1 year / unlimited mileage, towing covered under engine and transmission warranty
PURCHASE PRICE:		\$154,441.00
3 YR LEASE/MO		N/A
4 YR LEASE/MO		N/A
5 YR LEASE/MO		N/A
MSRP FOR PURCHASE PRICE:		\$240,413.00

Item # 1000029768
Medium Duty, 54,000 -
66,000 # Truck

Dealer Name: Summit Truck Group

Make Bidding: Crane Carrier

Model Bidding: COE2-46 Year 2017

Model Code: COE2-54-66K

Year 2017

Engines	Options		Purchase	3 YR Lease
Gas Engine	List Specs	Not Available		N/A
Diesel Engine	330HP/900 LBFT	Cummins 330 HP in lieu of ISL9 370 HP	-\$4,553	N/A
Software/Cable	Software/Cable	Cummins insite	\$3,000	N/A
CNG Engine	BiFuel - List Capacities	Not Available		N/A
CNG Engine	Dedicated - List Capacity	ISLG 320 HP in lieu of ISL9 370 HP	-\$2,732	N/A
Air Cleaner System	Higher Capacity - List Additional Capacity	Not Available		N/A
Dust Shield	Dust Shield for Snow Removal Operations	Not Available		N/A
Transmission				
Front PTO	Front Mounted PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille, Factory Install Include "C" Reinforcement to Front	Front mounted PTO not available with Cab Over Chassis		N/A
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Not Available		N/A
Front Axle				
Front Axle	16000 lb w/ 16,000 Springs	Not Available		N/A
Front Axle	18000 lb with 18000 Springs	20,000 lb. with 17,000 lb springs	STD	N/A
Body & Chassis				
CA	Decrease to 120" CA, Clear	120" CA	No Charge	N/A
CA	Decrease to 138" CA, Clear	138" CA	No Charge	N/A
CA	Decrease to 150" CA, Clear	150" CA	\$490	N/A
CA	Decrease to 186" CA, Clear	186" CA	\$1,218	N/A
Body	4 Door Crew Cab	2 man only in Cab Over Chassis		N/A
Frame	Delete Frame Reinforcement C Channel Type. 120,000 PSI	120,000 psi is standard	STD	N/A
Frame	Front Frame Extension W/O PTO Adaptor	Front mounted PTO not available with Cab Over Chassis		N/A
Axle, Min Front Rating/lb/seals	12,000/Oil,with Springs	20,000 lb. with springs on spec		N/A
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil, with Articulating Susp.	D46-170P with HN suspension	STD	N/A
Electrical				
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	Leece Neville 210 amp	\$140	N/A
Worklights	Worklight Accommodation Package, List Specs	2 spare rocker switches in dash	STD	N/A
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Electrical switch and wiring	\$430	N/A
Exterior				
Screen	Grille Mounted Bug Screen	Not Available		N/A
Mirrors	Heated Mirrors	Included in spec		N/A
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Any custom color excluding metallic	\$470	N/A
Exhaust	Horizontal	Vertical only		N/A
Grille	Stationary Grille	Standard with Cab Over Chassis	STD	N/A
Interior				
AC	Delete AC	No A/C	\$1,590	N/A
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	2 man only in Cab Over Chassis		N/A
Tilt & Cruise	Tilt Wheel & Cruise Control	Tilt wheel & Cruise control	STD	N/A
Safety	Air Bag Both Sides	Not Available		N/A
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	Not Available		N/A
Keys	3 Additional Keys Per Truck	Included in spec		N/A
Visor	Visor over Windshield	Steel	\$2,000	N/A