

Item # 100029768
 Medium Duty, 54,000 -
 66,000 # Truck

Rush Truck Center

Make Bidding: _____
 Model Bidding: _____
 Model Code: _____

567
 567

Can this Vehicle come ALT
 Fuel Equipped?? YES/NO:

YES

Body & Chassis	Minimum Specification	
GVMR	66,000	Yes (Peterbilt 567 Model)
Curb Weight/Payload	Mfg. Std. List Size	10581lbs (curb weight) / 40410 lbs (payload)
Chassis CA	194" CA, Clear Frame Rail	Yes
Style, Cab/Tilt Hood	Tilt Hood or Low Cab Forward, List	Tilt Hood
Axle, Min Front Rating/lb/seats	20,000/LB with Springs	Yes
Axle, Min Rear Rating/lb/seats	40,000 LBS/Oil, with Walking Beam Type	Yes
Frame, RBM, Min, in-b	3,200,000 Double Frame "C" Channel Reinforcement	Yes
Cab Mounts	Air Ride Cab	Yes
Engine		
Engine Type	Diesel Turbocharged	Yes
Engine Cyl/HP/Gross Torque, Min	Inline 6 Cyl / 8 Liter or Larger / 1350 LBFT	Peccar MXC 455/1650 Lb/Tq
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press.	Yes
Air Cleaner System	List Capacity	Donaldson Inwell mounted air cleaner
Transmission		
Trans. Type/Speeds, Mtr.	Allison 4500RDS 6 Spd.	Yes
Transmission ECU	Mounted in Cab	Yes
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory Install. Include "C" Reinforcement to front	N/A with the model
PTO	R/L Side 10 boll.	Yes
Electrical		
Alternator/Rating Cap/Min (amps)	12 Volt/ 130 Amp	Peccar 180 Amp Brushed
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	(3) Peccar Dual Purpose Batt 2100 CCA
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Saut	Mounted Outside Battery Box	Yes
Block Heater Min.	1000 Watt	Immersion Type Block Heater 110-120V
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		Yes
Body Builder Wiring to Rear of Frame		5' BDC Body builder wiring
Power Supply	12 Volt Power Supply in Dash	Yes
Fuel		
Fuel Tank Capacity	80 Gallon Minimum	Yes
Fuel Filters	Primary & Fuel Water Separator Heated	Yes
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 1 Electric Horn	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes
Grill	Chrome Grille Mount Bug Screen	Yes
Courtesy Lights	Mounted Below Each Door	Yes
Handles	Grab Handles Both Sides	Yes
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Power door locks and power windows (standard equipment)
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes
Radio	AM/FM	Yes
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min.	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes
Safety		
Brakes	Air Brakes W/ Compressor W/ Air Dryer & Drain Valve, 10.5 in x 5 in	Yes
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	Hendrickson Haulmax HMX 460 46,000lb
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	20 Ply, 315/80R 22.5	Yes
Tires, Tubeless, Size/Tread Rear	11R/22.5/14 Ply/Load G, Mud/Snow Tread	Yes
Warranty		
2 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	2 year towing with engine or transmission failure only
PURCHASE PRICE		\$130,995.00
3 YR LEASE/MO		\$0.00
4 YR LEASE/MO		\$0.00
5 YR LEASE/MO		\$0.00
MSRP FOR PURCHASE PRICE		\$168,114.00

Item # 1000029768
 Medium Duty, 54,000 -
 66,000 # Truck

Dealer Name: Rush Truck Center

Make Bidding: 567

Model Bidding: ~~567~~ 567

Model Code: 567

Engines	Options	
Gas Engine	List Specs	N/A
Diesel Engine	330HP/900 LBFT	Cummins X15 450V/1650 Lb/Ft Tq.
Software/Cable	Software/Cable	J-Pro DLA Reader
CNG Engine	BiFuel - List Capacities	N/A
CNG Engine	Dedicated - List Capacity	Cummins L9N 320 HP
Air Cleaner System	Higher Capacity - List Additional Capacity	Standard equipment
Dust Shield	Dust Shield for Snow Removal Operations	Dust shields Cam brakes front and rear axle
Transmission		
Front PTO	Front Mounted PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille, Factory Install Include "C" Reinforcement to Front	N/A with this model
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Fuller FRO16210C-10 Speed Manual
Front Axle		
Front Axle	16000 lb w/ 16,000 Springs	14,600lb front axle
Front Axle	18000 lb with 18000 Springs	N/A
Body & Chassis		
CA	Decrease to 120" CA, Clear	Yes
CA	Decrease to 138" CA, Clear	Yes
CA	Decrease to 150" CA, Clear	Yes
CA	Decrease to 186" CA, Clear	yes
Body	4 Door Crew Cab	N/A with this model
Frame	Delete Frame Reinforcement C Channel Type. 120,000 PSI	Yes
Frame	Front Frame Extension W/O PTO Adaptor	N/A with this model
Axle, Min Front Rating/lb/seals	12,000/Oil, with Springs	Yes
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil, with Articulating Susp.	Yes
Electrical		
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	275 Amp 40 SI Brushless
Worklights	Worklight Accomodation Package, List Specs	
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Installed @ dealership
Exterior		
Screen	Grille Mounted Bug Screen	Yes
Mirrors	Heated Mirrors	Standard equipment
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Yes
Exhaust	Horizontal	Yes
Grille	Stationary Grille	Yes

Interior		
AC	Delete AC	Standard equipment
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	Yes Non-air 2 passenger bench
Tilt & Cruise	Tilt Wheel & Cruise Control	Tilt and telescope steering
Safety	Air Bag Both Sides	N/A
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	Yes std equipment with this model
Keys	3 Additional Keys Per Truck	Yes
Visor	Visor over Windshield	Stainless Steel Visor
Tire Inflator Tool	Air Cab Blower with Tire Inflator Tool	Installed @ dealership
Windows	Power Windows	Standard Equipment
Refuse Electronics Package	All items necessary for Refuse Package	
Safety		
Alarm	Park Brake Alarm	Standard equipment
Hydraulic Brakes	Deduct for Hydraulic Brakes	N/A
Tires & Wheels		
Tires	Rear Tires, Highway tread	Yes
Spare Wheel	Steel Spare Wheel	yes
Tires for 14,000 lb Axle	List Specs	16 Ply 12R22.5
Tires for 16,000 lb Axle	List Specs	Axle N/A
Tires for 18,000 lb Axle	List Specs	Axle N/A
Towing		
Hooks	Front Tow Hooks	Standard Equipment
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring	Hand valve plumbed to rear service brakes w/7way A&E to EOF
Delivery		
Delivery Cost	Price to Deliver Truck more than 150 miles	
Other		
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	N/A
Options not listed	Discount off MSRP for options not listed	25% off list

567 MODEL
54. 66,000 lb.



Rush Pblt Truck Centers (O500)
8700 West I-40
Oklahoma City, Oklahoma 73128

Stock

Chaz Eubank
Cell Phone: 405-782-3502
Office Phone: 405-782-3500
Email: eubankc@rush-enterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 567	Fr Axle Load (lbs):	20000
Type:	Tractor	Rr Axle Load (lbs):	46000
Description 1:	OMES 567	G.C.W. (lbs):	66000
Description 2:			
Intended Serv.:	Application	Road Conditions:	
Commodity:	General Freight	Class A (Highway)	100
	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
	Body	Class D (Off-Road)	0
Type:		Maximum Grade:	6
Length (ft):	0	Wheelbase (in):	226
Height (ft):	0	Overhang (in):	55
Max Laden Weight (lbs):	0	Fr Axle to BOC (in):	68.2
		Cab to Axle (in):	157.8
	Trailer	Cab to EOF (in):	212.8
No. of Trailer Axles:	3	Overall Comb. Length (in):	717.23
Type:	Flatbed		
Length (ft):	40	Special Req.	
Height (ft):	8		
Kingpin Inset (in):	36		
Corner Radius (in):	2		
	Restrictions		
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	Weight
Base Model			
0005671	S	Model 567 The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	14,860
0091200	S	Other Commodity	0
0093170	S	General Freight Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0
0096060	O	Flatbed A flat trailer with no enclosure or doors. Can be loaded/unloaded from the sides or above, and does not require elevated access for forklifts.	0
0098170	O	United States Registry	0
Configuration			
0200700	S	Not Applicable Secondary Manufacturer	0
Frame & Equipment			
0515020	O	10-5/8" Steel Rails 286-325" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	147
0601500	O	Full Steel Inner Liner	659
0611250	O	Heavy-Duty Iron Front Spring Brackets Forward and Rear	35
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0
0644000	S	EOF Tractor Tapered with Crossmember Includes Kingpin Cutout	0
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0
0854010	S	Fifth Wheel Not Furnished	0
0940330	S	No Access Package or Deckplate Desired Use with tractors without access package or deckplate	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
Front Axle & Equipment			
1011360	O	Dana Spicer D2000F 20,000 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	111
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	119
1243050	O	Power Steering Sheppard HD94 Dual For use with 16,000 to 20,000 lb. axle ratings.	80
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	2
1354850	O	PHP10 Iron PreSet PLUS Hubs-Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	42
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0
1391060		50mm Front Spring Spacer Blocks	0
Rear Axle & Equipment			
1523440	O	Dana Spicer D46-172 46,000 LBS Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity.	521
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0
1680390	S	Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0
1680450	O	Rear Brake Camshaft Reinforcement	9

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
		Rear brake camshaft reinforcement helps guard against wear and corrosion.	
1680460	O	Heavy Wall, Drive Axle(s)	88
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1704560	O	Ratio 4.56 Rear Axle	0
1824440	O	Hendrickson HMX EX 460 46,000 LBS., 52" Haulmax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	202
1921375	O	16.5" Saddle Height HMX EX 400/460 IPO Std 18.5"	0

Engine & Equipment

2072820	S	PACCAR MX-13 455@1600 GV@2200 1650@900 The PACCAR MX Engine boasts a B10 design life of one million miles in linehaul applications. This means 90 percent of PACCAR MX Engines will log up to one million miles without a major overhaul, almost double the life of comparable engines. The PACCAR MX Engines B10 design life stands as the pinnacle of our promise to you a lifetime of unparalleled durability. N20740 N015 NO....Enable MX Retarder in Neutra N20710 N052 650...Idle Target (N052) N21310 N718 155...LRSL SPEED LIMIT N20690 N711 65....MAX PEDAL SPEED N20750 N874 0.1...ENGINE BRAKE DELAY TIME N20760 N871 2.....DSC TGT VEH SPD LIMIT OFFSET N20770 N870 4.....DSL TGT VEH SPD LIMIT OFFSET N20700 N504 64....CC MAX TARGET SPEED N20800 N506 17....CC MIN ENABLE SPEED N20830 N890 MT....MULTI TORQUE IN CC N22000 N509 OFF...Dynamic Cruise Control Enabl N20850 N690 5.....EIST STANDSTILL IDLE TIME N20840 N689 5.....EIST PARKED MAX IDLE TIME N20910 N692 YES...EIST ENGINE LOAD RESET	0
---------	---	---	---

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/ Opt	Description	Weight
N21170	N693	NO....EIST ENGINE LOAD OVERRIDE	
N20900	N688	5.....EIST PTO MAX IDLE TIME	
N21260	N702	YES...EIST OVERRIDE IN PTO MODE	
N20860	N687	39....EIST AMB AIR TEMP OVERRIDE L	
N20870	N686	80....EIST AMB AIR TEMP OVERRIDE H	
N21910	N684	30....EIST CLNT TEMP OVERRIDE LO	
N21230	N699	YES...EIST ACCEL POSITION RESET	
N21250	N701	YES...EIST CLUTCH PEDAL RESET	
N21240	N700	YES...EIST FOOT BRAKE RESET	
N21640	N681	YES...EIST PARK BRAKE RESET ENABLE	
N20940	N726	1900..FIC MAX ENG SPEED	
N21140	N545	YES...PTO Remote Pedal Enable	
N21990	N578	YES...PTO REMOTE PEDAL ENABLE	
N21020	N523	6.....CAB:MAX VEHICLE SPEED	
N21120	N520	2000..Cab: Max Eng Spd- Sw Ctrl	
N21180	N519	2000..Cab: Max Eng Spd- Accel Ctrl	
N21200	N603	650...Cab: Minumum Engine Speed	
N21220	N535	800...Cab: Dedicated Preset "-"	
N21270	N536	900...Cab: Dedicated Preset "+"	
N21110	N553	2000..REM: MAX ENG SPD-SW/ TSC1 CT	
N21980	N552	2000..REM:MAX ENG SPD-CAB/REM ACCE	
N21320	N602	650...REMOTE: MINIMUM ENGINE SPEED	
N21290	N568	800...Remote: Dedicated Preset "-"	
N21490	N569	900...Remote: Dedicated Preset "+"	
N22020	N538	750...Cab Station: Custom Preset 1	
N22040	N540	850...Cab Station: Custom Preset 2	
N22060	N542	950...Cab: Custom Preset 3	
N21950	N637	3.....MIN SPEED FOR DR SHIFT AID	
N21960	N638	1.....LOWEST TRANS GEAR RATIO	
N21970	N639	6.....HIGHEST TRANS GEAR RATIO	
N21930	N618	5.....DRIVER REWARD VEH SPD BONUS	
N21940	N621	-5....DRIVER REWARD VEH SPD PENALT	
N22090	N571	750...Cab/Rem: Custom Preset 1	
N22110	N573	850...Cab/Rem: Custom Preset 2	
N22130	N575	950...Cab/Rem: Custom Preset 3	
N20930	N071	ON....FIC Enable/Disable (N071)	
N21300	N717	0.....VSL EXPIRATION DISTANCE	
N21190	N695	0.....EIST EXPIRATION DISTANCE	
N21010	N549	ON A..CAB: PARK BRAKE INTERLOCK	
N20990	N546	ON A..CAB: CLUTCH INTERLOCK	
N21030	N548	ON A..CAB: NEUTRAL INTERLOCK	
N21150	N550	ON A..Ser Brk Intlk: Pressed = N P	
N21130	N543	DEDIC.Cab: Preset +/- Switch Type	
N21600	N580	ON AD.Remote: Clutch Interlock	
N21700	N582	ON AD.Remote: Neutral Interlock	
N21710	N584	ON AD.Ser Brk Intlk: Pressed=No PT	
N21580	N576	DEDIC.Rem: Preset +/- Switch Type	
N21900	N544	SPD...CAB:ACCEL PEDAL TYPE IN PTO	
N22010	N537	CNCL..Cab: Custom Preset 1	
N22030	N539	CNCL..Cab: Custom Preset 2 Functio	
N22050	N541	CNCL..Cab: Custom Preset 3 Functio	

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
		N21920 N632 NONE..OFFSET MODE	
		N22080 N570 CNCL..Cab/Rem: Custom Preset 1 Fun	
		N22100 N572 CNCL..Cab/Rem: Custom Preset 2 Fun	
		N22120 N574 CNCL..Cab/Rem: Custom Preset 3 Fun	
		N22070 N547 OFF...Cab: Custom Interlock	
		N22140 N581 OFF...Remote: Custom Interlock	
2091140	O	CECU/VECU Electronics Architecture Features include: Faster processing and larger hard drive capacity to provide new features customers are requesting, Improved data security, accessibility, and reliability of SmartLINQ, SmartNav, Telematics Pre-Wire, PTO/body controller, and RP1226 connector diagnostics and Driver Performance Assistance (DPA) Off-Boarding to allow improved fleet analytics.	0
2091305	S	Engine Idle Shutdown Timer Enabled	0
2091315	O	Enable EIST Ambient Temp Ovrerule	0
2091372		Eff EIST NA Expiration Miles	0
2091640		Effective VSL Setting NA	0
2092016	O	Typical Operating Speed 62 MPH	0
2092027	O	MX Retarder State Cruise Control On (Manual Mode Engine Parameter)	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2092079	O	Decline Driver Performance Assistant	0
2092082	S	Engine Monitoring Protection - Derate (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
2140410	S	Engine Brake Controls Located on RH Column	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/ Opt	Description	Weight
		heater keeps the coolant in the engine block from freezing when the engine is not running.	
2522080	S	PACCAR Premium Starter - MX Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	4
2539720	S	Low Voltage Disconnect System	0
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
2738410	S	WABCO 25.9 CFM Air Compressor, MX only WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0
2811160	S	Compression Brake, MX The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. The specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0
2921120	S	PACCAR Fuel/Water Separator Extended Service Interval	0
2921210	S	No Fluid Heat Option for Fuel Filter	0
2921310	S	No Electric Heat Option for Fuel Filter	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0
3291680	S	(1) Air Cleaner Firewall Mounted Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
3365270	S	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	0
3381770	O	Curved Tip Standpipe(s)	1
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0

Transmission & Equipment

4052420	O	Allison 4500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-4.70, 2nd-2.21, 3rd-1.53, 4th-1.00, 5th-0.76, 6th-0.67. Reverse ratios: DR-(5.55).	355
4210190	O	1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing	90
4216590	O	1710 Driveline Interaxle For tandem rear axles	0
4252890	O	Allison FuelSense 2.0 Not Desired	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0
4256740	O	Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 transmission only	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	0

Air & Trailer Equipment

4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	-8
4540420	S	Nylon Chassis Hose	0
4541490	O	Tractor Air System, Spring Brake Relay IPO QR-1C Functions as a quick release valve for the emergency side of the spring brakes.	0
4543320	S	Steel Painted Air Tanks	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/ Opt	Description	Weight
		All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	
4610920	S	Self Returning Brake Hand Valve Dash mounted controls	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	6
4614810	S	AE Connections BOC/BOS, Hose Tenna	0
Tires & Wheels			
5064010	O	FF: BR 20ply 315/80R22.5 M870 Efficiency Rating: Fair Diameter= 42.8 inches; SLR= 19.9 inches The Bridgestone M870 is a high scrub All-Position Radial tire designed specifically for urban waste collection.	94
5169440	O	RR: BR 16ply 11R22.5 M853 Efficiency Rating: Poor Diameter= 41.8 inches; SLR= 19.4 inches	192
5190008	S	Code-rear Tire Qty 08	0
5210550	O	FF: Accur Stl Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	74
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0
5390008	S	Code-rear Rim Qty 08	0
Fuel Tanks			
5554130	O	26" Aluminum 80 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	20
5602080	O	Location LH U/C 80 Gallon	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0
5652990	S	DEF To Fuel Ratio 2:1 Or Greater	0
5655019	S	DEF Tank Small 11.1 Gallon Capacity	0
5760010	O	RH Tank None Furnished	-86

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
Battery Box & Bumper			
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	-60
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0
6111110	O	Steel Bumper Swept Back Painted, Without FEPTO Two tow points and step plates on top of bumper	40
Cab & Equipment			
6515690	S	Vocational 115" BBC Alum Cab and Metton Hood SBFA Stainless crown and grille with tilt assist.	0
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
6700000	S	No Sleeper Selected	0
6911100	S	Peterbilt ST Driver Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standand vinyl finish - color coordinate with interior color.	0
6921140	O	Peterbilt ST Passenger seat Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standand vinyl finish - color coordinate with interior color.	40
6939400	S	Air Ride Driver	0
6939420	S	High Back Driver	0
6939470	S	Vinyl Driver	0
6939500	O	Air Ride Passenger	0
6939520	S	High Back Passenger	0
6939570	S	Vinyl Passenger	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0
7037130	S	Prestige Interior - Sterling Gray	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0
7210550	S	1-Piece Glass Rear Cab Window Fixed	0
7230060	S	1-Piece Curved Windshield	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7514010	O	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	3
7514020	S	Aero Rear View Mirror Housing - Body Color	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0
7610500	S	Air Horn Mounted Under Cab	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	4
7728050	O	USB Port	0
7748145	O	CB Terminals/Wiring Mounted Under Header With mounting bracket	2
7748150	O	(1) Antenna for Factory Installed or F/O CB Mounted LH cowl, low mount only, with antenna cable. Provides clear top of cab.	1
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/Opt	Description	Weight
		SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	
7788056	S	24 Months SmartLINQ Subscription With OTA Functionality - PACCAR MX Engines	0
7851040	O	Removable Bugscreen Behind Grille	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
7852020	O	Cab Air Suspension	15
7900040	O	Fire Extinguisher, Ship Loose Hazmat approved UL listed/rated ABC.	7
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7901130	O	Backup Alarm (107 DB)	3
8011400	O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	0
8021390	S	Air Filter Restriction Pressure Gauge Located in Driver Information Display	0
8071890	S	Main Instrument Panel Includes Driver Information Display and Instrument Package With Speedometer, Tachometer, Fuel Level Gauge, Engine Oil Pressure, Engine Coolant Temperature, two Air Pressure, DEF Level Gauge. With gas engines, DEF Level Gauge will be replaced with Brake Application Gauge.	0
8110070	S	Headlights Projector Module Pod Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0
8140000	S	Incandescent Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	0
8140650	S	Peterbilt Signature Door Light Turn Signal	0
Paint			
8500710	S	Standard Paint Color Selection	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A- L0006EY WHITE N85700 BUMPER L0001EA BLACK	0

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7



Sales Code	Std/ Opt	Description	Weight
N85500		CAB ROOF L0006EY WHITE	
N85300		FENDER L0006EY WHITE	
N85200		FRAME L0001EA BLACK	
N85400		HOOD TOP L0006EY WHITE	

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0
9400092	S	PACCAR MX Standard Coverage 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0

Miscellaneous

9409001	S	Day Cab / Prestige Interior (DM)	0
9409791	O	Peterbilt Motors Company	0
9409831	S	2021 EPA Emissions Engine Warranty Only	0

Promotions

Order Comments

Total Weight 17,701

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: July 1, 2020

Deal: OMES 567

Printed On: 1/19/2021 9:47:44 AM

Date: January 14, 2021

Quote Number: QUO-762437-Z6B2M7