

Item # 100029768
 Medium Duty, 54,000 -
 66,000 # Truck

RUSH TRUCK CENTER

Make Bidding: PETERBILT
 Model Bidding: 520
 Model Code:

Can this Vehicle come ALT
 Fuel Equipped?? YES/NO:

YES

| Body & Chassis | Minimum Specification | |
|-------------------------------------|---|---|
| GWR | 66,000 | Yes (Peterbilt 520 Model) |
| Curb Weight/Payload | Mfg. Std. List Size | 17700lbs (curb weight) 48,294lbs (payload) |
| Chassis CA | 104" CA, Clear Frame Rail | Yes |
| Style, Cab/Tilt Hood | Tilt Hood or Low Cab Forward, List | Yes |
| Axle, Min Front Rating/lb/axle | 20,000/ LB. with Springs | Yes |
| Axle, Min Rear Rating/lb/spd/axle | 46,000 LBS/OIL with Walking Beam Type | Yes |
| Frame, RBM, Min. In-lb | 3,200,000 Double Frame "C" Channel Reinforcement | Yes |
| Cab Mounts | Air Ride Cab | Yes |
| Engine | | |
| Engine Type | Diesel Turbocharged | Yes |
| Engine Cyl/GHP/Gross Torque, Min | Inline 6 Cyl / 8 Liter or Larger / 1350 LBFT | Peccar PX-9 370 Hp 1250@1400 |
| Governor | Electronic PTO Provision | Yes |
| Electronic Engine Shutdown | High Water Temp/Low Oil Press. | Yes |
| Air Cleaner System | List Capacity | Heavy Duty Air Cleaner Radial Seal technology |
| Transmission | | |
| Trans. Type/Speeds, Min. | Allison 4500RDS 6 Spd. | Yes |
| Transmission ECU | Mounted in Cab | Yes |
| PTO Front Mount | Front Mounted PTO Adeption with Integral Frame Extension/Bumper with Stationary Grille, Factory Install. Include "C" Reinforcement to front | Yes |
| PTO | R/Lt Side 10 bolt | Yes |
| Electrical | | |
| Alternator/Rating Cap/Min (amps) | 12 Volt/ 130 Amp | 100 Amp Brushed |
| Battery, CCA @ 0 deg F/Reserve | Two/1500 CAA | 3 Batteries 2100 CCA |
| Disconnect Switch | Battery Disconnect Switch | Yes |
| Jump Start Stud | Mounted Outside Battery Box | Yes |
| Block Heater Min. | 1000 Watt | Immersion Type Block 110-120V |
| Radio Wiring Harness | Two Way Radio Wiring Harness in Header Console | Yes |
| Header Console | | Yes |
| Body Bulder Wiring to Rear of Frame | | Yes (5F1 BOC) |
| Power Supply | 12 Volt Power Bussety in Dash | Yes |
| Fuel | | |
| Fuel Tank Capacity | 80 Gallon Minimum | Yes |
| Fuel Filters | Primary & Fuel Water Separator, Heated | Yes |
| Exterior | | |
| Paint | Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black | Yes |
| Exhaust, Type | Vertical | Yes |
| Horn | 1 Air Horn & 1 Electric Horn | Yes |
| Mirrors | Power Mirrors, Heated, Right and Left | Yes |
| Grill | Chrome Grille Mount Bug Screen | Yes |
| Courtesy Lights | Mounted Below Each Door | Yes |
| Handles | Grab Handles Both Sides | Yes |
| Doors & Windows | | |
| Doors | 2 Doors | Yes |
| Door Locks | 1 Keyed Doors | Yes |
| Windows | Roll Up Windows | Power windows and door locks standard equipment |
| Floor | | |
| Floor Covering | Vinyl/Rubber | Yes |
| Interior | | |
| Air Conditioning and Heater | Front AC Required | Yes |
| Radio | AMFM | Yes |
| Hand Throttle | Electronic | Yes |
| Gauges | All W/ Tach & Hour Meter List | Yes |
| Seats | | |
| Seating Capacity min. | 2 Passenger | Yes |
| Seats | Two (2) Air Suspension- Driver & Passenger | Yes |
| Safety | | |
| Brakes | Air Brakes W/ Compressor W/ Air Dryer & Drain Valve, 16.5 in ± 5 in | Yes 18.7 CFM Air Compressor |
| Alarm | Back-Up Alarm | Yes |
| Restraint System All Pass | Required | Yes |
| Suspension | | |
| Suspension/Shocks | Mfg. Std. List Size | 20,000 lb. Taper Leaf spring/40,000 Haulmax HMX 480 |
| Tires & Wheels | | |
| Wheels, Type | Disc 10 | Yes |
| Tires, Tubeless, Size/Tread Front | 20 Ply, 315/80R 22.5 | Yes |
| Tires, Tubeless, Size/Tread Rear | 11R/22.5/14 Ply Load G, Mud/Snow Tread | Yes |
| Warranty | | |
| 2 Yr/Unlimited Mile Warranty | Includes Towing for Warrantable Failure | Yes (2 year towing w/ engine and transmission failure only) |
| PURCHASE PRICE: | | \$135,850.00 |
| 3 YR LEASE/MO | | \$0.00 |
| 4 YR LEASE/MO | | \$0.00 |
| 5 YR LEASE/MO | | \$0.00 |
| MSRP FOR PURCHASE PRICE: | | \$183,121.00 |

Item # 1000029768
 Medium Duty, 54,000 -
 66,000 # Truck

Dealer Name: RUSH TRUCK CENTER

Make Bidding: PETERBILT
 Model Bidding: 520
 Model Code: 520

| Engines | Options | | Purchase | 3 YR Lease |
|------------------------------------|--|---|-----------|------------|
| Gas Engine | List Specs | N/A | | |
| Diesel Engine | 330HP/1000 LBFT | 350HP/1050 LBFT | -\$1,937 | |
| Software/Cable | Software/Cable | J-Pro DLA Reader | \$6,150 | |
| CNG Engine | BiFuel - List Capacities | N/A | | |
| CNG Engine | Dedicated - List Capacity | Cummins L9N 320HP | \$15,002 | |
| Air Cleaner System | Higher Capacity - List Additional Capacity | Std. | \$0 | |
| Dust Shield | Dust Shield for Snow Removal Operations | Front & Rear Brake shields | \$60 | |
| Transmission | | | | |
| Front PTO | Front Mounted PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille, Factory Install Include "C" Reinforcement to Front | Included with base model pricing | \$0 | |
| Transmission | 10 Speed, Manual, O/D with "C" Series Rating | RTO16908LL | -\$10,222 | |
| Front Axle | | | | |
| Front Axle | 16000 lb w/ 16,000 Springs | 14,600 w/ Taper Leaf Spring | -\$988 | |
| Front Axle | 18000 lb with 18000 Springs | N/A | | |
| Body & Chassis | | | | |
| CA | Decrease to 120" CA, Clear | Yes | -\$130 | |
| CA | Decrease to 138" CA, Clear | Yes | -\$130 | |
| CA | Decrease to 150" CA, Clear | Yes | -\$130 | |
| CA | Decrease to 188" CA, Clear | Yes | -\$50 | |
| Body | 4 Door Crew Cab | N/A | | |
| Frame | Delete Frame Reinforcement C Channel Type. 120,000 PSI | Yes | -\$400 | |
| Frame | Front Frame Extension W/O PTO Adaptor | Yes | -\$1,130 | |
| Axle, Min Front Rating/lb/seals | 12,000/Oil with Springs | Yes | -\$300 | |
| Axle, Min Rear Rating/lb/spd/seals | 40,000/Oil with Articulating Susp. | Yes | -\$2,518 | |
| Electrical | | | | |
| Switch | High Amp (for attenuator, arrowboard, excess lighting, etc.) | (2) Additional Electric Rocker Switches | \$98 | |
| Worklights | Worklight Accomodation Package, List Specs | LH Spotlight and (2) BOC Loadlights | \$234 | |
| Additional Wiring | Snowplow Light Electrical Wiring to Front of Frame | Installed at Dealership | \$500 | |
| Exterior | | | | |
| Screen | Grille Mounted Bug Screen | Yes | \$122 | |
| Mirrors | Heated Mirrors | Heated only | -\$235 | |
| Custom Paint Color | Chrome Yellow (Per FAA Guidelines) | Yes | \$4,500 | |
| Exhaust | Horizontal | CNG Horizontal | -\$809 | |
| Grille | Stationary Grille | Yes, Included w/ FEPTO Front End | \$0 | |
| Interior | | | | |
| AC | Delete AC | N/A | | |
| Seats | 3 Passenger - Air Suspension Driver, 2 Man Passenger | Air Driver & Fixed Passenger | \$267 | |
| Tilt & Cruise | Tilt Wheel & Cruise Control | Yes, Tilt & Telescope | \$328 | |
| Safety | Air Bag Both Sides | N/A | | |
| Instrument Panel | Ergonomic Instrument Panel (Wrap-Around) | N/A | | |
| Keys | 3 Additional Keys Per Truck | Yes | \$15 | |
| Visor | Visor over Windshield | Yes | \$186 | |
| Tire Inflator Tool | Air Cab Blower with Tire Inflator Tool | Yes | \$200 | |
| Windows | Power Windows | Yes | \$100 | |
| Refuse Electronics Package | All items necessary for Refuse Package | Included in base model pricing plus Remote throttle provision | \$100 | |

| Safety | | | | |
|---|---|-----------------------------------|------------|--|
| Alarm | Park Brake Alarm | Std. | \$0 | |
| Hydraulic Brakes | Deduct for Hydraulic Brakes | N/A | | |
| Tires & Wheels | | | | |
| Tires | Rear Tires, Highway tread | Yes | -\$500 | |
| Spare Wheel | Steel Spare Wheel | Yes | \$250 | |
| Tires for 14,000 lb Axle | List Specs | 14,600 lb. GY 18 Ply 315/80R 22.5 | -\$105 | |
| Tires for 18,000 lb Axle | List Specs | N/A | | |
| Tires for 18,000 lb Axle | List Specs | N/A | | |
| Towing | | | | |
| Hooks | Front Tow Hooks | Std (2) in Bumper | \$0 | |
| Trailer Connection | Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring | Yes | \$100 | |
| Delivery | | | | |
| Delivery Cost | Price to Deliver Truck more than 150 miles | | 1.50/ mile | |
| Other | | | | |
| Deduct for orders of multiple vehicles to same location | List # of vehicles to qualify | N/A | | |
| Options not listed | Discount off MSRP for options not listed | 25% off list | | |



Rush Pblt Truck Centers (O500)
 8700 West I-40
 Oklahoma City, Oklahoma 73128

Stock

William Duncan
 Cell Phone: 405-922-4093
 Office Phone: 405-782-3508
 Email: duncanw@rushenterprises.com

Stock Order

Vehicle Summary

| | | | | |
|-------------------------|--------------|--------------------------------|----------------------------|-------|
| Model: | Unit | Model 520 | Fr Axle Load (lbs): | 20000 |
| Type: | | Full Truck | Rr Axle Load (lbs): | 46000 |
| Description 1: | | OMES 520 Model | G.C.W. (lbs): | 66000 |
| Description 2: | | | | |
| Intended Serv.: | Application | Refuse/On-Highway | Road Conditions: | |
| Commodity: | | Refuse, Scrap, Recycling | Class A (Highway) | 100 |
| | | | Class B (Hwy/Mtn) | 0 |
| | | | Class C (Off-Hwy) | 0 |
| | | | Class D (Off-Road) | 0 |
| Type: | Body | Automated Side Loader/Push-Out | Maximum Grade: | 6 |
| Length (ft): | | 24 | Wheelbase (in): | 195 |
| Height (ft): | | 13.5 | Overhang (in): | 54 |
| Max Laden Weight (lbs): | | 1000 | Fr Axle to BOC (in): | 0.1 |
| | | | Cab to Axle (in): | 194.9 |
| | | | Cab to EOF (in): | 248.9 |
| | | | Overall Comb. Length (in): | 306.6 |
| No. of Trailer Axles: | Trailer | 0 | | |
| Type: | | | | |
| Length (ft): | | 0 | Special Req. | |
| Height (ft): | | 0 | | |
| Kingpin Inset (in): | | 0 | | |
| Corner Radius (in): | | 0 | | |
| | Restrictions | | | |
| Length (ft): | | 40 | | |
| Width (in): | | 102 | | |
| Height (ft): | | 13.5 | | |

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



| Sales Code | Std/Opt | Description | Weight |
|-----------------------------------|---------|--|--------|
| Base Model | | | |
| 0005201 | S | Model 520 Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points. | 16,475 |
| 0091180 | O | Refuse, Scrap, Recycling | 0 |
| 0093035 | O | Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills. | 0 |
| 0095220 | O | Automated Side Loader/Push-Out A lift-equipped truck used to pick up wheeled waste containers to load waste materials into the truck body. Requires a single operator. A hydraulic ram pushes the load out of the body. | 0 |
| 0098170 | S | United States Registry | 0 |
| Configuration | | | |
| 0200700 | O | Not Applicable Secondary Manufacturer | 0 |
| Frame & Equipment | | | |
| 0514150 | S | 10-3/4" Steel Rails To 305" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair | 88 |
| 0601500 | S | Full Steel Inner Liner | 616 |
| 0644090 | S | EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember. | 0 |
| 0651090 | S | Omit Rear Mudflaps and Hangers | 0 |
| 0713130 | S | (2) Solid Mount Cable Hooks | 40 |
| Front Axle & Equipment | | | |
| 1011890 | S | PACCAR Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency. | 0 |

Price Level: July 1, 2020
Deal: OMES 520 Model
Printed On: 1/16/2021 9:12:53 AM

Date: January 16, 2021
Quote Number: QUO-763756-J3R9Y3



| Sales Code | Std/Opt | Description | Weight |
|----------------------------------|---------|---|--------|
| | | The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles. | |
| 1114030 | S | Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks. | 0 |
| 1243010 | O | Power Steering Sheppard M100 Dual For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components. | 0 |
| 1354850 | S | PHP10 Iron PreSet PLUS Hubs-Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear. | 0 |
| 1354870 | O | Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle. | 0 |
| 1380290 | S | Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations. | 0 |
| 1380490 | O | PACCAR Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius. | 0 |
| Rear Axle & Equipment | | | |
| 1523440 | S | Dana Spicer D46-172 46,000 LBS Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity. | 0 |
| 1616305 | S | PHP10 Iron Preset + Hubs - Air Disc | 0 |
| 1616310 | O | Severe Service Disc Brake Rotor Severe Service Disc Brake Rotor for refuse applications. | 0 |
| 1680460 | S | Heavy Wall, Drive Axle(s) | 88 |
| 1680500 | S | SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. | 0 |
| 1682430 | S | Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system. | 0 |
| 1684200 | S | Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold | 0 |



| Sales Code | Std/ Opt | Description | Weight |
|------------|----------|---|--------|
| | | conditions and withstand the stress from high temperatures, extending component life. | |
| 1687040 | S | Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters. | 0 |
| 1705250 | S | Ratio 5.25 Rear Axle | 0 |
| 1824440 | O | Hendrickson HMX EX 460 46,000 LBS., 52" Haulmax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability. | -88 |
| 1921375 | O | 16.5" Saddle Height HMX EX 400/460 IPO Std 18.5" | 0 |

Engine & Equipment

| | | | |
|---------|---|---|---|
| 2074513 | O | PACCAR PX-9 370@1900 GOV@2100 1250@1200 Performance (2021 Emissions) | 0 |
| | | N21350 C121 65....Maximum Accelerator Pedal Ve N21370 C128 65....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21630 C190 80....High Ambient Temperature Thr N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21590 C382 YES...Enable Hot Ambient Automatic N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21620 C189 60....Intermediate Ambient Tempera N21550 C206 100...Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21500 C395 0.....Expiration Distance (N209) N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207) | |
| 2091305 | S | Engine Idle Shutdown Timer Enabled | 0 |
| 2091315 | S | Enable EIST Ambient Temp Overrule | 0 |
| 2091372 | | Eff EIST NA Expiration Miles | 0 |



| Sales Code | Std/Opt | Description | Weight |
|------------|---------|--|--------|
| 2091640 | | Effective VSL Setting NA | 0 |
| 2092009 | S | Typical Operating Speed 58 MPH | 0 |
| 2092032 | S | Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs. | 0 |
| 2140200 | S | CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard. | 0 |
| 2147460 | O | Bed Plate for PX-9, L9N Engines Designed to increase engine longevity by incorporating a stiffener bracket on the bottom side of the engine, inside the oil pan, for additional reinforcement. Required for all PX-9/L9N refuse applications and recommended for other high load 9-liter applications. | 0 |
| 2513060 | S | PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle. | 0 |
| 2521090 | S | Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running. | 2 |
| 2522110 | O | PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. | 0 |
| 2538040 | S | 3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. | 0 |
| 2539740 | S | Kissling Battery Disconnect Switch, 300 amp Mounted on battery box | 3 |
| 2621000 | S | 2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower. | 0 |
| 2723210 | O | 18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line. | 0 |
| 2921110 | S | PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components. | 0 |
| 2921210 | S | No Fluid Heat Option for Fuel Filter | 0 |
| 2921310 | S | No Electric Heat Option for Fuel Filter | 0 |

Price Level: July 1, 2020
Deal: OMES 520 Model
Printed On: 1/16/2021 9:12:53 AM

Date: January 16, 2021
Quote Number: QUO-763756-J3R9Y3



| Sales Code | Std/ Opt | Description | Weight |
|-------------------------------------|----------|---|--------|
| 3114270 | S | High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in. | 0 |
| 3120450 | S | Stainless Steel Grille | 0 |
| 3261980 | S | Heavy Duty Air Cleaner Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake. | 0 |
| 3365300 | S | Exhaust Vertical LH DPF/SCR LH Back of Cab Vertical. | 0 |
| 3381770 | S | Curved Tip Standpipe(s) | 1 |
| Transmission & Equipment | | | |
| 4052420 | O | Allison 4500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-4.70, 2nd-2.21, 3rd-1.53, 4th-1.00, 5th-0.76, 6th-0.67. Reverse ratios: DR-(5.55). | 390 |
| 4210190 | O | 1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing | 15 |
| 4216590 | O | 1710 Driveline Interaxle For tandem rear axles | -5 |
| 4252830 | O | Allison FuelSense 2.0 Basic Features include: EcoCal shift technology keeps the engine speed at the most efficient level and DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction. | 0 |
| 4252950 | S | Omit Allison Neutral At Stop | 0 |
| 4256020 | S | Console Mounted Push Button Shifter Allison Automatic Transmissions or LFNA Electric Vehicle | 0 |
| 4256350 | S | Auto Neutral AK, Allison HD/RDS | 0 |

Price Level: July 1, 2020

Deal: OMES 520 Model

Printed On: 1/16/2021 9:12:53 AM

Date: January 16, 2021

Quote Number: QUO-763756-J3R9Y3



| Sales Code | Std/ Opt | Description | Weight |
|------------------------------------|----------|--|--------|
| | | Single steer left-hand or right-hand, add code 4540940 if plumbed to flip valve to actuate service brakes is desired | |
| 4256450 | S | Allison MD/HD Shift Select AL Dual station controls | 0 |
| 4256740 | O | Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 transmission only | 0 |
| Air & Trailer Equipment | | | |
| 4510210 | S | Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant. | -8 |
| 4520420 | S | Pull Cords All Air Tanks | 1 |
| 4540420 | S | Nylon Chassis Hose | 0 |
| 4543320 | S | Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. | 0 |
| 4612000 | S | Route AE Lines To Allow Welding Of Sub Frame To top of frame 8" forward of back-of-cab to end-of-frame | 0 |
| Tires & Wheels | | | |
| 5064010 | S | FF: BR 20ply 315/80R22.5 M870 Efficiency Rating: Fair Diameter= 42.8 inches; SLR= 19.9 inches The Bridgestone M870 is a high scrub All-Position Radial tire designed specifically for urban waste collection. | 0 |
| 5169440 | O | RR: BR 16ply 11R22.5 M853 Efficiency Rating: Poor Diameter= 41.8 inches; SLR= 19.4 inches | 192 |
| 5190008 | S | Code-rear Tire Qty 08 | 0 |
| 5220520 | S | FF: Alcoa 89U637 22.5 X 9.00 Clean Buff Finish Aluminum, Ultra ONE wheels with MagnaForce alloy that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating. | -110 |
| 5310610 | O | RR: Accur Steel Armor 50344PK 22.5X8.25 Heavy Duty, 5 Hand Holes | 16 |
| 5390008 | S | Code-rear Rim Qty 08 | 0 |

Price Level: July 1, 2020
Deal: OMES 520 Model
Printed On: 1/16/2021 9:12:53 AM

Date: January 16, 2021
Quote Number: QUO-763756-J3R9Y3



| Sales Code | Std/Opt | Description | Weight |
|---------------------------------|---------|---|--------|
| 5409320 | O | Wheel Guards, Tandem Axle Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels. | 0 |
| Fuel Tanks | | | |
| 5552070 | S | 26" Aluminum 60 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks. | 9 |
| 5556130 | O | 26" Aluminum 80 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks. | 13 |
| 5604080 | O | Location LH BOC 80 Gallon | 0 |
| 5652980 | O | DEF To Fuel Ratio Between 1:1 And 2:1 | 0 |
| 5655069 | S | DEF Tank 520 | 0 |
| Battery Box & Bumper | | | |
| 6010460 | O | Aluminum Space Saver Battery Box LH Back Of Cab | -11 |
| 6122810 | S | Steel Bumper Swept Back Painted Requires bumper extension, includes two front tow eyes with pins | 2 |
| 6132400 | S | Notched Top Flange Of Bumper Does not include fepto provisions | 0 |
| 6132420 | S | 4-7/8" Bumper Extension, Without FEPTO | 31 |
| Cab & Equipment | | | |
| 6501080 | S | 53" LCF ProBilt Cab LH Drive Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, doghousefull insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, adjustable side flip-down interior sunvisor, 16" steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls and 12V power connection behind header cover, rear cab corner windows, 18" bolt-on | 0 |



| Sales Code | Std/Opt | Description | Weight |
|------------|---------|--|--------|
| | | step each side, self-canceling turn signals and front directional and side mounted turn signals. | |
| 6800500 | S | 4.5" Rubber Flares On Cab And wheel well fenders | 0 |
| 6911720 | S | Peterbilt Driver Seat | 0 |
| 6921720 | S | Peterbilt Passenger Seat | 0 |
| 6939410 | S | Non-Air Ride Driver | 0 |
| 6939440 | S | Low Back Driver | 0 |
| 6939470 | S | Vinyl Driver | 0 |
| 6939510 | S | Non-Air Ride Passenger | 0 |
| 6939520 | S | High Back Passenger | 0 |
| 6939560 | S | Fabric Passenger | 0 |
| 7000000 | S | Gray Interior Color Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover. For LH, RH, and dual steer dual seated power windows are standard on both doors. For dual steer RH stand-up the LH window is power and the RH window is a manual sliding window. | 0 |
| 7001520 | S | Adjustable Steering Column - Tilt/Telescope | 0 |
| 7001620 | S | Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button. | 0 |
| 7110680 | S | Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only. | 0 |
| 7220130 | S | Rear Window Back of Cab Standard Tint 18.5in X 54in | 0 |
| 7230350 | S | 2-Piece Flat Windshield | 0 |
| 7322010 | S | Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. | 0 |
| 7561260 | S | Black LH/RH Tri-plane Mirrors, Heated, Motorized, Mounted to Doors. Features: Heated on All Three Surfaces, Upper/Lower Mirrors are Convex and Middle is a Flat Pane Motorized Mirror. | 0 |
| 7610020 | S | (1) Air Horn 15" Painted Mounted under cab. | 0 |
| 7722120 | O | ConcertClass, AM/FM, Weatherband, 3.5 Aux | 10 |
| 7725740 | S | Midlevel Speaker Package For Cab (4) Speakers | 6 |

Price Level: July 1, 2020
 Deal: OMES 520 Model
 Printed On: 1/16/2021 9:12:53 AM

Date: January 16, 2021
 Quote Number: QUO-763756-J3R9Y3



| Sales Code | Std/Opt | Description | Weight |
|--------------|---------|--|--------|
| 7788055 | S | SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine. | 0 |
| 7788057 | O | 24 Months SmartLINQ Subscription PACCAR PX Engines. | 0 |
| 7851870 | S | Rain Gutters Over Driver and Passenger Doors | 8 |
| 7852150 | S | Peterbilt Pantograph Windshield Wipers With intermittent feature. | 0 |
| 7900970 | S | Backup Alarm Wiring To EOF | 0 |
| 8011400 | S | Main Transmission Oil Temperature Gauge Located in Driver Information Display | 0 |
| 8021315 | S | Air Restriction Indicator Mounted on exhaust stanchion | 0 |
| 8031120 | S | Warning Light Battery Disconnect, Switch Engaged Marker light external mounted | 0 |
| 8110090 | S | Headlights Single Rectangular Halogen | 0 |
| 8120550 | S | (5) Light Guards On Marker Lights | 2 |
| 8120570 | S | (5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door | 0 |
| 8133900 | S | None Furnished Stop/Tail/Backup Lights Available with full truck only, not available with tractor | 0 |
| 8133960 | S | Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles. | 0 |
| Paint | | | |
| 8500710 | S | Standard Paint Color Selection | 0 |
| 8530770 | S | (1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK | 0 |

Price Level: July 1, 2020

Deal: OMES 520 Model

Printed On: 1/16/2021 9:12:53 AM

Date: January 16, 2021

Quote Number: QUO-763756-J3R9Y3



| Sales Code | Std/Opt | Description | Weight |
|------------|---------|-------------------------------|--------|
| | | N85500 CAB ROOF L0006EY WHITE | |
| | | N85200 FRAME L0001EA BLACK | |

Shipping Destination

Options Not Subject To Discount

| | | | |
|---------|---|--|---|
| 9400090 | S | Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km) | 0 |
| 9400094 | O | PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs | 0 |

Miscellaneous

| | | | |
|---------|---|--|---|
| 9409831 | S | 2021 EPA Emissions Engine Warranty Only | 0 |
|---------|---|--|---|

Promotions

Order Comments

Total Weight

17,786

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information