

Item # 100009354
 Medium Duty, 25,500 #
 Truck

Dealer Name: Rush Truck Center OKC

Make Bidding: Peterbilt
 Model Bidding: 220 LCF
 Model Code: 220

Can this Vehicle come ALT Fuel Equipped?? YES/NO: NO

| Body & Chassis | Standard Minimum Specifications | |
|------------------------------------|--|--|
| GVWR | 25,500 | 26,000 GVWR |
| Curb Weight/Payload | Mfg. Std. List Size | 10132lbs (Curb weight) 15,868lbs (payload) |
| Chassis CA | 84" CA, Clear Frame Rail | |
| Style, Cab/Tilt Hood | Tilt Hood | LCF LH drive |
| Axle, Min Front Rating/lb/seals | 8000 lbs w/ springs | 12,000lb |
| Axle, Min Rear Rating/lb/spd/seals | 17,500 lbs, Oil | 17,000lb |
| Suspension, Front/Rear, lb | 8,000/17,500 | 12,000lb front/17,000lb rear |
| Frame, RBM, Min, In-lb | 80,000 PSI | Yes |
| Cab Mount | Air Ride Cab | Yes |
| Engine | | |
| Engine Type | Diesel Turbocharged, Wet Sleeve Type, Parent Bore. - List Type | Paccar PX-7 |
| Engine Cyl/GHP/Gross Torque, Min | Inline 6 Cyl/210 HP/520 Torque | 220 Hp @2000 |
| Electronic Shutdown | High Water Temp/Low Oil Press | Yes |
| Governor | Electronic Control PTO Provision | Yes |
| Air Cleaner System | List Capacity | 1 air cleaner fender mounted |
| Transmission | | |
| Trans. Type/Speeds, Min. | Allison 2500 RDS 5 Speed | Yes |
| PTO | Rt. Side 6 bolt | Yes |
| Electrical | | |
| Alternator/Rating Cap/Min (amps) | 12 Volt/ 130 Amp | 160 Amp Brushed |
| Battery, CCA @ 0 deg F/Reserve | Two/1500 CCA | (2) Paccar Premium Batteries 2000 CCA |
| Disconnect Switch | Battery Disconnect Switch | Yes |
| Jump Start Stud | Mounted Outside Battery Box | Yes |
| Radio Wiring Harness | Two Way Radio Wiring Harness in Header Console | |
| Header Console | | Yes |
| Body Builder wiring/Rear of frame | | Yes |
| Block Heater Min. | 1000 Watt | Immersion type block heater 110V |
| Fuel | | |
| Fuel Capacity, (gal) Min | 45 Gallon minimum | 45 Gallon rectangular |
| Fuel Filters | Primary & Fuel Water Separator, Heated | Yes |
| Exterior | | |
| Paint | Cab-White Base Coat Clear Coat, Frame/Running Gear-Black | Yes |
| Exhaust, Type | Horizontal | Yes |
| Horn | Dual Electric | Yes |
| Mirrors | Power Mirrors, Heated, Right and Left | Yes |
| Grill | Chrome Grill Mount Bug Screen | N/A w/ this model |
| Courtesy Lights | Mounted Below Each Door | Yes |
| Handles | Grab Handles Both Sides | Yes |
| Doors & Windows | | |
| Doors | 2 Doors | Yes |
| Door Locks | 1 Keyed Doors | Yes |
| Windows | Roll Up Windows | Power windows and locks standard equipment |
| Keys | 3 Additional Keys | Yes |
| Floor | | |
| Floor Covering | Vinyl/Rubber | Yes |
| Interior | | |
| Air Conditioning and Heater | Front AC Req. | Yes |
| Radio | AM/FM | Yes |
| Hand Throttle | Electronic | N/A w/ this model |
| Gauges | All W/ Tach & Hour Meter List | Yes |
| Power Supply | 12 Volt Power Supply In Cab | Yes |
| Seats | | |
| Seating Capacity min. | Two (2) Air Suspension- Driver & Passenger | Yes |
| Safety | | |
| Brakes | Air Brakes W/ 12 cu ft. Compressor W/ Air Dryer, Air Horn & Drain Valve w/ Battery Disconnect Switch | Yes |
| Alarm | Back-Up Alarm | Yes |
| Restraint System All Pass | Req. | Yes |
| Tires & Wheels | | |
| Wheels, Type | Disc | Yes |
| Tires, Tubeless, Size/Tread Front | 11R/22.5/14 Ply/ Load G | Yes |
| Tires, Tubeless, Size/Tread Rear | 11R/22.5/14 Ply/ Load G, Mud/Snow Tread | Yes |
| Warranty | | |
| 2 Yr/Unlimited Mile Warranty | Includes Towing for Warrantable Failure | 2 year towing w/ engine and trans failure only |
| PURCHASE PRICE: | | \$78,675.00 |

Item # 100009354
 Medium Duty, 25,500 #
 Truck

Dealer Name: Rush Truck Center

Make Bidding: 2020 Peterbilt
 Model Bidding: 220 LCF
 Model Code: 220

| | | | Purchase | 3 YR Lease | 4 YR Lease | 5 YR Lease |
|---|---|------------------------|----------|------------|------------|------------|
| Engines | | | | | | |
| Engine Diagnostic Reader | Software/Cable | J-Pro DLA Reader | \$5,750 | | | |
| Gas Engine | List Specs | N/A | | | | |
| Air Filter | Increase Capacity | Standard Equipment | | | | |
| CNG Engine | BFuel - List Capacities | N/A | | | | |
| CNG Engine | Dedicated - List Capacity | N/A | | | | |
| Air Cleaner System | Higher Capacity - List Additional Capacity | N/A | | | | |
| Dust Shield | Dust Shield for Snow Removal Operations | N/A | | | | |
| Transmission | | | | | | |
| Transmission | 8 Speed, Manual | N/A | | | | |
| Electrical | | | | | | |
| Switch | High Amp (for attenuator, arrowboard, excess lighting, etc.) | Installed @ dealership | \$250 | | | |
| Worklights | Worklight Accomodation Package, List Specs | N/A | | | | |
| Additional Wiring | Snowplow Light Electrical Wiring to Front of Frame | N/A | | | | |
| Body & Chassis | | | | | | |
| CA | Increase to 102" CA, clear w/80000 PSI frame | Yes | \$100 | | | |
| CA | Increase to 120" CA, clear w/80000 PSI frame | Yes | \$150 | | | |
| CA | Increase to 138" CA, clear w/120,000 PSI frame | Yes | \$200 | | | |
| CA | Increase to 156" CA, clear w/120,000 PSI frame | Yes | \$250 | | | |
| Body | 4 Door Crew Cab | N/A | | | | |
| Exterior | | | | | | |
| Mirrors | Heated Mirrors | Standard Equipment | | | | |
| Custom Paint Color | Chrome Yellow (Per FAA Guidelines) | Yes | \$4,500 | | | |
| Screen | Grille Mounted Bug Screen | N/A | | | | |
| Interior | | | | | | |
| AC | Delete AC | N/A | | | | |
| Seats | 3 Passenger - Air Suspension Driver, 2 Man Passenger | Yes | \$0 | | | |
| Tilt & Cruise | Tilt Wheel & Cruise Control | Standard equipment | | | | |
| Safety | Air Bags Both Sides | N/A | | | | |
| Instrument Panel | Ergonomic Instrument Panel (Wrap-Around) | N/A | | | | |
| Visor | Visor over Windshield | N/A | | | | |
| Fuel | | | | | | |
| Tank | 100 Gallon Minimum | N/A | | | | |
| Brakes | | | | | | |
| Hydraulic Brakes | Deduct for Hydraulic Brakes | N/A | | | | |
| Safety | | | | | | |
| Alarm | Park Brake Alarm | Standard equipment | | | | |
| Tires & Wheels | | | | | | |
| Tires | Rear Tires, Highway tread | Yes | (\$250) | | | |
| Towing | | | | | | |
| Hooks | Front Tow Hooks | Yes | | | | |
| Trailer Connection | Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring | N/A | | | | |
| Delivery | | | | | | |
| Delivery Cost | Price to Deliver Truck more than 150 miles | Yes | \$100 | | | |
| Other | | | | | | |
| Deduct for orders of multiple vehicles to same location | List # of vehicles to qualify | N/A | | | | |
| Options not listed | Discount off MSRP for options not listed | 25% off list | | | | |



Rush Pblt Truck Centers (O500)
 8700 West I-40
 Oklahoma City, Oklahoma 73128

Stock

William Duncan
 Cell Phone: 405-922-4093
 Office Phone: 405-782-3508
 Email: duncanw@rushenterprises.com

Stock Order

Vehicle Summary

| Unit | | Chassis | |
|-------------------------|-----------------|----------------------------|-------|
| Model: | Model 220 | Fr Axle Load (lbs): | 12000 |
| Type: | Full Truck | Rr Axle Load (lbs): | 21000 |
| Description 1: | OMES 220 | G.C.W. (lbs): | 26000 |
| Description 2: | | | |
| Application | | Road Conditions: | |
| Intended Serv.: | City Delivery | Class A (Highway) | 100 |
| Commodity: | Household Goods | Class B (Hwy/Mtn) | 0 |
| | | Class C (Off-Hwy) | 0 |
| | | Class D (Off-Road) | 0 |
| Body | | Maximum Grade: | |
| Type: | Flatbed | | 6 |
| Length (ft): | 20 | Wheelbase (in): | 170 |
| Height (ft): | 13.5 | Overhang (in): | 72 |
| Max Laden Weight (lbs): | 1000 | Fr Axle to BOC (in): | 11.4 |
| | | Cab to Axle (in): | 158.6 |
| | | Cab to EOF (in): | 230.6 |
| | | Overall Comb. Length (in): | 293.6 |
| Trailer | | Special Req. | |
| No. of Trailer Axles: | 0 | | |
| Type: | | | |
| Length (ft): | 0 | | |
| Height (ft): | 0 | | |
| Kingpin Inset (in): | 0 | | |
| Corner Radius (in): | 0 | | |
| Restrictions | | | |
| Length (ft): | 40 | | |
| Width (in): | 102 | | |
| Height (ft): | 13.5 | | |

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



| Sales Code | Std/ Opt | Description | Weight |
|-----------------------------------|----------|---|--------|
| Base Model | | | |
| 0002201 | S | Model 220 The Model 220 is a beautifully compact package offering driver comfort, easy service, entry safety features and vigorous power. The 220 is available with a GVW of 26,000-33,000 lbs. Designed for driver productivity, the Model 220 features 360-degree visibility, superior maneuverability, rugged protection and convenient storage. With low chassis weight, it's perfect for high-volume payloads while the standard Allison automatic transmission and air disc brakes help to provide a comfortable driver experience. The 220 is ideal for pickup and delivery as well as beverage and refuse applications, and it is available in a right-hand drive configuration for street sweepers and paint striper operations. | 9,794 |
| 0070529 | S | LFNA, Euro 6, LHD, Hi-HP, U.S. Registry | 0 |
| 0091090 | S | Household Goods | 0 |
| 0093340 | S | City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery. | 0 |
| 0095020 | S | Flatbed | 0 |
| 0098170 | S | United States Registry | 0 |
| Configuration | | | |
| 0200700 | S | Not Applicable Secondary Manufacturer | 0 |
| 0210260 | O | Class 6 Chassis Weight Rating 26,000 lb GVWR | 0 |
| Frame & Equipment | | | |
| 0510170 | S | 10-1/4" Steel Rails, Steel Crossmembers | 0 |
| 0612410 | S | 170" Wheelbase, 72" Overhang Suitable for 18' body length | 0 |
| 0644090 | S | EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember. | 0 |
| 0651090 | S | Omit Rear Mudflaps and Hangers | 0 |
| Front Axle & Equipment | | | |
| 1011875 | S | Dana Spicer E12021L 12,000 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 lb. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance. | 0 |
| 1111190 | S | Taper Leaf Springs, Shocks 12,000 lb | 0 |

Price Level: July 1, 2020

Deal: OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/ Opt | Description | Weight |
|----------------------------------|----------|---|--------|
| | | Hendrickson taper leaf springs, shocks for 12,000 lbs. | |
| 1233140 | S | Power Steering, 12K Capacity, Single Power Supplier: Bosch | 0 |
| 1354855 | S | PHP10 Iron PreSet Hubs-Air Disc | 0 |
| 1380290 | S | Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations. | 0 |
| Rear Axle & Equipment | | | |
| 1512945 | S | Dana Spicer S21-140 21,000 lb | 0 |
| 1616370 | S | PHP10 Iron PreSet Hubs | 0 |
| 1680500 | S | SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. | 0 |
| 1680950 | S | Stability System Not Selected Or Not Available | 0 |
| 1683255 | S | WABCO Electronic Braking System (EBS) With Antilock And Traction Control | 0 |
| 1684200 | S | Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life. | 0 |
| 1687010 | S | Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. | 0 |
| 1705290 | O | Ratio 5.29 Rear Axle | 0 |
| 1816140 | S | Reyco 79KB Taper Leaf 21,000 lb | 0 |
| Engine & Equipment | | | |
| 2073117 | S | PACCAR PX-7 220@2400 GOV@2600 520@1600 Efficiency (2021 Emissions) N21350 C121 65....Maximum Accelerator Pedal Ve N21370 C128 65....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre | 0 |

Price Level: July 1, 2020

Deal: OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/ Opt | Description | Weight |
|------------|----------|---|--------|
| | | N21630 C190 80....High Ambient Temperature Thr | |
| | | N21510 C225 YES...Enable Idle Shutdown Park Br | |
| | | N21450 C231 NO....Gear Down Protection (P026) | |
| | | N21570 C233 NO....Idle Shutdown Manual Overrul | |
| | | N21440 C234 NO....Engine Protection Shutdown (| |
| | | N21480 C238 NO....Auto Engine Brake in Cruise | |
| | | N21470 C239 NO....Cruise Control Auto Resume (| |
| | | N21590 C382 YES...Enable Hot Ambient Automatic | |
| | | N21530 C396 YES...Enable Impending Shutdown Wa | |
| | | N21540 C397 60....Timer For Impending Shutdown | |
| | | N21620 C189 60....Intermediate Ambient Tempera | |
| | | N21550 C206 100...Engine Load Threshold (P516) | |
| | | N21340 C209 120...Hard Maximum Speed Limit (P1 | |
| | | N21430 C333 0.....Reserve Speed Limit Offset (| |
| | | N21410 C334 0.....Maximum Cycle Distance (N202 | |
| | | N21500 C395 0.....Expiration Distance (N209) | |
| | | N21320 C399 120...Standard Maximum Speed Limit | |
| | | N21400 C400 252...Reserve Speed Function Reset | |
| | | N21420 C401 10....Maximum Active Distance (N20 | |
| | | N21330 C402 0.....Expiration Distance (N207) | |
| 2091305 | S | Engine Idle Shutdown Timer Enabled | 0 |
| 2091315 | O | Enable EIST Ambient Temp Overrule | 0 |
| 2091372 | | Eff EIST NA Expiration Miles | 0 |
| 2091640 | | Effective VSL Setting NA | 0 |
| 2092014 | O | Typical Operating Speed 65 MPH | 0 |
| 2092032 | O | Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs. | 0 |
| 2140200 | S | CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard. | 0 |
| 2513050 | S | 160 Amp Alternator, Brushed 160 amp alternator is a brush style alternator is designed to address vehicle applications that require higher electrical output, but also want lower weight, improved temperature capability and fuel savings. | 0 |
| 2521090 | O | Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running. | 2 |
| 2521330 | S | Cold Start Engine Grid Heater Effective to -4 F / -20 C | 0 |

Price Level: July 1, 2020

Deal: OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/ Opt | Description | Weight |
|-------------------------------------|----------|---|--------|
| 2522020 | S | Delco Starter 12V Delco Starter 12 volt used on utility/work trucks to power inverters, plug-in power tools, lights and other electrical equipment. Ideal for highway trucks with multiple battery auxiliary power units. | 0 |
| 2538030 | S | 2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. | 0 |
| 2539740 | S | Kissling Battery Disconnect Switch, 300 amp Mounted on battery box | 0 |
| 2636030 | S | Viscous Type Fan Clutch | 0 |
| 2723210 | S | 18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line. | 0 |
| 2921160 | S | Spin-On Fuel/Water Separator | 0 |
| 2921210 | S | No Fluid Heat Option for Fuel Filter | 0 |
| 2921310 | S | No Electric Heat Option for Fuel Filter | 0 |
| 3114270 | S | High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in. | 0 |
| 3270020 | S | (1) Air Cleaner Fender Mounted RH BOC | 0 |
| 3280030 | S | High Air Intake | 0 |
| 3365290 | S | Exhaust Single RH Horizontal DPF/SCR RH Under Frame. | 0 |
| Transmission & Equipment | | | |
| 4051710 | O | Allison 2500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Allison Shift Performance, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes dash mounted indicator light when the transmission fluid, filter or clutches need service. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.51, 2nd-1.90, 3rd-1.44, 4th-1.00, 5th-0.74, 6th-0.64. Reverse ratios: DR-(5.09). | 35 |
| 4210930 | S | SPL100 Driveline, 1 Midship Bearing | 0 |
| 4252840 | S | Allison FuelSense 2.0 Plus | 0 |

Price Level: July 1, 2020

Deal. OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/ Opt | Description | Weight |
|------------------------------------|----------|---|--------|
| | | Features include: EcoCal shift technology keeps the engine speed at the most efficient level, DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction and Neutral at Stop reduces or eliminates the load on the engine when vehicle is stopped, lowering fuel consumption and emissions. | |
| 4252940 | S | Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only. | 0 |
| 4256020 | S | Console Mounted Push Button Shifter Allison Automatic Transmissions or LFNA Electric Vehicle | 0 |
| 4256760 | S | Allison 5-Speed Configuration, Wide Ratio Gears Allison 2500 transmissions only. | 0 |
| Air & Trailer Equipment | | | |
| 4510830 | S | WABCO SS1200 Plus Air Dryer, Heater Coalescing filter | 0 |
| 4543320 | S | Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. | 0 |
| Tires & Wheels | | | |
| 5069600 | S | FF: BR 14ply 11R22.5 R268 Ecopia Efficiency Rating: Poor R268 tread is not a Line Haul tire and is only for Pickup and Delivery or Regional use. Diameter = 41.5 inches; SLR = 19.3 inches | 0 |
| 5169350 | O | RR: BR 14ply 11R22.5 M770 Efficiency Rating: Poor Diameter = 42.2 inches; SLR = 19.8 inches. Single drive only. | 52 |
| 5190004 | S | Code-rear Tire Qty 04 | 0 |
| 5212020 | S | FF: Accu-Lite Steel Armor 51487PK 22.5X8.25 PHP10-5 hand holes. | 0 |
| 5312020 | S | RR: Accu-Lite Steel Armor 51487PK 22.5X8.25 PHP10-5 hand holes. | 0 |
| 5390004 | S | Code-rear Rim Qty 04 | 0 |
| Fuel Tanks | | | |

Price Level: July 1, 2020
Deal: OMES 220
Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021
Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/ Opt | Description | Weight |
|---------------------------------|----------|--|--------|
| 5576020 | S | 45 Gallon Rectangular Fuel Tank LH BOC | 0 |
| 5604045 | S | Location LH BOC 45 Gallon | 0 |
| 5652890 | S | DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab. | 0 |
| 5652990 | S | DEF To Fuel Ratio 2:1 Or Greater | 0 |
| 5655059 | S | DEF Tank Rectangular 7.5 Gallon Capacity | 0 |
| Battery Box & Bumper | | | |
| 6020010 | S | Steel Battery Box RH BOC Mounted on right-hand frame rail | 0 |
| 6030630 | S | Aluminum Battery Box Cover | 0 |
| 6121210 | S | Steel Bumper Painted Gray | 0 |
| Cab & Equipment | | | |
| 6520020 | S | Steel 63.5in BBC ProBilt Cab, LH Drive | 0 |
| 6914130 | S | Sears C2 Driver Seat | 0 |
| 6924130 | O | Sears C2 Passenger Seat | 0 |
| 6939400 | S | Air Ride Driver | 0 |
| 6939420 | S | High Back Driver | 0 |
| 6939460 | S | Fabric Driver | 0 |
| 6939500 | O | Air Ride Passenger | 0 |
| 6939520 | O | High Back Passenger | 0 |
| 6939560 | S | Fabric Passenger | 0 |
| 7000015 | S | Adjustable Steering Column - Tilt Only | 0 |
| 7001540 | S | Rear Wall Storage | 0 |
| 7001620 | S | Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button. | 0 |
| 7039180 | S | Interior Gray Includes view window in RH door and 18 inch 4-spoke foam soft-touch steering wheel. | 0 |

Price Level: July 1, 2020

Deal: OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/ Opt | Description | Weight |
|--------------|----------|---|--------|
| 7210540 | S | Day Cab Rear Window Day cab rear window flush to back of cab. | 0 |
| 7230060 | S | 1-Piece Curved Windshield | 0 |
| 7230170 | S | Electric Powered Window Lift, LH/RH Side | 0 |
| 7322010 | S | Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. | 0 |
| 7561170 | S | LH/RH Driving Mirrors Heated/Motorized Heated and motorized mirrors for left and right sides. | 0 |
| 7722120 | S | ConcertClass, AM/FM, Weatherband, 3.5 Aux | 0 |
| 7728040 | O | Bluetooth Phone and Audio | 0 |
| 7728050 | O | USB Port | 0 |
| 7851480 | S | Peterbilt Electric Windshield Wipers With Intermittent Feature. | 0 |
| 7901130 | O | Backup Alarm (107 DB) | 3 |
| 8021380 | S | Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall | 0 |
| 8041200 | S | Dual Scale Speedometer MPH Over KPH | 0 |
| 8111150 | S | Headlights Dual Round Halogen, Integral Turn Signals | 0 |
| 8121010 | S | (5) Marker Lights | 0 |
| 8133270 | S | Fog / Driving Lights | 0 |
| 8133960 | S | Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles. | 0 |
| 8143270 | S | Stop/Tail/Turn/Backup Lights RHLH | 0 |
| Paint | | | |
| 8530340 | S | Axalta Single Stage Non-Metallic Cab/Hood (Solid Color Paint) N85020 A - M8870EA ICE WHITE DAF N85200 FRAME L0001EA BLACK | 0 |
| 8531330 | S | Medium Duty Paint Color M8870 Ice White Lead Time for Ice White Cab is 12 weeks. | 0 |

Shipping Destination

Options Not Subject To Discount

Price Level: July 1, 2020

Deal: OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7



| Sales Code | Std/Opt | Description | Weight |
|----------------------|---------|--|--------|
| 9400091 | S | Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km | 0 |
| 9400093 | S | PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs | 0 |
| Miscellaneous | | | |
| 9409831 | O | 2021 EPA Emissions Engine Warranty Only | 0 |

Promotions

Order Comments

Total Weight

9,886

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: July 1, 2020

Deal: OMES 220

Printed On: 1/16/2021 9:21:45 AM

Date: January 13, 2021

Quote Number: QUO-761901-P6N8L7