

Item # 100029768
 Medium Duty, 54,000 -
 66,000 # Truck

Rush Truck Center

Make Bidding: Peterbilt
 Model Bidding: 389
 Model Code: 389

Can this Vehicle come ALT
 Fuel Equipped?? YES/NO:

No

Body & Chassis	Minimum Specification	
GWR	66,000	Yes
Curb Weight/Payload	Mfg. Std. List Size	17881 lbs / 48119 lbs.
Chassis CA	104" CA, Clear Frame Rail	Yes
Style, Cab/Tilt Hood	Tilt Hood or Low Cab Forward, List	Tilt Cab
Axle, Min Front Rating, lb/axle	20,000 LB. with Springs	Yes
Axle, Min Rear Rating, lb/axle	48,000 LBS/CR, with Walking Beam Type.	Yes
Frame, RBM, Min. In-b	3,200,000 Double Frame "C" Channel Reinforcement	Yes
Cab Mounts	Air Ride Cab	Yes
Engine		
Engine Type	Diesel Turbocharged	Yes
Engine Cyl/HP/Gross Torque, Min.	Inline 6 Cyl / 8 Liter or Larger / 1350 LBFT	Cummins X15 450V/1650 Lb/Ft
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press.	Yes
Air Cleaner System	List Capacity	1 15" Air Cleaner w/ Stainless straps
Transmission		
Trans. Type/Speeds, Min.	Allison 4500RDS 6 Spd.	Yes
Transmission ECU	Mounted in Cab	Yes
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory Instal. Include "C" Reinforcement to front	N/A with this model
PTO	Rt/Lt Side 10 bolt.	Yes
Electrical		
Alternator/Rating Cap/Min (amps)	12 Volt/ 130 Amp	100 Amp Brushed
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	(3) Paccar Dual Purpose Batt 2100 CCA
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Block Heater Min.	1000 Watt	Immersion Type Block heater 110V
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		Yes
Body Bulder Wiring to Rear of Frame		5 BOC
Power Supply	12 Volt Power Supply in Dash	Yes
Fuel		
Fuel Tank Capacity	90 Gallon Minimum	Yes
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 1 Electric Horn	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes
Grill	Chrome Grille Mount Bug Screen	Yes
Courtesy Lights	Mounted Below Each Door	Yes
Handles	Grab Handles Both Sides	Yes
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Power windows
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes
Radio	AM/FM	Yes
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min.	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes
Safety		
Brakes	Air Brakes W/ Compressor W/ Air Dryer & Drain Valve, 18.5 in x 5 in	Yes 18.7 CFM Compressor
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	Hendrickson Haulmax HMX 40 46,000lb
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	20 Ply, 315/80R 22.5	Yes
Tires, Tubeless, Size/Tread Rear	11R22.5/14 Ply/ Load G, Mud/Snow Tread	Yes
Warranty		
3 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	Towing included for two years with engine or trans failure only
PURCHASE PRICE:		\$134,854.00
3 YR LEASE/MO		\$0.00
4 YR LEASE/MO		\$0.00
5 YR LEASE/MO		\$0.00
MSRP FOR PURCHASE PRICE:		\$178,840.00

Item # 1000029768
 Medium Duty, 54,000 -
 66,000 # Truck

Dealer Name: Rush Truck Center

Make Bidding: Peterbilt

Model Bidding: 389

Model Code: 389

Engines	Options		Purchase	3 YR Lease
Gas Engine	List Specs	N/A		
Diesel Engine	330HP/900 LBFT	Paccar MX13 405@1600	-\$5,156	
Software/Cable	Software/Cable	J-PRO DLA Reader Diag	\$5,750	
CNG Engine	BiFuel - List Capacities	N/A		
CNG Engine	Dedicated - List Capacity	N/A		
Air Cleaner System	Higher Capacity - List Additional Capacity	Standard equipment		
Dust Shield	Dust Shield for Snow Removal Operations	Dust shields for front and rear brakes only	\$75	
Transmission				
Front PTO	Front Mounted PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille, Factory Install Include "C" Reinforcement to Front	N/A with this model		
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Fuller FRO165010C-10 Speed	-\$18,128	
Front Axle				
Front Axle	16000 lb w/ 16,000 Springs	14,600lbs front axle	-\$943	
Front Axle	18000 lb with 18000 Springs	N/A		
Body & Chassis				
CA	Decrease to 120" CA, Clear	Yes	-\$250	
CA	Decrease to 138" CA, Clear	Yes	-\$200	
CA	Decrease to 150" CA, Clear	Yes	-\$150	
CA	Decrease to 186" CA, Clear	Yes	-\$75	
Body	4 Door Crew Cab	N/A		
Frame	Delete Frame Reinforcement C Channel Type 120,000 PSI	Yes	-\$1,023	
Frame	Front Frame Extension W/O PTO Adaptor	N/A		
Axle, Min Front Rating/lb/seals	12,000/Oil, with Springs	N/A	-\$1,411	
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil, with Articulating Susp.	Yes	-\$1,757	
Electrical				
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)	275 Amp 40SI Brushless	\$696	
Worklights	Worklight Accommodation Package, List Specs	(1) 6" Spot light and (2) load lights	\$252	
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame			
Exterior				
Screen	Grille Mounted Bug Screen	Yes	\$122	
Mirrors	Heated Mirrors	Standard equipment	\$0	
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Yes	\$4,500	
Exhaust	Horizontal	Yes	\$204	
Grille	Stationary Grille	N/A		
Interior				
AC	Delete AC	N/A		
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	Yes	\$324	
Tilt & Cruise	Tilt Wheel & Cruise Control	Yes	\$336	
Safety	Air Bag Both Sides	N/A		
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	N/A		
Keys	3 Additional Keys Per Truck	Yes	\$20	
Visor	Visor over Windshield	Yes Stainless Steel	\$327	
Tire Inflator Tool	Air Cab Blower with Tire Inflator Tool	Installed @ dealership	\$100	
Windows	Power Windows	Yes	\$45	

Refuse Electronics Package	All items necessary for Refuse Package	Yes	\$250	
Safety				
Alarm	Park Brake Alarm	Yes	\$0	
Hydraulic Brakes	Deduct for Hydraulic Brakes	N/A		
Tires & Wheels				
Tires	Rear Tires, Highway tread	Yes	-\$250	
Spare Wheel	Steel Spare Wheel	Yes	\$250	
Tires for 14,000 lb Axle	List Specs	16 Ply 12R 22.5		
Tires for 16,000 lb Axle	List Specs	N/A		
Tires for 18,000 lb Axle	List Specs	N/A		
Towing				
Hooks	Front Tow Hooks	Standard equipment	\$0	
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring	Yes	\$565	
Delivery				
Delivery Cost	Price to Deliver Truck more than 150 miles	Yes	1.50 per mile	
Other				
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	N/A		
Options not listed	Discount off MSRP for options not listed	25% off list		



Rush Pblt Truck Centers (O500)
 8700 West I-40
 Oklahoma City, Oklahoma 73128

Stock

Chaz Eubank
 Cell Phone: 405-782-3502
 Office Phone: 405-782-3500
 Email: eubankc@rush-enterprises.com

Stock Order

Vehicle Summary

Unit		Chassis	
Model:	Model 389	Fr Axle Load (lbs):	20000
Type:	Tractor	Rr Axle Load (lbs):	46000
Description 1:	OMES 389	G.C.W. (lbs):	66000
Description 2:			
Application		Road Conditions:	
Intended Serv.:	General Freight	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:		Wheelbase (in):	226
Length (ft):	0	Overhang (in):	54.7
Height (ft):	0	Fr Axle to BOC (in):	92.8
Max Laden Weight (lbs):	0		
		Cab to Axle (in):	133.2
		Cab to EOF (in):	187.9
		Overall Comb. Length (in):	857
Trailer		Special Req.	
No. of Trailer Axles:	2		
Type:	Flatbed		
Length (ft):	53		
Height (ft):	13.5		
Kingpin Inset (in):	36		
Corner Radius (in):	2		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

389 MODEL
54-66, 000lb



Rush Pblt Truck Centers (O500)
8700 West I-40
Oklahoma City, Oklahoma 73128

Stock

Chaz Eubank
Cell Phone: 405-782-3502
Office Phone: 405-782-3500
Email: eubankc@rush-enterprises.com

Stock Order

Vehicle Summary

Model:	Unit	Model 389	Fr Axle Load (lbs):	20000
Type:		Tractor	Rr Axle Load (lbs):	46000
Description 1:		OMES 389	G.C.W. (lbs):	66000
Description 2:				
Intended Serv.:	Application	General Freight	Road Conditions:	
Commodity:		Other Commodity	Class A (Highway)	100
			Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	Body		Class D (Off-Road)	0
Type:			Maximum Grade:	6
Length (ft):		0	Wheelbase (in):	226
Height (ft):		0	Overhang (in):	54.7
Max Laden Weight (lbs):		0	Fr Axle to BOC (in):	92.8
			Cab to Axle (in):	133.2
	Trailer		Cab to EOF (in):	187.9
No. of Trailer Axles:		2	Overall Comb. Length (in):	857
Type:		Flatbed		
Length (ft):		53	Special Req.	
Height (ft):		13.5		
Kingpin Inset (in):		36		
Corner Radius (in):		2		
	Restrictions			
Length (ft):		65		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	Weight
Base Model			
0003891	S	Model 389 The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability.	14,915
0091200	S	Other Commodity	0
0093170	S	General Freight Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0
0096060	O	Flatbed A flat trailer with no enclosure or doors. Can be loaded/unloaded from the sides or above, and does not require elevated access for forklifts.	0
0098170	S	United States Registry	0
Configuration			
0200700	O	Not Applicable Secondary Manufacturer	0
Frame & Equipment			
0515020	O	10-5/8" Steel Rails 286-325" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	89
0601500	O	Full Steel Inner Liner	625
0644000	S	EOF Tractor Tapered with Crossmember Includes Kingpin Cutout	0
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0
0854010	S	Fifth Wheel Not Furnished	0
0940330	S	No Access Package or Deckplate Desired Use with tractors without access package or deckplate	0
Front Axle & Equipment			
1011360	O	Dana Spicer D2000F 20,000 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis	111

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/ Opt	Description	Weight
		EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	119
1243010	O	Power Steering Sheppard M100 Dual For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	71
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	2
1354850	O	PHP10 Iron PreSet PLUS Hubs-Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	42
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0
1390610		40mm Front Spring Spacer Blocks	0
Rear Axle & Equipment			
1523440	O	Dana Spicer D46-172 46,000 LBS Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity.	521
1616300	O	PHP10 Iron PreSet PLUS Hubs	0
1680390	S	Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0
1680450	O	Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion.	9
1680460	O	Heavy Wall, Drive Axle(s)	88
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over	0

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/Opt	Description	Weight
		current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1704560	O	Ratio 4.56 Rear Axle	0
1824410	O	Hendrickson HMX EX 460 46,000 LBS., 54" Haulmaax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	223

Engine & Equipment

2059790	O	X15 450V@1900 GOV@2000 1650@950 Productivity Series (2021 Emissions) N21350 C121 64....Maximum Accelerator Vehicle N21370 C128 64....Maximum Cruise Control Speed N21460 C132 1400..PTO Maximum Engine Speed N21520 C133 5.....Idle Shutdown Timer N21610 C188 39....Idle Shutdown Cold Ambient A N21630 C190 80....Idle Shutdown Hot Ambient Ai N21510 C225 YES...Idle Shutdown with Parking B N21450 C231 NO....Gear Down Protection N21570 C233 NO....Idle Shutdown Manual Overrid N21440 C234 NO....Engine Protection Shutdown N21480 C238 NO....Cruise Control and Engine Br N21470 C239 NO....Cruise Control Auto-Resume N21590 C382 YES...Idle Shutdown Hot Ambient Au N21530 C396 YES...Idle Shutdown Warning Period N21540 C397 60....Idle Shutdown Warning Period N21320 C399 120...Green House Gas Vehicle Spee N21620 C189 60....Idle Shutdown Intermediate A N21550 C206 100...Idle Shutdown Percent Engine N21340 C209 120...Maximum Vehicle Speed N21430 C333 0.....Driver Initiated OverrideMax N21410 C334 0.....Driver Initiated Override Ma N21500 C395 0.....Green House Gas Automatic En N21400 C400 252...Driver Initiated Overide Re N21420 C401 10....Green House Gas Vehicle Spee N21330 C402 0.....Green House Gas Vehicle Spee	292
2091305	S	Engine Idle Shutdown Timer Enabled	0
2091315	O	Enable EIST Ambient Temp Overrule	0



Sales Code	Std/ Opt	Description	Weight
2091372		Eff EIST NA Expiration Miles	0
2091640		Effective VSL Setting NA	0
2092013	O	Typical Operating Speed 60 MPH	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	4
2539715	O	Kissling Battery Disconnect Switch Terminals Mounted Inside Battery Box	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
2723220	O	Naturally Aspirated 18.7 CFM Air Compressor X15 Only	17
2812170	O	Intebrake (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0
2921220	O	Fuel Heat for Fuel Filter	0
2921310	S	No Electric Heat Option for Fuel Filter	0

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/ Opt	Description	Weight
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0
3213500	S	(1) 15" Painted Air Cleaner Cowl Mtd, Painted Cap Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake. Stainless steel air cleaner straps, brackets, & fasteners provide a durable bright finish.	0
3365270	S	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	0
3381770	O	Curved Tip Standpipe(s)	1
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0
Transmission & Equipment			
4052420	O	Allison 4500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-4.70, 2nd-2.21, 3rd-1.53, 4th-1.00, 5th-0.76, 6th-0.67. Reverse ratios: DR-(5.55).	310
4210190	O	1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing	90
4216590	O	1710 Driveline Interaxle For tandem rear axles	0
4252890	O	Allison FuelSense 2.0 Not Desired	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0
4256740	O	Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 transmission only	0

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/ Opt	Description	Weight
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	0
Air & Trailer Equipment			
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	-8
4540420	S	Nylon Chassis Hose	0
4541490	O	Tractor Air System, Spring Brake Relay IPO QR-1C Functions as a quick release valve for the emergency side of the spring brakes.	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	6
4612800	S	Trailer Hand Valve, Column Mounted Controls	0
4614810	S	AE Connections BOC/BOS, Hose Tenna	0
Tires & Wheels			
5064010	O	FF: BR 20ply 315/80R22.5 M870 Efficiency Rating: Fair Diameter= 42.8 inches; SLR= 19.9 inches The Bridgestone M870 is a high scrub All-Position Radial tire designed specifically for urban waste collection.	94
5169440	O	RR: BR 16ply 11R22.5 M853 Efficiency Rating: Poor Diameter= 41.8 inches; SLR= 19.4 inches	192
5190008	S	Code-rear Tire Qty 08	0
5210550	O	FF: Accur Stl Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	74
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0
5390008	S	Code-rear Rim Qty 08	0

Fuel Tanks

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/ Opt	Description	Weight
5554130	O	26" Aluminum 80 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	20
5602080	O	Location LH U/C 80 Gallon	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0
5652990	S	DEF To Fuel Ratio 2:1 Or Greater	0
5655019	S	DEF Tank Small 11.1 Gallon Capacity	0
5760010	O	RH Tank None Furnished	-86
Battery Box & Bumper			
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	-20
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0
6122050	O	Steel Bumper Tapered Painted Two tow points	-30
Cab & Equipment			
6510140	S	Alum Cab 123in BBC Alum Hood SFFA fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.	0
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
6700000	S	No Sleeper Selected	0
6911170	S	Sears Driver Seat	0

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/ Opt	Description	Weight
		Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	
6921170	S	Sears Passenger Seat	0
		Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	
6939400	S	Air Ride Driver	0
6939420	S	High Back Driver	0
6939470	S	Vinyl Driver	0
6939500	O	Air Ride Passenger	43
6939520	S	High Back Passenger	0
6939570	S	Vinyl Passenger	0
7000005	S	Fixed Steering Column	0
7000350	S	Power Door Locks Both Doors	0
7001620	S	Steering Wheel With Peterbilt Logo	0
		Steering Wheel with embossed Peterbilt logo over horn button.	
7039050	S	ProBilt Interior - Arctic Gray	0
		Includes rugged charcoal instrument panels, gray dash with glare-resistant, charcoal soft-touch upper, dark gray hard trim, black bezels on gauges, cigar lighter and ashtray with power port, monochromatic dark gray durable doorpads with map pocket on driver's side, dark gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted domelight, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, cup holder and map bin in dash.	
7210540	S	Day Cab Rear Window	0
		Day cab rear window flush to back of cab.	
7230350	O	2-Piece Flat Windshield	0
7230680	S	Power Lift Windows - Both Doors	0
		For use with ProBilt or Prestige Interior	
7322010	S	Combo Fresh Air Heater/Air Conditioner	0
		With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	
7330700	S	Peterbilt Comfort Control - Cab	0
7521030	O	Moto Mirror Traditional, Heated and Motorized	2
		Motorized head movement delivers better range and visibility than mirrors with glass movement alone with a rugged and durable	

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/Opt	Description	Weight
		construction that lasts. Film heater which provides superior heat distribution and durability.	
7560850	S	(2) Convex 8 Inch SSTL Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	0
7610470	S	(1) Air Horn 24.5" Chrome - Round w/Horn Shield	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	4
7728050	O	USB Port	0
7748140	O	CB Terminals/Wiring Mounted Under Header	0
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0
7788058	O	24 Months SmartLINQ Subscription Cummins Engines.	0
7851040	O	Removable Bugscreen Behind Grille	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
7851970	O	Unibilt Cab Air Suspension Includes dual air bag suspension, leveling valve, and tracking rod. Provides a more ergonomic installation, higher EAU, easier serviceability and fewer parts.	25
7900040	O	Fire Extinguisher, Ship Loose Hazmat approved UL listed/rated ABC.	7
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7901130	O	Backup Alarm (107 DB)	3
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Sales Code	Std/Opt	Description	Weight
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
8111140	S	Headlights Projector Module Pod Integral Turn Signals	0
8120980	S	(5) Marker Lights, Aero LED	0
8140000	S	Incandescent Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	0
Paint			
8500710	O	Standard Paint Color Selection	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE N85720 SK FAIRINGS L0006EY WHITE	0
Shipping Destination			
Options Not Subject To Discount			
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0
Miscellaneous			
9409000	S	Day Cab / ProBilt Interior (DB)	0
9409831	S	2021 EPA Emissions Engine Warranty Only	0

Promotions

Order Comments

Price Level: July 1, 2020

Deal: OMES 389

Printed On: 1/19/2021 9:46:50 AM

Date: January 14, 2021

Quote Number: QUO-761873-L0G2Y6



Total Weight

17,881

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information