

Item # 100009333  
 Medium Duty, 33,000 #  
 Truck

Dealer Name: Rush Truck Center

Make Bidding: Peterbilt

Model Bidding: 337

Model Code: 337

Yes

Can this Vehicle come ALT Fuel Equipped?? YES/NO:

Body & Chassis	Standard Specification	
GVWR	33,000	Yes
Curb Weight/Payload	Mfg. Std. List Size	10,595 lbs
Chassis CA	102" CA, Clear Frame Rail	Yes
Style, Cab/Tilt Hood	Tilt Hood	Yes
Axle, Min Front Rating/lb/seals	12,000 lbs w/ springs	Yes
Axle, Min Rear Rating/lb/spd/seals	21,000 lbs, Oil, Walking Beam Type	Yes
Suspension, Front/Rear, lb	12,000/21,000	Yes
Frame, RBM, Min, in-lb	120,000 PSI	Yes
Cab Mounts	Air Ride Cab	Yes
<b>Engine</b>		
Engine Type	Diesel Turbocharged, Wet Sleeve Type	Yes
Engine Cy/GHP/Gross Torque, Min	Inline 6 Cy/270 HP/800 Torque	Yes PX-9 270 HP 800 @ 1300
Electronic Shutdown	High Water Temp/Low Oil Press	Yes
Governor	Electronic Control PTO Provision	Yes
Air Cleaner System	List Capacity	Radial Seal, Dry Type Frontal Entry
<b>Transmission</b>		
Trans. Type/Speeds, Min	Alison 3500 RDS 6 Speed	Yes
Transmission ECU	Mounted in Cab	Yes
PTO	Rt/Li Side 10 Bolt	Yes
<b>Electrical</b>		
Alternator/Rating Cap/Mn (amps)	12 Volt/ 130 Amp	12 Volt 180Amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CCA	(2) AGM 12V Batteries 1800 CCA
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Radio Wiring Harness	Two Way Radio Wiring Harness in Headler Console	Yes
Body Builder wiring/Rear of frame		Body Connections 5' BGC
Block Heater Min	1000 Watt	Immersion Type Block heater 110-120V
<b>Fuel</b>		
Fuel Tank Capacity, L (gal) Min	70 Gallon minimum	26" Aluminum 70 Gallon
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes
<b>Exterior</b>		
Paint	Cab-White Base Coat Clear Coat, Frame-Running Gear-Black	Yes
Exhaust, Type	Horizontal	Yes
Horn	Air Electric	Yes
Mirrors	Power Mirrors, Heated, Right and Left	Yes
Handles	Grab Handles Both Sides	Yes
Grill	Chrome Grill Mount Bug Screen	Yes
Courtesy Lights	Mounted Below Each Door	Yes
<b>Doors &amp; Windows</b>		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Power windows included with motorized/mtd mirrors
Keys	3 Additional Keys	Yes
<b>Floor</b>		
Floor Covering	Vinyl/Rubber	Yes
<b>Interior</b>		
Air Conditioning and Heater	Front AC Req	Yes
Radio	AM/FM	Yes
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Power Supply	12 Volt Power Supply in Cab	Yes
<b>Seats</b>		
Seating Capacity min.	2 Passenger	Yes
Seats	Air Suspension Driver & Passenger	Yes
<b>Safety</b>		
Brakes	Air Brakes with 13.2 cfm Compressor, Air Dryer, Air Horn, Auto Drain Valve	yes 18.7 CFM
Restraint System All Pass	Req	Yes
Alarm	Back-Up Alarm	Yes
<b>Tires &amp; Wheels</b>		
Wheels, Type	Disc	Yes
Tires, Tubeless, Size/Tread Front	11R/22.5, 14 Ply Load G	Yes
Tires, Tubeless, Size/Tread Rear	11R/22.5, 14 Ply Load G, Mud/Snow Tread	Yes
<b>Warranty</b>		
2 Yr/Unlimited Mile Warranty	Includes towing for warrantable failure	Yes (engine or transmission failure only)
PURCHASE PRICE:		\$80,843
3 YR LEASE/MO		\$0
4 YR LEASE/MO		\$0
5 YR LEASE/MO		\$0
MSRP FOR PURCHASE PRICE:		\$95,820

Item # 100009333  
 Medium Duty, 33,000 #  
 Truck

Dealer Name: Rush Truck Center

Make Bidding: Peterbilt

Model Bidding: 337

Model Code: 337

Engines	Options		Purchase	3 YR Lease	4 YR Lease	5 YR Lease
Engine Diagnostic Reader Software/Cable	Software/Cable	J-PRO DLA reader w/ 1yr subscription	\$0.125			
Air Filter	Increase Capacity	N/A				
Diesel Engine	300HP/800LBFY	PX-6 300 HP 865 LB FY	\$691			
Gas Engine	List Specs	N/A				
CNG Engine	BIFuel - List Capcities	N/A				
CNG Engine	Dedicated - List Capacity	Cummins L9N 320 HP w 73 DGE BOC system	\$56,340			
Air Cleaner System	Higher Capacity - List Additional Capacity	N/A				
Dust Shield	Dust Shield for Snow Removal Operations	N/A				
<b>Transmission</b>						
PTO Front	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille, Factory Install. Cannot be both.	FEPTO Provision 27" Bumper Extension	\$1,066			
Transmission	6 Speed, Manual, Direct Drive	Fulter FS08406A 6 Speed	-\$8,015			
<b>Rear Axle</b>						
Rear Axle	23,000 LB, 2-Spd Rear Axle with 23,000 LB Springs, includes 4500 LB Auxiliary Springs.	Dens Spicer 23082T 23,000 lb w/ springs and 4500lb helper	\$2,506			
<b>Electrical</b>						
Switch	High Amp (for attenuator, snowboard, excess lighting, etc.)	Yes	\$500			
Worklights	Worklight Accomodation Package, List Specs	(1) 6" spotlight (2) Lead Lights mounted low outboard	\$125			
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Yes	\$500			
<b>Body &amp; Chassis</b>						
CA	Decrease To 84" CA, clear frame	Yes	\$0			
CA	Increase to 120" CA, clear frame	Yes	\$0			
CA	Increase to 138" CA w/120,000 PSI	Yes	\$0			
CA	Increase to 156" CA w/120,000 PSI	Yes	\$0			
Body	4 Door Crew Cab	Waldons MFG (Aftermarket) w/std Interior pkg	\$21,250			
Reinforcement	Increase frame to 120,000 PSI With "C" Channel Reinforcement	Full Steel Liner	\$925			
Suspension	Air Ride Rear Suspension	Peterbilt Low Air Leaf 21 000lb	\$150			
Frame	Front Frame Extension WithOut PTO Adaptation		N/A			
Front Extension	"C" Channel Reinforcement to Front of Frame	Included in full steel liner pricing above	\$0			
<b>Exterior</b>						
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)	Yes	\$4,500			
Mirrors	Heated Mirrors	Included in base price	\$0			
Exhaust	Vertical	Exhaust single RH side of cab w/ 24" standpipe curved	\$128			
Screen	Grille Mounted Bug Screen	Included in base price				
<b>Interior</b>						
Tire Inflator	List Specs	air line attachment w/ 50' air line	\$250			
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger	air ride driver and non-air 2 passenger bench	\$0			
Tilt & Cruise	Tilt Wheel & Cruise Control	Included in base price				
Safety	Air Bags Both Sides	N/A				
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)	N/A				
Visor	Visor over Windshield	Stainless Steel	\$167			
<b>Fuel</b>						
Larger Fuel Capacity	100 Gallon Minimum	Yes	\$100			
<b>Safety</b>						
Alarm	Park Brake Alarm	Std equipment	\$0			
Hydraulic Brakes	Deduct for Hydraulic Brakes	Hydraulic front and rear brakes	\$1,016			
<b>Tires &amp; Wheels</b>						
Tires	Highway Tread Rear Tires		-\$250			
<b>Towing</b>						
Hooks	Front Tow Hooks	Included in base price				
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring	A&E Conn EOF w/7-way socket and trailer hand valve	\$405			
<b>Delivery</b>						
Delivery Cost	Price to Deliver Truck more than 150 miles		1.50/mile			
<b>Other</b>						
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify	N/A				
Options not listed	Discount off MSRP for options not listed	25% off list				



Rush Pblt Truck Centers (O500)  
 8700 West I-40  
 Oklahoma City, Oklahoma 73128

Stock

William Duncan  
 Cell Phone: 405-922-4093  
 Office Phone: 405-782-3508  
 Email: duncanw@rushenterprises.com

Stock Order

## Vehicle Summary

Unit		Chassis	
Model:	Model 337	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	21000
Description 1:	OMES 337	G.C.W. (lbs):	33000
Description 2:			
<b>Application</b>		<b>Road Conditions:</b>	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
<b>Body</b>		Maximum Grade:	6
Type:	Van	Wheelbase (in):	178
Length (ft):	24	Overhang (in):	62.8
Height (ft):	13.5	Fr Axle to BOC (in):	69.8
Max Laden Weight (lbs):	1000		
		Cab to Axle (in):	108.2
		Cab to EOF (in):	171
		Overall Comb. Length (in):	279
<b>Trailer</b>		<b>Special Req.</b>	
No. of Trailer Axles:	0		
Type:			
Length (ft):	0		
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
<b>Restrictions</b>			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	Weight
<b>Base Model</b>			
0003371	S	<b>Model 337</b> The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	10,070
0091200	S	<b>Other Commodity</b>	0
0093340	S	<b>City Delivery</b> Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0
0095040	S	<b>Van</b>	0
0098170	S	<b>United States Registry</b>	0
<b>Configuration</b>			
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0
<b>Frame &amp; Equipment</b>			
0515030	S	<b>10-5/8" Steel Rails to 285"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	118
0612160	O	<b>178" Wheelbase</b>	0
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0
<b>Front Axle &amp; Equipment</b>			
1011875	O	<b>Dana Spicer E1202IL 12,000 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 lb. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	0
1111190	O	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	0
1243040	S	<b>Power Steering Sheppard HD94</b> Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 12,000 to 14,000 lb. axle ratings.	0
1250180	O	<b>Power Steering Reservoir Frame Mounted</b>	0

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/Opt	Description	Weight
		The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	
1354845	S	PHP10 Iron PreSet Hubs	0
1380260	S	<b>Bendix Air Cam Front Drum Brakes 16.5x5</b> For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
1391410	S	Gusseted Cam Brackets, Steer Axle	0
<b>Rear Axle &amp; Equipment</b>			
1513270	O	Dana Spicer S21-172 Single Axle, 21000 lb	250
1616370	S	PHP10 Iron PreSet Hubs	0
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680950	S	<b>Stability System Not Selected Or Not Available</b>	0
1681337	S	Single Drive Axle (Model 337)	0
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
1687010	S	<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1705250	O	Ratio 5.25 Rear Axle	0
1816140	S	Reyco 79KB Taper Leaf 21,000 lb	0
<b>Engine &amp; Equipment</b>			
2074212	O	<b>PACCAR PX-9 270@2000 GOV@2200 860@1200</b> Productivity (2021 EMISSIONS)	0
		N21350 C121 65...Maximum Accelerator Pedal Ve	
		N21370 C128 65...Maximum Cruise Speed (P059)	
		N21460 C132 1400..Max PTO Speed (P046)	

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/ Opt	Description	Weight
		N21520 C133 5....Timer Setting (P030)	
		N21610 C188 39....Low Ambient Temperature Thre	
		N21630 C190 80....High Ambient Temperature Thr	
		N21510 C225 YES...Enable Idle Shutdown Park Br	
		N21450 C231 NO....Gear Down Protection (P026)	
		N21570 C233 NO....Idle Shutdown Manual Overrul	
		N21440 C234 NO....Engine Protection Shutdown (	
		N21480 C238 NO....Auto Engine Brake in Cruise	
		N21470 C239 NO....Cruise Control Auto Resume (	
		N21590 C382 YES...Enable Hot Ambient Automatic	
		N21530 C396 YES...Enable Impending Shutdown Wa	
		N21540 C397 60....Timer For Impending Shutdown	
		N21620 C189 60....Intermediate Ambient Tempera	
		N21550 C206 100...Engine Load Threshold (P516)	
		N21340 C209 120...Hard Maximum Speed Limit (P1	
		N21430 C333 0.....Reserve Speed Limit Offset (	
		N21410 C334 0.....Maximum Cycle Distance (N202	
		N21500 C395 0.....Expiration Distance (N209)	
		N21320 C399 120...Standard Maximum Speed Limit	
		N21400 C400 252...Reserve Speed Function Reset	
		N21420 C401 10....Maximum Active Distance (N20	
		N21330 C402 0.....Expiration Distance (N207)	
2091305	O	<b>Engine Idle Shutdown Timer Enabled</b>	0
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0
2091640		<b>Effective VSL Setting NA</b>	0
2092016	O	<b>Typical Operating Speed 62 MPH</b>	0
2092032	O	<b>Powertrain Optimized for Performance</b> Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2140200	S	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2522110	S	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b> PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
2538030	S	<b>2 PACCAR Premium 12V Starting Batteries 2000 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/Opt	Description	Weight
2539740	O	<b>Kissling Battery Disconnect Switch, 300 amp</b> Mounted on battery box	3
2621090	S	<b>DM Advantage ON/OFF Fan Clutch</b> Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
2921160	S	<b>Spin-On Fuel/Water Separator</b>	0
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0
2921310	S	<b>No Electric Heat Option for Fuel Filter</b>	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0
3211120	S	<b>Radial Seal, Dry Type Air Cleaner, Frontal</b> Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
3365280	S	<b>Exhaust Single RH Horizontal</b> DPF/SCR RH Under Cab.	0

### Transmission & Equipment

4052230	O	<b>Allison 3500 RDS-P Transmission, Gen 5</b> Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-4.59, 2nd-2.25, 3rd-1.54, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.00).	195
4210080	S	<b>1710 HD Driveline, 1 Midship Bearing</b>	0
4252890	O	<b>Allison FuelSense 2.0 Not Desired</b>	0
4252940	O	<b>Allison Neutral At Stop</b>	0

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/ Opt	Description	Weight
		Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	
4256680	O	Allison 6-Speed Configuration, Wide Ratio Gears	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	0
<b>Air &amp; Trailer Equipment</b>			
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0
4520420	O	Pull Cords All Air Tanks	0
4540420	S	Nylon Chassis Hose	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	4
<b>Tires &amp; Wheels</b>			
5061050	O	FF: BR 14ply 11R22.5 R284 Ecopia Efficiency Rating: Optimal	-4
5169440	O	RR: BR 16ply 11R22.5 M853 Efficiency Rating: Poor Diameter= 41.8 inches; SLR= 19.4 inches	92
5190004	O	Code-rear Tire Qty 04	0
5211990	S	FF: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0
5390004	O	Code-rear Rim Qty 04	0
<b>Fuel Tanks</b>			
5534190	O	23" Aluminum 100 Gallon Fuel Tank LH U/C	-106

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/ Opt	Description	Weight
		Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	
5602100	O	Location LH U/C 100 Gallon	0
5652880	O	<b>DEF Tank Mounted RH BOC</b> You have selected a Diesel Exhaust Fluid (DEF) tank mounted on the right-hand (passenger) side of the vehicle. Note, some retail fuel distributors have chosen to standardize on DEF dispensing pumps oriented to the left-hand (driver) side of the vehicle. Please verify your selection for DEF tank mounting.	0
5652980	O	DEF To Fuel Ratio Between 1:1 And 2:1	0
5655019	O	DEF Tank Small 11.1 Gallon Capacity	0
<b>Battery Box &amp; Bumper</b>			
6010670	O	Aluminum Space Saver Battery Box LH BOC Battery access from side	-84
6030150	O	Rubber Battery Pad In Bottom of (1) Battery Box Mat in box that holds batteries only	4
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0
6121180	S	Steel Styled Aero Bumper Painted Cab Color Two tow points	0
<b>Cab &amp; Equipment</b>			
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0
6911700	S	National Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
6921700	O	National Passenger Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
6939400	O	Air Ride Driver	0
6939420	S	High Back Driver	0
6939470	S	Vinyl Driver	0
6939500	O	Air Ride Passenger	43
6939540	S	Low Back Passenger	0

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/Opt	Description	Weight
6939570	S	Vinyl Passenger	0
7000015	S	Adjustable Steering Column - Tilt Only	0
7001620	S	<b>Steering Wheel With Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0
7036120	S	<b>Interior Gray/Black</b> Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0
7230060	S	<b>1-Piece Curved Windshield</b>	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7560100	O	<b>Mirrors SSTL Each Side Heated and Motorized</b> with Switch on Door.	2
7564110	S	<b>Power Package</b> Includes power door locks and power windows.	0
7610020	O	<b>(1) Air Horn 15" Painted</b> Mounted under cab.	8
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	10
7725710	O	<b>Standard Speaker Package For Cab</b> (2) Speakers	4
7728040	O	<b>Bluetooth Phone and Audio</b>	0
7728050	O	<b>USB Port</b>	0
7748140	O	<b>CB Terminals/Wiring Mounted Under Header</b>	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0
7851780	O	<b>CabMate Cab Air Suspension</b> Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	15
8011400	O	<b>Main Transmission Oil Temperature Gauge</b> Located in Driver Information Display	0
8021015	O	<b>Air Application Gauge</b>	0

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/Opt	Description	Weight
		Located in Driver Information Display	
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0
8071870	S	<b>Main Instrumentation Panel, Graphics Display</b> Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral park, turn, and side marker	0
8120980	S	<b>(5) Marker Lights, Aero LED</b>	0
8140120	S	<b>Incandescent Square Stop/Turn/Tail/Backup</b> Left-hand / right-hand square end of frame or dropped a-brace	0
<b>Paint</b>			
8500710	O	<b>Standard Paint Color Selection</b>	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0
<b>Shipping Destination</b>			
<b>Options Not Subject To Discount</b>			
9400091	S	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0
9400094	S	<b>PACCAR PX-9 Standard Coverage</b> 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0
<b>Miscellaneous</b>			
9409831	O	<b>2021 EPA Emissions Engine</b> Warranty Only	0
<b>Promotions</b>			

Price Level: July 1, 2020

Deal: OMES 337

Printed On: 1/16/2021 9:24:22 AM

Date: January 13, 2021

Quote Number: QUO-761811-R3K8F4



Sales Code	Std/ Opt	Description	Weight
------------	-------------	-------------	--------

**Order Comments**

**Total Weight**

10,624

**Prices and Specifications Subject to Change Without Notice.**

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

**PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*