

Item # 100009383
 Medium Duty, 46,000 -
 54,000 # Truck

Dealer Name: Rush Truck Center

Make Bidding: Peterbilt
 Model Bidding: 348
 Model Code: 348
 Yes

LT Fuel Equipped?? YES/NO:

Body & Chassis		
GVWR	54,000	Yes
Curb Weight/Payload	Mfg. Std. List Size	Yes
Chassis CA	102" CA, Clear Frame Ref	Yes
Style, Cab/Tilt Hood	Tilt Hood	Yes
Axle, Min Front Rating/lb/axle	14,000/LB with Springs	Yes, 14,000 Springs
Axle, Min Rear Rating/lb/spd/axle	40,000 LBS/Oil with Walking Beam Type	Yes
Frame, RBM, Min. In-b	3,200,000 Double Frame "C" Channel Reinforcement	Yes
Cab Mounts	Air Ride Cab	Yes
Engine		
Engine Type	Diesel Turbocharged	Yes PX-9 300 HP @ 2000 RPM, 800 @ 1200
Engine Cyl/GHP/Gross Torque, Min	Inline 6 Cyl / 8 Liter or Larger / 850LBFT	Yes
Governor	Electronic PTO Provision	Yes
Electronic Engine Shutdown	High Water Temp/Low Oil Press.	Yes
Air Cleaner System	List Capacity	1,000 Square Inch
Transmission		
Trans. Type/Speeds, Min.	Allison 3000RDS 8 Spd.	Yes
Transmission ECU	Mounted in Cab	Yes
PTO Front Mount	Front Mounted PTO Adaptation with Integral Frame Extension/Bumper with Stationary Grille. Factory Install. Include "C" Reinforcement to front	Yes
PTO	R/L Side 10 bolt.	Yes
Electrical		
Alternator/Rating Cap/Min (amps)	12 Volt/ 130 Amp	12 Volt 160 Amp
Battery, CCA @ 0 deg F/Reserve	Two/1500 CAA	2-2,000 CCA's
Disconnect Switch	Battery Disconnect Switch	Yes
Jump Start Stud	Mounted Outside Battery Box	Yes
Block Heater Min.	1000 Watt	Yes Immersion Type Block Heater
Radio Wiring Harness	Two Way Radio Wiring Harness in Header Console	Yes
Header Console		N/A
Body Builder Wiring to Rear of Frame		Yes
Power Supply	12 Volt Power Supply in Dash	Yes
Additional Wiring	Snowplow Light Electrical Wiring to Front of Frame	Yes, Installed at Dealer
Fuel		
Fuel Tank Capacity	100 Gallon Minimum	Yes
Fuel Filters	Primary & Fuel Water Separator, Heated	Yes
Exterior		
Paint	Cab-White Base Coat/Clear Coat, Frame/Running Gear-Black	Yes
Exhaust, Type	Vertical	Yes
Horn	1 Air Horn & 2 Electric Horn	1 Air/ 1 Electric
Mirrors	Power Mirrors, Heated, Right and Left	Yes
Grill	Chrome Grill Mount Bug Screen	Yes
Courtesy Lights	Mounted Below Each Door	Yes
Handles	Grab Handles Both Sides	Yes
Doors & Windows		
Doors	2 Doors	Yes
Door Locks	1 Keyed Doors	Yes
Windows	Roll Up Windows	Yes/ Passenger power
Floor		
Floor Covering	Vinyl/Rubber	Yes
Interior		
Air Conditioning and Heater	Front AC Required	Yes
Radio	AM/FM	Yes
Hand Throttle	Electronic	Yes
Gauges	All W/ Tach & Hour Meter List	Yes
Seats		
Seating Capacity min.	2 Passenger	Yes
Seats	Two (2) Air Suspension- Driver & Passenger	Yes
Safety		
Brakes	Air Brakes W/ 12 cu. ft. Compressor W/ Air Dryer & Drain Valve	Yes, 18.7 CFM
Alarm	Back-Up Alarm	Yes
Restraint System All Pass	Required	Yes
Suspension		
Suspension/Shocks	Mfg. Std. List Size	Hendrickson Haulmax HMX-40
Tires & Wheels		
Wheels, Type	Disc 10	Yes
Tires, Tubeless, Size/Tread Front	12R/22 5/14 Ply/ Load G	Yes
Tires, Tubeless, Size/Tread Rear	11R/22 5/14 Ply/ Load G, Mud/Snow Tread	Yes
Warranty		
2 Yr/Unlimited Mile Warranty	Includes Towing for Warrantable Failure	Yes Towing Included w/ Engine or Trans failure
PURCHASE PRICE		\$94,224.00
3 YR LEASE/MO		\$9.00
4 YR LEASE/MO		\$9.00
5 YR LEASE/MO		\$9.00
MSRP FOR PURCHASE PRICE:		\$120,298.00

Item # 100009383
 Medium Duty, 46,000 -
 54,000 # Truck

Dealer Name: Rush Truck Center

Make Bidding: Peterbilt

Model Bidding: 348

Model Code: 348

Engines	Options		Purchase	3 YR Lease	4 YR Lease	5 YR Lease
Gas Engine	List Specs	N/A				
Diesel Engine	330HP/900 LBFT		\$706			
Software/Cable	Software/Cable	Yes				
CNG Engine	Bifuel - List Capacities	N/A				
CNG Engine	Dedicated - List Capacity	L9N 320@2000, 1000@1300	\$22,053			
Air Cleaner System	Higher Capacity - List Additional Capacity	Std. Equip.				
Dust Shield	Dust Shield for Snow Removal Operations	Dust shields F/A & R/A	\$56			
Transmission						
Delete Front PTO	Delete Front PTO Adaptation with Integral Frame Extension/Front Bumper with Stationary Grille	Yes				
Transmission	10 Speed, Manual, O/D with "C" Series Rating	Fuller FRO14210C (10 Spd)	-\$6,779			
Front Axle						
Front Axle	12000 lb W/ 12000 Springs	Yes	-\$285			
Front Axle	16000 lb w/ 16,000 Springs	Yes				
Front Axle	18000 lb with 18000 Springs		\$1,596			
Body & Chassis						
CA	Increase to 120" CA, Clear		\$0			
CA	Increase to 136" CA, Clear		\$0			
CA	Increase to 150" CA, Clear		\$0			
CA	Increase to 166" CA, Clear		\$0			
Body	4 Door Crew Cab	Weldons Mig. Aftermarket Crew Cab	\$21,555			
Frame	Delete Frame Reinforcement C Channel Type. 120,000 PSI		-\$745			
Frame	Front Frame Extension W/O PTO Adaptor		\$0			
Axle, Min Front Rating/lb/seals	12,000/Oil with Springs		\$0			
Axle, Min Rear Rating/lb/spd/seals	40,000/Oil with Articulating Susp.		\$0			
Electrical						
Switch	High Amp (for attenuator, arrowboard, excess lighting, etc.)		\$500			
Worklights	Worklight Accommodation Package, List Specs		\$200			
Exterior						
Screen	Grille Mounted Bug Screen		\$150			
Mirrors	Heated Mirrors		-\$200			
Custom Paint Color	Chrome Yellow (Per FAA Guidelines)		\$5,000			
Exhaust	Horizontal		-\$300			
Grille	Stationary Grille		\$0			
Interior						
AC	Delete AC		n/a			
Seats	3 Passenger - Air Suspension Driver, 2 Man Passenger		\$100			
Tilt & Cruise	Tilt Wheel & Cruise Control		\$75			
Safety	Air Bag Both Sides		N/A			
Instrument Panel	Ergonomic Instrument Panel (Wrap-Around)		Yes			
Keys	3 Additional Keys Per Truck		\$10			
Visor	Visor over Windshield		\$175			
Tire Inflator Tool	Air Cab Blower with Tire Inflator Tool		\$100			
Safety						
Alarm	Park Brake Alarm		Std.			
Hydraulic Brakes	Deduct for Hydraulic Brakes		N/A			
Tires & Wheels						
Tires	Rear Tires, Highway tread		\$0			
Spare Wheel	Steel Spare Wheel		\$350			
Tires for 14,000 lb Axle	List Specs		\$0			
Tires for 16,000 lb Axle	List Specs		N/A			
Tires for 18,000 lb Axle	List Specs		\$150			
Towing						
Hooks	Front Tow Hooks		\$0			
Trailer Connection	Air & Electric, 4 Wheel W/ Hand Control Valve/Tractor Protection Valve/7 Way Wiring		\$500			
Delivery						
Delivery Cost	Price to Deliver Truck more than 150 miles		1.50 per/mile			
Other						
Deduct for orders of multiple vehicles to same location	List # of vehicles to qualify		n/a			
Options not listed	Discount off MSRP for options not listed					



348 MODEL
46-54,000 lb.

Rush Pblt Truck Centers (O500)
8700 West I-40
Oklahoma City, Oklahoma 73128

Stock

Chaz Eubank
Cell Phone: 405-782-3502
Office Phone: 405-782-3500
Email: eubankc@rush-enterprises.com

Stock Order

Vehicle Summary

Model:	Unit	Model 348	Fr Axle Load (lbs):	14600
Type:		Full Truck	Rr Axle Load (lbs):	40000
Description 1:		OMES 348	G.G.W. (lbs):	54600
Description 2:				
Intended Serv.:	Application	City Delivery	Road Conditions:	
Commodity:		Other Commodity	Class A (Highway)	100
			Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
			Class D (Off-Road)	0
Type:	Body	Van	Maximum Grade:	6
Length (ft):		24	Wheelbase (in):	178
Height (ft):		13.5	Overhang (in):	62.8
Max Laden Weight (lbs):		1000	Fr Axle to BOC (in):	69.8
			Cab to Axle (in):	108.2
			Cab to EOF (in):	171
No. of Trailer Axles:	Trailer	0	Overall Comb. Length (in):	279
Type:				
Length (ft):		0	Special Req.	
Height (ft):		0		
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	Restrictions			
Length (ft):		65		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____ Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	Weight
Base Model			
0003481	S	Model 348 The Model 348 was designed to exceed the rigid demands of Class 7 and Class 8 specialty application markets that require rugged durability and a wide range of optional content. The Model 348 represents a multi-dimensional performer with a GVW from 33,000 to 66,000 lbs. and optional capacity ratings to suit almost any vocation. The 348 is also available in a specifically designed all-wheel-drive configuration. From construction and crane service to utility and delivery services in both Class 7 and Class 8 markets, the 348 is in a class by itself.	10,610
0091200	S	Other Commodity	0
0093340	S	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0
0095040	S	Van	0
0098170	S	United States Registry	0
Configuration			
0200700	S	Not Applicable Secondary Manufacturer	0
Frame & Equipment			
0515030	S	10-5/8" Steel Rails to 285" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	133
0601500	O	Full Steel Inner Liner	501
0612160	O	178" Wheelbase	0
0613090	S	Three-Piece Crossmembers	0
0620550	O	FEPTO Provision 3.2in Bumper Extension Includes Crankshaft Adapter Plate and Stationary Grille	86
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0
0651090	S	Omit Rear Mudflaps and Hangers	0
Front Axle & Equipment			
1011350	O	Dana Spicer E1462I 14,600 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel	53

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/Opt	Description	Weight
		economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	
1112150	O	Taper Leaf Springs, Shocks 14,600 lb Hendrickson Taper Leaf Springs, shocks 14,6000 lb.	57
1233050	O	Power Steering TRW TAS85 TRW TA85 Power Steering for use with 14,600 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	7
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0
1354845	S	PHP10 Iron PreSet Hubs	0
1380260	S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
1391410	S	Gusseted Cam Brackets, Steer Axle	0
Rear Axle & Equipment			
1523300	O	Dana Spicer DSP41 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	2,071
1616370	S	PHP10 Iron PreSet Hubs	0
1680450	O	Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion.	9
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
1680950	S	Stability System Not Selected Or Not Available	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the	0

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/Opt	Description	Weight
		lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
1687348	O	Tandem Drive Axle (Model 348)	0
1705290	O	Ratio 5.29 Rear Axle	0
1824400	O	Hendrickson HMX EX 400 40,000 Lbs., 54" Haulmaax, 60K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	523

Engine & Equipment

2074307	O	PACCAR PX-9 300@2000 GOV@2200 860@1200 Productivity (2021 Emissions)	0
		N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21630 C190 80....High Ambient Temperature Thr N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21590 C382 YES...Enable Hot Ambient Automatic N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21620 C189 60....Intermediate Ambient Tempera N21550 C206 100...Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21500 C395 0.....Expiration Distance (N209) N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)	
2091305	O	Engine Idle Shutdown Timer Enabled	0
2091315	O	Enable EIST Ambient Temp Override	0



Sales Code	Std/Opt	Description	Weight
2091372		Eff EIST NA Expiration Miles	0
2091640		Effective VSL Setting NA	0
2092016	O	Typical Operating Speed 62 MPH	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0
2140150	O	Remote PTO and Throttle Provision 12-pin connector on engine harness.	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
2522110	S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
2921160	S	Spin-On Fuel/Water Separator	0
2921210	S	No Fluid Heat Option for Fuel Filter	0
2921310	S	No Electric Heat Option for Fuel Filter	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, &	0

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/ Opt	Description	Weight
		reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
3365270	O	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	29
3381770	O	Curved Tip Standpipe(s)	0
3387870	O	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0
Transmission & Equipment			
4052110	O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	195
4210080	S	1710 HD Driveline, 1 Midship Bearing	0
4252890	O	Allison FuelSense 2.0 Not Desired	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions.	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	0
Air & Trailer Equipment			
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and	0

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/ Opt	Description	Weight
		oil aerosols before they can contaminate the moisture removing desiccant.	
4540420	S	Nylon Chassis Hose	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	4
Tires & Wheels			
5069460	O	FF: BR 16ply 12R22.5 M853 Diameter= 43.2 inches; SLR= 20.0 inches	68
5169440	O	RR: BR 16ply 11R22.5 M853 Efficiency Rating: Poor Diameter= 41.8 inches; SLR= 19.4 inches	184
5190008	O	Code-rear Tire Qty 08	0
5211990	S	FF: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0
5390008	O	Code-rear Rim Qty 08	0
Fuel Tanks			
5534190	O	23" Aluminum 100 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	20
5602100	O	Location LH U/C 100 Gallon	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0
5652990	S	DEF To Fuel Ratio 2:1 Or Greater	0
5655019	S	DEF Tank Small 11.1 Gallon Capacity	0
Battery Box & Bumper			
6010780	O	Aluminum Space Saver Battery Box RH BOC	-84

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/Opt	Description	Weight
		Battery access from side	
6030150	O	Rubber Battery Pad In Bottom of (1) Battery Box Mat in box that holds batteries only	4
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0
6121060	O	Steel Bumper Swept Back Painted Black, With FEPTO Two tow pin holes and step plates on top of bumper	90
Cab & Equipment			
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0
6540120	O	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	39
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
6911700	S	National Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
6921700	S	National Passenger Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
6939400	S	Air Ride Driver	0
6939420	S	High Back Driver	0
6939470	S	Vinyl Driver	0
6939500	O	Air Ride Passenger	43
6939520	S	High Back Passenger	0
6939570	S	Vinyl Passenger	0
7000015	S	Adjustable Steering Column - Tilt Only	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0
7036120	S	Interior Gray/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4)	0

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/Opt	Description	Weight
		inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0
7230060	S	1-Piece Curved Windshield	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
7560100	O	Mirrors SSTL Each Side Heated and Motorized with Switch on Door.	2
7564110	S	Power Package Includes power door locks and power windows.	0
7610020	O	(1) Air Horn 15" Painted Mounted under cab.	8
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	10
7725710	O	Standard Speaker Package For Cab (2) Speakers	4
7728050	O	USB Port	0
7748140	O	CB Terminals/Wiring Mounted Under Header	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
7851780	O	CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	15
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
7900270	O	Fire Extinguisher, Cab Mounted Hazmat approved UL listed/rated ABC	8
7901130	O	Backup Alarm (107 DB)	3
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night	0

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Sales Code	Std/Opt	Description	Weight
		mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0
8120980	S	(5) Marker Lights, Aero LED	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	0
Paint			
8500710	S	Standard Paint Color Selection	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0
Shipping Destination			
Options Not Subject To Discount			
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0
Miscellaneous			
9409831	O	2021 EPA Emissions Engine Warranty Only	0

Promotions

Order Comments

Total Weight

14,710

Prices and Specifications Subject to Change Without Notice.

Price Level: July 1, 2020

Deal: OMES 348

Printed On: 1/19/2021 9:45:29 AM

Date: January 13, 2021

Quote Number: QUO-761159-Q7S6M8



Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information