

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

## S P E C I F I C A T I O N P R O P O S A L

### Description

#### Price Level

WST 47X/49X PRL-27X (EFF:MY24 ORDERS)

#### Data Version

SPECPRO21 DATA RELEASE VER 008

#### Vehicle Configuration

WESTERN STAR 47X  
2024 MODEL YEAR SPECIFIED  
SET FORWARD AXLE - TRUCK  
TRAILER TOWING PROVISION AT END OF  
FRAME WITH SAE J560, WITHOUT END OF  
FRAME AIR CONNECTIONS  
LH PRIMARY STEERING LOCATION

#### General Service

TRUCK CONFIGURATION  
DOMICILED, USA (EXCLUDING CALIFORNIA AND  
CARB OPT-IN STATES)  
CONSTRUCTION SERVICE  
GOVERNMENT BUSINESS SEGMENT  
DIRT/SAND/ROCK COMMODITY  
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN  
TRANSIT, IS SPENT ON PAVED ROADS  
MAXIMUM 8% EXPECTED GRADE  
SMOOTH CONCRETE OR ASPHALT PAVEMENT -  
MOST SEVERE IN-TRANSIT (BETWEEN SITES)  
ROAD SURFACE  
WESTERN STAR VOCATIONAL WARRANTY  
EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

EXPECTED REAR DRIVE AXLE(S) LOAD :  
21000.0 lbs  
EXPECTED GROSS VEHICLE WEIGHT CAPACITY  
: 33000.0 lbs

**Truck Service**

END DUMP BODY  
3-V DISTRIBUTING INC

**Engine**

CUM L9 270 HP @ 2200 RPM; 2200 GOV RPM,  
860 LB-FT @ 1200 RPM

**Electronic Parameters**

75 MPH ROAD SPEED LIMIT  
PTO MODE ENGINE RPM LIMIT - 1400 RPM  
PTO MODE BRAKE OVERRIDE - SERVICE  
BRAKE APPLIED  
PTO RPM WITH CRUISE SET SWITCH - 700 RPM  
PTO RPM WITH CRUISE RESUME SWITCH - 700  
RPM  
ONE REMOTE PTO SPEED  
PTO SPEED 1 SETTING - 900 RPM  
PTO MINIMUM RPM - 700  
PTO 1, DASH SWITCH, ENGAGE BEFORE  
DRIVING

**Engine Equipment**

2010 EPA/CARB/GHG21 CONFIGURATION  
NO 2008 CARB EMISSION CERTIFICATION  
STANDARD OIL PAN  
ENGINE MOUNTED OIL CHECK AND FILL  
SIDE OF HOOD AIR INTAKE WITH ENGINE  
MOUNTED AIR CLEANER  
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD  
ALTERNATOR WITH REMOTE BATTERY VOLT  
SENSE  
(3) DTNA GENUINE, FLOODED STARTING, MIN  
3000CCA, 555RC, THREADED STUD BATTERIES  
BATTERY BOX WITH ALUMINUM COVER  
MOUNTED SHORT SIDE TO RAIL  
SINGLE BATTERY BOX FRAME MOUNTED LH  
SIDE BACK OF CAB  
WIRE GROUND RETURN FOR BATTERY CABLES  
WITH ADDITIONAL FRAME GROUND RETURN

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

---

UNPOLISHED ALUMINUM WST BATTERY BOX COVER

POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT

POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM

C-BRAKE BY JACOBS WITH LOW/OFF/HIGH BRAKING DASH SWITCH

RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER

11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT

RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP

13 GALLON DIESEL EXHAUST FLUID TANK

UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP

PERFORATED SINGLE STAINLESS STEEL MUFFLER/TAILPIPE SHIELD WITH WESTERN STAR LOGO

AIR POWERED ON/OFF ENGINE FAN CLUTCH

AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED

DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

1400 SQUARE INCH VOCATIONAL RADIATOR

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

#### Description

---

ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT  
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT  
RADIATOR DRAIN VALVE  
LOWER RADIATOR GUARD  
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER  
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR  
ELECTRIC GRID AIR INTAKE WARMER  
DELCO 12V 39MT HD/OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH

#### Transmission

ALLISON 3500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

#### Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV  
ALLISON VOCATIONAL RATING FOR CONCRETE MIXER APPLICATIONS ONLY AVAILABLE WITH 3000 PRODUCT FAMILIES  
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY  
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY  
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE  
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE  
PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE  
SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE  
QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

CUSTOMER INSTALLED CHELSEA 280 SERIES  
PTO  
PTO MOUNTING, LH SIDE OF MAIN  
TRANSMISSION ALLISON  
MAGNETIC PLUGS, ENGINE DRAIN,  
TRANSMISSION DRAIN, AXLE(S) FILL AND  
DRAIN  
HEAVY DUTY ELECTRONIC TRANSMISSION  
SHIFT CONTROL, COLUMN MOUNTED  
WATER TO OIL TRANSMISSION COOLER  
TRANSMISSION OIL CHECK AND FILL WITH  
ELECTRONIC OIL LEVEL CHECK  
SYNTHETIC TRANSMISSION FLUID (TES-295  
COMPLIANT)

**Front Axle and Equipment**

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74  
DROP SINGLE FRONT AXLE  
CONMET PRESET PLUS PREMIUM IRON FRONT  
HUBS  
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT  
BRAKES, DOUBLE ANCHOR, FABRICATED  
SHOES  
NON-ASBESTOS FRONT BRAKE LINING  
GUNITE CAST IRON FRONT BRAKE DRUMS  
FRONT BRAKE DUST SHIELDS  
FRONT OIL SEALS  
VENTED FRONT HUB CAPS WITH WINDOW,  
CENTER AND SIDE PLUGS - OIL  
GUNITE AUTOMATIC FRONT SLACK  
ADJUSTERS  
SINGLE POWER STEERING GEAR, BENDIX, 12-  
13.3K  
2 QUART SEE THROUGH POWER STEERING  
RESERVOIR  
CURRENT AVAILABLE SYNTHETIC 75W-90  
FRONT AXLE LUBE

**Front Suspension**

12,000# DUAL TAPERLEAF FRONT SUSPENSION  
THREADED SPRING PINS AND BUSHINGS -  
FRONT SUSPENSION  
FRONT SHOCK ABSORBERS

**Rear Axle and Equipment**

**Prepared for:**  
 CINI  
 ZACHARIA  
 OKLAHOMA STATE OF  
 5005 N LINCOLN  
 BLVD  
 OKLAHOMA CITY, OK 73105  
 Phone: 405-521-2116

**Prepared by:**  
 Mike Sartin  
 PREMIER TRUCK GROUP OF  
 TULSA  
 5104 W. 60TH STREET  
 TULSA, OK 74107  
 Phone: 918-445-5300 ext 4061

**Description**

RS-23-160 23,000# R-SERIES SINGLE REAR  
 AXLE  
 CONMET PRESET PLUS PREMIUM IRON REAR  
 HUBS  
 5.38 REAR AXLE RATIO  
 IRON REAR AXLE CARRIER WITH STANDARD  
 AXLE HOUSING  
 MXL 17T MERITOR EXTENDED LUBE MAIN  
 DRIVELINE WITH HALF ROUND YOKES  
 NO INTERAXLE (#3) DRIVELINE  
 DRIVER CONTROLLED TRACTION  
 DIFFERENTIAL - SINGLE REAR AXLE  
 (1) DRIVER CONTROLLED DIFFERENTIAL LOCK  
 REAR VALVE FOR SINGLE DRIVE AXLE  
 INDICATOR LIGHT FOR EACH DIFFERENTIAL  
 LOCKOUT SWITCH  
 MERITOR 16.5X8.62 Q+ CAST SPIDER HEAVY  
 DUTY CAM REAR BRAKES, DOUBLE ANCHOR,  
 FABRICATED SHOES  
 NON-ASBESTOS REAR BRAKE LINING  
 BRAKE CAMS AND CHAMBERS ON REAR SIDE  
 OF DRIVE AXLE(S)  
 GUNITE CAST IRON REAR BRAKE DRUMS  
 NO REAR BRAKE DUST SHIELDS  
 REAR OIL SEALS  
 BENDIX EVERSURE LONGSTROKE 3-DRIVE  
 AXLES SPRING PARKING CHAMBERS  
 HALDEX AUTOMATIC REAR SLACK ADJUSTERS  
 CURRENT AVAILABLE SYNTHETIC 75W-90 REAR  
 AXLE LUBE  
 STANDARD REAR AXLE BREATHER(S)

**Rear Suspension**

23,000# FLAT LEAF SPRING REAR SUSPENSION  
 WITH RADIUS ROD  
 8.5 INCH NOMINAL RIDE HEIGHT (430MM  
 GLOBAL REFERENCE HEIGHT)  
 STANDARD AXLE SEATS IN AXLE CLAMP  
 GROUP  
 FORE/AFT CONTROL RODS  
 NO REAR SHOCK ABSORBERS

**Brake System**

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

#### Description

WABCO 4S/4M ABS WITH TRACTION CONTROL  
WITH ATC SHUT OFF SWITCH  
REINFORCED NYLON, FABRIC BRAID AND WIRE  
BRAID CHASSIS AIR LINES  
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,  
NO REAR PROPORTIONING VALVE  
WABCO SYSTEM SAVER HP WITH INTEGRAL  
AIR GOVERNOR AND HEATER  
AIR DRYER FRAME MOUNTED  
STEEL AIR BRAKE RESERVOIRS  
BW DV-2 AUTO DRAIN VALVE WITH HEATER TO  
WET TANK; DRAIN VALVE CABLES ON ALL  
OTHER TANKS

#### Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED  
FOR SEPARATE STOP/TURN, ABS CENTER PIN  
POWERED THROUGH IGNITION  
SAE J560 7-WAY PRIMARY TRAILER CABLE  
RECEPTACLE MOUNTED END OF FRAME

#### Wheelbase & Frame

4790MM (189 INCH) WHEELBASE, SFA ONLY  
13.0MM X 87.0MM X 311.0MM STEEL FRAME  
(0.51X3.43X12.24 INCH) 120 KSI  
950MM (37 INCH) REAR FRAME OVERHANG  
FRAME OVERHANG RANGE: 31 INCH TO 40  
INCH  
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :  
107.09 in  
CALC'D FRAME LENGTH - OVERALL : 254.8 in  
FRAME HEIGHT TOP FRONT UNLADEN : 41.33 in  
FRAME HEIGHT TOP FRONT LADEN : 39.12 in  
FRAME HEIGHT TOP REAR UNLADEN : 42.77 in  
FRAME HEIGHT TOP REAR LADEN : 27.68 in  
FLANGE TAPERED END OF FRAME, GRIND AND  
POLISH WELDS  
STANDARD WEIGHT ENGINE CROSSMEMBER  
STANDARD CROSSMEMBER BACK OF  
TRANSMISSION  
STANDARD CAST ALUMINUM MIDSHIP  
HEAVY DUTY REAR CROSSMEMBER  
STANDARD SUSPENSION CROSSMEMBER

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

CAST ALUMINUM REAR SUSPENSION  
CROSSMEMBER

**Chassis Equipment**

UNPOLISHED ALUMINUM WST EQUIPMENT  
COVERS  
PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL  
BUMPER  
REMOVABLE FRONT TOW/RECOVERY  
DEVICE, STORED ON CHASSIS FRAME  
BUMPER MOUNTING FOR SINGLE LICENSE  
PLATE  
CLASS 10.9 THREADED METRIC FASTENERS;  
REAR SUSPENSION HANGER TO BE HUCK-SPIN  
EXTERIOR HARNESSES WRAPPED IN  
ABRASION TAPE  
LEFT HAND SIDE HEAVY DUTY BRACKETS  
REQUIRED  
RIGHT HAND SIDE HEAVY DUTY BRACKETS  
REQUIRED

**Fuel Tanks**

80 GALLON/302 LITER ALUMINUM FUEL TANK -  
LH  
25 INCH DIAMETER FUEL TANK(S)  
POLISHING OF FUEL/HYDRAULIC TANK(S) WITH  
PAINTED BANDS  
FUEL TANK(S) FORWARD  
PLAIN STEP FINISH  
CHROME FUEL TANK CAP(S)  
EQUIFLO INBOARD FUEL SYSTEM  
HIGH TEMPERATURE REINFORCED NYLON  
FUEL LINE

**Tires**

BRIDGESTONE R213 ECOPIA 11R22.5 14 PLY  
RADIAL FRONT TIRES  
BRIDGESTONE M770 11R22.5 14 PLY RADIAL  
REAR TIRES

**Wheels**

ACCURIDE 28828 22.5X8.25 10-HUB PILOT 6.18  
INSET 2-HAND HD STEEL DISC FRONT WHEELS  
MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT  
5-HAND STEEL DISC REAR WHEELS  
FRONT WHEEL MOUNTING NUTS

**Prepared for:**  
 CINI  
 ZACHARIA  
 OKLAHOMA STATE OF  
 5005 N LINCOLN  
 BLVD  
 OKLAHOMA CITY, OK 73105  
 Phone: 405-521-2116

**Prepared by:**  
 Mike Sartin  
 PREMIER TRUCK GROUP OF  
 TULSA  
 5104 W. 60TH STREET  
 TULSA, OK 74107  
 Phone: 918-445-5300 ext 4061

	Description
	REAR WHEEL MOUNTING NUTS
<b>Cab Exterior</b>	
	111.6 INCH BBC CONVENTIONAL ALUMINUM CAB
	STAINLESS STEEL CAB ACCENT MOLDING
	FRONT FENDERS
	BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS
	INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES
	BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS
	X-SERIES STEEL REINFORCED ALUMINUM CAB
	X-SERIES VOCATIONAL HOOD
	HOOD OPENING ASSIST WITH LOCKING STRUT
	WESTERN STAR NAMEPLATES
	DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS
	SINGLE ELECTRIC HORN
	REAR LICENSE PLATE MOUNT END OF FRAME SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS, FOR LH & RH BACK OF CAB ROOF MOUNTING
	DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM
	ROOF MOUNTED LED MARKER LIGHTS
	DAYTIME RUNNING LIGHTS
	INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
	LED SIDE TURN SIGNAL
	C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR
	102 INCH EQUIPMENT WIDTH
	LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS
	RH DOWN VIEW MIRROR
	STANDARD SIDE/REAR REFLECTORS
	REAR REFLECTIVE DEVICE

**Prepared for:**  
 CINI  
 ZACHARIA  
 OKLAHOMA STATE OF  
 5005 N LINCOLN  
 BLVD  
 OKLAHOMA CITY, OK 73105  
 Phone: 405-521-2116

**Prepared by:**  
 Mike Sartin  
 PREMIER TRUCK GROUP OF  
 TULSA  
 5104 W. 60TH STREET  
 TULSA, OK 74107  
 Phone: 918-445-5300 ext 4061

**Description**

UNPOLISHED ALUMINUM WST  
 AFTERTREATMENT SYSTEM COVER  
 SINGLE SOLAR TINTED REAR WINDOW, (1) 31  
 INCH X 20 INCH  
 1-PIECE ROPED-IN SOLAR GREEN GLASS  
 WINDSHIELD  
 8 LITER (2 GAL) WINDSHIELD WASHER  
 RESERVOIR, CAB MOUNTED, WITH FLUID  
 LEVEL INDICATOR

**Cab Interior**

X-SERIES BASE INTERIOR TRIM LEVEL  
 PACKAGE  
 CHARCOAL BLACK VINYL BASE LEVEL  
 INTERIOR  
 CARBON WITH BASE BLACK ACCENT  
 BLACK MATS WITH ADDED FLOOR HEAT AND  
 NOISE INSULATION  
 (2) DASH MOUNTED POWER OUTLETS AND  
 COIN TRAY  
 FORWARD ROOF MOUNTED CONSOLE  
 LH AND RH DOOR STORAGE POCKETS  
 INTEGRATED INTO MOLDED DOOR PANELS  
 (2) COAT HOOKS ON BACKWALL OF CAB  
 DIGITAL ALARM CLOCK IN DRIVER DISPLAY  
 2-1/2 LB. FIRE EXTINGUISHER MOUNTED  
 INBOARD OF DRIVER SEAT  
 STANDARD HEATER PLUMBING WITH BALL  
 SHUTOFF VALVES AT SUPPLY LINES ONLY  
 RADIATOR MOUNTED AIR CONDITIONER  
 CONDENSER  
 STANDARD INSULATION  
 STANDARD LED CAB LIGHTING  
 REMOTE KEYLESS ENTRY AND 2  
 TRANSMITTERS  
 DOOR LOCKS AND IGNITION SWITCH KEYED  
 THE SAME  
 KEY QUANTITY OF 4  
 LH AND RH ELECTRIC DOOR LOCKS WITH  
 AUTO UNLOCK FEATURE WHEN DOOR IS SET  
 FROM OPEN TO CLOSED POSITION  
 BRIGHT DOOR HANDLES  
 TRIANGULAR REFLECTORS WITHOUT FLARES

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

PREMIUM 2.0 HIGH BACK AIR SUSPENSION  
DRIVER SEAT WITH 2 AIR LUMBAR,  
INTEGRATED CUSHION EXTENSION, TILT AND  
ADJUSTABLE SHOCK

PREMIUM 2.0 HIGH BACK AIR SUSPENSION  
PASSENGER SEAT WITH 2 AIR LUMBAR,  
INTEGRATED CUSHION EXTENSION, TILT AND  
ADJUSTABLE SHOCK

DUAL DRIVER SEAT ARMRESTS, NO  
PASSENGER SEAT ARMRESTS

BLACK MORDURA CLOTH DRIVER SEAT COVER  
WITH EMBROIDERED LOGO

BLACK MORDURA CLOTH PASSENGER SEAT  
COVER WITH EMBROIDERED LOGO

3 POINT HIGH VISIBILITY ORANGE ADJUSTABLE  
D-RING RETRACTOR DRIVER AND FIXED D-RING  
RETRACTOR PASSENGER SEAT BELTS

ADJUSTABLE TILT AND TELESCOPING  
STEERING COLUMN

4-SPOKE 18 INCH (450MM) BLACK STEERING  
WHEEL WITH SWITCHES

DRIVER AND PASSENGER INTERIOR SUN  
VISORS

**Instruments & Controls**

STOCK TRUCK/UPFIT PACKAGE LVL 1

STANDARD FOOT PEDAL SYSTEM

ELECTRONIC ACCELERATOR CONTROL

ENGINE REMOTE INTERFACE WITH PARK  
BRAKE INTERLOCK

BLACK GAUGE BEZELS

STANDARD CENTER INSTRUMENT PANEL

DUAL NEEDLE PRIMARY AND SECONDARY AIR  
PRESSURE GAUGE

INTAKE MOUNTED AIR RESTRICTION  
INDICATOR WITHOUT GRADUATIONS

ELECTRONIC CRUISE CONTROL WITH  
CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND  
INTEGRAL START POSITION; 4 POSITION  
OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0  
INCH TFT COLOR DISPLAY

DIGITAL PANEL LAMP DIMMER SWITCH IN  
DRIVER DISPLAY

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

---

HEAVY DUTY ONBOARD DIAGNOSTICS  
INTERFACE CONNECTOR WITH DUST CAP  
LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

ENGINE REMOTE INTERFACE NOT  
CONFIGURED

ELECTRICAL ENGINE COOLANT TEMPERATURE  
GAUGE

ENGINE OIL TEMPERATURE GAUGE

ELECTRIC ENGINE OIL PRESSURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE  
GAUGE

ELECTRONIC OUTSIDE TEMPERATURE  
SENSOR DISPLAY IN DRIVER MESSAGE  
CENTER

ENGINE, TRIP AND PTO HOUR METERS  
INTEGRAL WITHIN DRIVER DISPLAY

PTO CONTROLS FOR ENHANCED VEHICLE  
ELECTRIC/ELECTRONIC ARCHITECTURE

NO OBSTACLE DETECTION SYSTEM

ELECTRONIC STABILITY CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR  
LOCATED BEHIND PASSENGER SIDE  
REMOVEABLE DASH PANEL

TOP OF DASH RAM MOUNT WITHOUT POWER  
OR GROUND, FOR CUSTOMER FURNISHED  
DEVICE

AM/FM/WB WORLD TUNER RADIO WITH  
SIRIUSXM, BLUETOOTH, IPOD INTERFACE, USB  
AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

AM/FM ANTENNA MOUNTED ON RH SIDE  
MIRROR

POWER AND GROUND WIRING PROVISION  
OVERHEAD

ROOF/OVERHEAD CONSOLE CB RADIO  
PROVISION

SINGLE REMOTE SPEAKER WITH LEAD FOR 2-  
WAY RADIO

SINGLE FIBERGLASS LH MIRROR MOUNTED CB  
ANTENNA WITH BRACKET AND LEAD

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

HEADLINER MULTI-BAND ANTENNA:  
AM/FM/WEATHERBAND, WIFI/BLUETOOTH,  
GNSS/GPS  
INTEROPERABLE SDAR ANTENNA  
ELECTRONIC MPH SPEEDOMETER WITH  
SECONDARY KPH SCALE, WITHOUT  
ODOMETER  
ELECTRONIC 2500 RPM TACHOMETER  
DETROIT CONNECT PLATFORM HARDWARE  
IGNITION SWITCH CONTROLLED ENGINE STOP  
FOUR EXTRA HARDWIRED SWITCHES IN DASH,  
ROUTE TO UNDER CAB, CAPPED  
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10  
AMPS BATTERY POWER  
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10  
AMPS BATTERY POWER  
HARDWIRE SWITCH #3, ON/OFF LATCHING, 10  
AMPS BATTERY POWER  
HARDWIRE SWITCH #4, ON/OFF LATCHING, 10  
AMPS BATTERY POWER  
PRE-TRIP INSPECTION FEATURE FOR  
EXTERIOR LAMPS ONLY  
REAR SPRING LOADED HAND CONTROL BRAKE  
VALVE  
2 INCH TURBO AIR PRESSURE GAUGE  
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH  
DRIVER DISPLAY  
ROTARY HEADLAMP SWITCH, MARKER  
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT  
FOR OPTIONAL FOG/ROAD LAMPS  
ONE VALVE PARKING BRAKE SYSTEM WITH  
WARNING INDICATOR  
SELF CANCELING TURN SIGNAL SWITCH WITH  
DIMMER, HEADLAMP FLASH,  
WASH/WIPE/INTERMITTENT  
QUICKFIT POWERTRAIN INTERFACE  
CONNECTOR UNDER CAB WITH BLUNTCUTS

**Design**

PAINT: ONE SOLID COLOR

**Color**

CAB COLOR A: L0006EY WHITE ELITE EY  
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS  
PAINT

**Prepared for:**  
CINI  
ZACHARIA  
OKLAHOMA STATE OF  
5005 N LINCOLN  
BLVD  
OKLAHOMA CITY, OK 73105  
Phone: 405-521-2116

**Prepared by:**  
Mike Sartin  
PREMIER TRUCK GROUP OF  
TULSA  
5104 W. 60TH STREET  
TULSA, OK 74107  
Phone: 918-445-5300 ext 4061

---

**Description**

POWDER WHITE (N0006EA) FRONT  
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
POWDER WHITE (N0006EA) REAR  
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

**Certification / Compliance**

U.S. FMVSS CERTIFICATION, EXCEPT SALES  
CABS AND GLIDER KITS

**Extended Warranty**

TOWING: 2 YEARS/UNLIMITED MILES/KM EXTENDED TOWING  
COVERAGE \$750 CAP FEX APPLIES

(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.