

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

S P E C I F I C A T I O N P R O P O S A L

Description

Price Level

WST 47X/49X PRL-27X (EFF:MY24 ORDERS)

Data Version

SPECPRO21 DATA RELEASE VER 008

Vehicle Configuration

WESTERN STAR 47X
2024 MODEL YEAR SPECIFIED
SET FORWARD AXLE - TRUCK
TRAILER TOWING PROVISION AT END OF
FRAME WITH SAE J560, WITHOUT END OF
FRAME AIR CONNECTIONS
LH PRIMARY STEERING LOCATION

General Service

TRUCK CONFIGURATION
DOMICILED, USA (EXCLUDING CALIFORNIA AND
CARB OPT-IN STATES)
CONSTRUCTION SERVICE
CONSTRUCTION BUSINESS SEGMENT
DIRT/SAND/ROCK COMMODITY
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN
TRANSIT, IS SPENT ON PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
SMOOTH CONCRETE OR ASPHALT PAVEMENT -
MOST SEVERE IN-TRANSIT (BETWEEN SITES)
ROAD SURFACE
WESTERN STAR VOCATIONAL WARRANTY
EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

EXPECTED REAR DRIVE AXLE(S) LOAD :
46000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY
: 66000.0 lbs

Truck Service

Engine

DETROIT DD13 GEN 5 12.8L 410 HP @ 1625
RPM, 1900 GOV RPM, 1450 LB/FT @ 975 RPM

Electronic Parameters

65 MPH ROAD SPEED LIMIT
FLEET MANAGEMENT - DAILY ENGINE USAGE
ENABLED
PTO MODE ENGINE RPM LIMIT - 1400 RPM
PTO RPM CONTROL WITH STEERING WHEEL
SWITCHES
PTO MODE RPM INCREMENT - 25 RPM
PTO GOVERNOR RAMP RATE - 25 RPM PER
SECOND
ONE DASH MOUNTED PTO SPEED WITH PTO
SWITCH ENGAGEMENT
PTO SPEED 1 SETTING - 600 RPM
SOFT CRUISE CONTROL ENABLED
PTO MINIMUM RPM - 600
ENABLE AUTO ENGINE RPM ELEVATE FOR
EXTENDED IDLE
PTO 1, DASH SWITCH, ENGAGE BEFORE
DRIVING

Engine Equipment

2010 EPA/CARB/GHG21 CONFIGURATION
NO 2008 CARB EMISSION CERTIFICATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
SIDE OF HOOD AIR INTAKE WITH ENGINE
MOUNTED AIR CLEANER
LN 12V 170 AMP AVI 160 PAD MOUNT
ALTERNATOR
(3) DTNA GENUINE, FLOODED STARTING, MIN
3000CCA, 555RC, THREADED STUD BATTERIES
BATTERY BOX WITH ALUMINUM COVER
MOUNTED SHORT SIDE TO RAIL

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE BACK OF CAB

WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN

UNPOLISHED ALUMINUM WST BATTERY BOX
COVER

POSITIVE LOAD DISCONNECT WITH CAB
MOUNTED CONTROL SWITCH MOUNTED
OUTBOARD DRIVER SEAT

POSITIVE AND NEGATIVE POSTS FOR
JUMPSTART LOCATED ON FRAME NEXT TO
STARTER

BW MODEL FE-921 19.0 CFM SINGLE CYLINDER
AIR COMPRESSOR WITH SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM

JACOBS COMPRESSION BRAKE

RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND VIRTUAL REGENERATION REQUEST
SWITCH IN CLUSTER

11 FOOT 06 INCH (138 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT

30 DEGREE CURVE BRIGHT UPPER STACK(S)
AND ELBOW(S)

RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP

13 GALLON DIESEL EXHAUST FLUID TANK

UNPOLISHED ALUMINUM WST DIESEL
EXHAUST FLUID TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP

PERFORATED SINGLE STAINLESS STEEL
MUFFLER/TAILPIPE SHIELD WITH WESTERN
STAR LOGO

ELECTRONICALLY CONTROLLED VARIABLE
SPEED VISCOUS FAN DRIVE

AUTOMATIC FAN CONTROL WITH DASH
SWITCH AND INDICATOR LIGHT, NON ENGINE
MOUNTED

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

DETROIT FUEL/WATER SEPARATOR WITH BYPASS
DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR
FULL FLOW OIL FILTER
1400 SQUARE INCH VOCATIONAL RADIATOR WITH PROTECTION PACKAGE
ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT
HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER
CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR
MITSUBISHI 12V MOD 3.175-DP60 STARTER WITH INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV
ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP

ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR

CUSTOMER INSTALLED CHELSEA 280 SERIES PTO

PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN

HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED

WATER TO OIL TRANSMISSION COOLER

TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE

CONMET PRESET PLUS PREMIUM IRON FRONT HUBS

MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

GUNITE AUTOMATIC FRONT SLACK ADJUSTERS

DUAL POWER STEERING GEARS, BENDIX 16-20K

4 QUART POWER STEERING RESERVOIR

OIL/AIR POWER STEERING COOLER

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

CURRENT AVAILABLE SYNTHETIC 75W-90
FRONT AXLE LUBE

Front Suspension

20,000# TAPERLEAF FRONT SUSPENSION
MAINTENANCE FREE RUBBER BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

RT-46-160 46,000# R-SERIES TANDEM REAR
AXLE
CONMET PRESET PLUS PREMIUM IRON REAR
HUBS
4.56 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD
AXLE HOUSING
MXL 18T MERITOR EXTENDED LUBE MAIN
DRIVELINE WITH HALF ROUND YOKES
MXL 17T MERITOR EXTENDED LUBE INTERAXLE
DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER
CONTROLLED DIFFERENTIAL LOCK FORWARD-
REAR AND REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE
LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DIFFERENTIAL
LOCKOUT SWITCH
MERITOR 16.5X8.62 Q+ CAST SPIDER HEAVY
DUTY CAM REAR BRAKES, DOUBLE ANCHOR,
FABRICATED SHOES
NON-ASBESTOS REAR BRAKE LINING
STANDARD BRAKE CHAMBER LOCATION
GUNITE CAST IRON REAR BRAKE DRUMS
NO REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE
AXLE SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR
AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

Rear Suspension

HENDRICKSON HAULMAAX EX 46,000# REAR
SUSPENSION
9.5 INCH NOMINAL RIDE HEIGHT (460MM
GLOBAL REFERENCE HEIGHT)
54 INCH AXLE SPACING
HENDRICKSON HN, HAULMAAX AND ULTIMAAX
SERIES STEEL BEAMS WITH BAR PIN
FORE/AFT AND TRANSVERSE CONTROL RODS
DOUBLE REBOUND STRAP - INBOARD AND
OUTBOARD
REAR SHOCK ABSORBERS - TWO AXLES
(TANDEM)

Brake System

WABCO 4S/4M ABS WITH TRACTION CONTROL
WITH ATC SHUT OFF SWITCH
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER HP WITH INTEGRAL
AIR GOVERNOR AND HEATER
AIR DRYER FRAME MOUNTED
STEEL AIR BRAKE RESERVOIRS
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME

Wheelbase & Frame

7090MM (279 INCH) WHEELBASE, SFA ONLY
15.0MM X 89.0MM X 315.0MM STEEL FRAME
(0.59X3.5X12.4 INCH) 120 KSI
1750MM (69 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 61 INCH TO 70
INCH
24 INCH INTEGRAL FRONT FRAME EXTENSION
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
197.64 in

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

CALC'D FRAME LENGTH - OVERALL : 400.63 in
FRAME HEIGHT TOP FRONT UNLADEN : 44.54 in
FRAME HEIGHT TOP FRONT LADEN : 41.26 in
FRAME HEIGHT TOP REAR UNLADEN : 43.55 in
FRAME HEIGHT TOP REAR LADEN : 41.26 in
SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CAST ALUMINUM CROSSMEMBER
BACK OF TRANSMISSION
STANDARD CAST ALUMINUM MIDSHIP
STANDARD CAST ALUMINUM REARMOST
CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER
STANDARD WEIGHT REAR SUSPENSION
CROSSMEMBER

Chassis Equipment

UNPOLISHED ALUMINUM WST EQUIPMENT
COVERS
PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL
BUMPER
FRONT TOW HOOKS - FRONT FRAME
EXTENSION MOUNTED
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
BETTS B-83 PAINTED COILED SPRING HEAVY
DUTY MUDFLAP BRACKETS
CLASS 10.9 THREADED METRIC FASTENERS;
REAR SUSPENSION HANGER TO BE HUCK-SPIN
EXTERIOR HARNESSES WRAPPED IN
ABRASION TAPE
LEFT HAND SIDE HEAVY DUTY BRACKETS
REQUIRED
RIGHT HAND SIDE HEAVY DUTY BRACKETS
REQUIRED

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK -
LH
25 INCH DIAMETER FUEL TANK(S)
POLISHING OF FUEL/HYDRAULIC TANK(S) WITH
PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH

Prepared for:
 CINI
 ZACHARIA
 OKLAHOMA STATE OF
 5005 N LINCOLN
 BLVD
 OKLAHOMA CITY, OK 73105
 Phone: 405-521-2116

Prepared by:
 Mike Sartin
 PREMIER TRUCK GROUP OF
 TULSA
 5104 W. 60TH STREET
 TULSA, OK 74107
 Phone: 918-445-5300 ext 4061

Description

CHROME FUEL TANK CAP(S)
 EQUIFLO INBOARD FUEL SYSTEM
 HIGH TEMPERATURE REINFORCED NYLON
 FUEL LINE

Tires

CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY
 RADIAL FRONT TIRES
 CONTINENTAL HDC3 11R22.5 16 PLY RADIAL
 REAR TIRES

Wheels

ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25
 INSET 5-HAND STEEL DISC FRONT WHEELS
 MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT
 5-HAND STEEL DISC REAR WHEELS
 FRONT WHEEL MOUNTING NUTS
 REAR WHEEL MOUNTING NUTS

Cab Exterior

111.6 INCH BBC CONVENTIONAL ALUMINUM
 CAB
 STAINLESS STEEL CAB ACCENT MOLDING
 FRONT FENDERS
 BOLT-ON MOLDED FLEXIBLE FENDER
 EXTENSIONS
 INTERIOR GRAB HANDLES WITH ADDED
 LOWER LH AND RH A PILLAR GRAB HANDLES
 AND LH AND RH EXTERIOR NON-SLIP GRAB
 HANDLES
 BRIGHT HOOD MOUNTED AIR INTAKE GRILLE,
 BLACK SCREEN, WITH LED ACCENT LIGHTS
 X-SERIES STEEL REINFORCED ALUMINUM CAB
 X-SERIES VOCATIONAL HOOD
 HOOD OPENING ASSIST WITH LOCKING STRUT
 WESTERN STAR NAMEPLATES
 DUAL HADLEY SD-978 26 INCH RECTANGULAR
 AIR HORNS
 SINGLE ELECTRIC HORN
 REAR LICENSE PLATE MOUNT END OF FRAME
 SWITCH, INDICATOR LIGHT AND WIRING FOR
 (2) CUSTOMER FURNISHED BEACONS, FOR LH
 & RH BACK OF CAB ROOF MOUNTING
 DUAL STAGE INTELLIGENT LED HEADLIGHTS
 WITH HEATED LENS SYSTEM

Prepared for:
 CINI
 ZACHARIA
 OKLAHOMA STATE OF
 5005 N LINCOLN
 BLVD
 OKLAHOMA CITY, OK 73105
 Phone: 405-521-2116

Prepared by:
 Mike Sartin
 PREMIER TRUCK GROUP OF
 TULSA
 5104 W. 60TH STREET
 TULSA, OK 74107
 Phone: 918-445-5300 ext 4061

Description

ROOF MOUNTED LED MARKER LIGHTS
 DAYTIME RUNNING LIGHTS
 INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
 LED SIDE TURN SIGNAL
 C-BAR MIRROR SYSTEM WITH DUAL HEATED
 MIRRORS WITH INTEGRAL HEATED CONVEX,
 DUAL REMOTE, STAINLESS STEEL BACK
 COVER, AND BLACK C-BAR
 102 INCH EQUIPMENT WIDTH
 LH AND RH CONVEX MIRRORS INTEGRAL WITH
 PRIMARY MIRRORS
 RH DOWN VIEW MIRROR
 STANDARD SIDE/REAR REFLECTORS
 REAR REFLECTIVE DEVICE
 UNPOLISHED ALUMINUM WST
 AFTERTREATMENT SYSTEM COVER
 SINGLE SOLAR TINTED REAR WINDOW, (1) 31
 INCH X 20 INCH
 1-PIECE ROPED-IN SOLAR GREEN GLASS
 WINDSHIELD
 8 LITER (2 GAL) WINDSHIELD WASHER
 RESERVOIR, CAB MOUNTED, WITH FLUID
 LEVEL INDICATOR

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL
 PACKAGE
 CHARCOAL BLACK VINYL BASE LEVEL
 INTERIOR
 CARBON WITH BASE BLACK ACCENT
 BLACK MATS WITH ADDED FLOOR HEAT AND
 NOISE INSULATION
 (2) DASH MOUNTED POWER OUTLETS AND
 COIN TRAY
 FORWARD ROOF MOUNTED CONSOLE
 LH AND RH DOOR STORAGE POCKETS
 INTEGRATED INTO MOLDED DOOR PANELS
 (2) COAT HOOKS ON BACKWALL OF CAB
 DIGITAL ALARM CLOCK IN DRIVER DISPLAY
 2-1/2 LB. FIRE EXTINGUISHER MOUNTED
 INBOARD OF DRIVER SEAT
 STANDARD HEATER PLUMBING WITH BALL
 SHUTOFF VALVES AT SUPPLY LINES ONLY

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

RADIATOR MOUNTED AIR CONDITIONER
CONDENSER
STANDARD INSULATION
STANDARD LED CAB LIGHTING
REMOTE KEYLESS ENTRY AND 2
TRANSMITTERS
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME
KEY QUANTITY OF 4
LH AND RH ELECTRIC DOOR LOCKS WITH
AUTO UNLOCK FEATURE WHEN DOOR IS SET
FROM OPEN TO CLOSED POSITION
BRIGHT DOOR HANDLES
TRIANGULAR REFLECTORS WITHOUT FLARES
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
DRIVER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
PASSENGER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
DUAL DRIVER SEAT ARMRESTS, NO
PASSENGER SEAT ARMRESTS
BLACK VINYL DRIVER SEAT COVER WITH NO
LOGO
BLACK VINYL PASSENGER SEAT COVER WITH
NO LOGO
3 POINT HIGH VISIBILITY ORANGE ADJUSTABLE
D-RING RETRACTOR DRIVER AND FIXED D-RING
RETRACTOR PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING
WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

STOCK TRUCK/UPFIT PACKAGE LVL 1
STANDARD FOOT PEDAL SYSTEM
ELECTRONIC ACCELERATOR CONTROL
BLACK GAUGE BEZELS
STANDARD CENTER INSTRUMENT PANEL

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS
ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY
PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY
DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY
HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH
2 INCH ELECTRIC FUEL GAUGE
ENGINE REMOTE INTERFACE NOT CONFIGURED
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
ENGINE OIL TEMPERATURE GAUGE
ELECTRIC ENGINE OIL PRESSURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER
ENGINE, TRIP AND PTO HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE
NO OBSTACLE DETECTION SYSTEM
ELECTRONIC STABILITY CONTROL
NO LANE DEPARTURE WARNING SYSTEM
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL
TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE
AM/FM/WB WORLD TUNER RADIO WITH SIRIUSXM, BLUETOOTH, IPOD INTERFACE, USB AND AUXILIARY INPUTS, J1939
DASH MOUNTED RADIO

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

STANDARD SPEAKER SYSTEM
AM/FM ANTENNA MOUNTED ON RH SIDE
MIRROR
POWER AND GROUND WIRING PROVISION
OVERHEAD
ROOF/OVERHEAD CONSOLE CB RADIO
PROVISION
SINGLE REMOTE SPEAKER WITH LEAD FOR 2-
WAY RADIO
SINGLE FIBERGLASS LH MIRROR MOUNTED CB
ANTENNA WITH BRACKET AND LEAD
INTEROPERABLE SDAR ANTENNA
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
ELECTRONIC 2500 RPM TACHOMETER
DETROIT CONNECT PLATFORM HARDWARE
5 YEARS DETROIT CONNECT BASE PACKAGE
(FEATURES VARY BY MODEL) DETROIT
CONNECT PLATFORM
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH,
ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #3, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #4, ON/OFF LATCHING, 10
AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR
EXTERIOR LAMPS ONLY
REAR SPRING LOADED HAND CONTROL BRAKE
VALVE
2 INCH TURBO AIR PRESSURE GAUGE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT
FOR OPTIONAL FOG/ROAD LAMPS
ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, HEADLAMP FLASH,
WASH/WIPE/INTERMITTENT
QUICKFIT POWERTRAIN INTERFACE
CONNECTOR UNDER CAB WITH BLUNTCUTS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT
POWDER WHITE (N0006EA) FRONT
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
POWDER WHITE (N0006EA) REAR
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

Extended Warranty

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.