

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

S P E C I F I C A T I O N P R O P O S A L

Description

Price Level

WST 47X/49X PRL-27X (EFF:MY24 ORDERS)

Data Version

SPECPRO21 DATA RELEASE VER 008

Vehicle Configuration

WESTERN STAR 47X
2024 MODEL YEAR SPECIFIED
SET FORWARD AXLE - TRUCK
TRAILER TOWING PROVISION AT END OF
FRAME WITH SAE J560, WITHOUT END OF
FRAME AIR CONNECTIONS
LH PRIMARY STEERING LOCATION

General Service

TRUCK CONFIGURATION
DOMICILED, USA (EXCLUDING CALIFORNIA AND
CARB OPT-IN STATES)
CONSTRUCTION SERVICE
CONSTRUCTION BUSINESS SEGMENT
DIRT/SAND/ROCK COMMODITY
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN
TRANSIT, IS SPENT ON PAVED ROADS
MAXIMUM 8% EXPECTED GRADE
SMOOTH CONCRETE OR ASPHALT PAVEMENT -
MOST SEVERE IN-TRANSIT (BETWEEN SITES)
ROAD SURFACE
WESTERN STAR VOCATIONAL WARRANTY
EXPECTED FRONT AXLE(S) LOAD : 14000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD :
40000.0 lbs

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

EXPECTED GROSS VEHICLE WEIGHT CAPACITY
: 54000.0 lbs

Truck Service

Engine

CUM L9 260 HP @ 2200 RPM; 2200 GOV RPM,
860 LB-FT @ 1200 RPM

Electronic Parameters

75 MPH ROAD SPEED LIMIT
PTO MODE ENGINE RPM LIMIT - 1600 RPM
PTO RPM WITH CRUISE SET SWITCH - 700 RPM
PTO RPM WITH CRUISE RESUME SWITCH - 700 RPM
ONE DASH MOUNTED PTO SPEED WITH PTO SWITCH ENGAGEMENT
PTO SPEED 1 SETTING - 700 RPM
PTO MINIMUM RPM - 700
PTO 1, DASH SWITCH, ENGAGE BEFORE DRIVING

Engine Equipment

2010 EPA/CARB/GHG21 CONFIGURATION
NO 2008 CARB EMISSION CERTIFICATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES
BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN
POLISHED ALUMINUM WST BATTERY BOX COVER
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

POSITIVE AND NEGATIVE POSTS FOR
JUMPSTART LOCATED ON FRAME NEXT TO
STARTER

CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM

C-BRAKE BY JACOBS WITH LOW/OFF/HIGH
BRAKING DASH SWITCH

RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND VIRTUAL REGENERATION REQUEST
SWITCH IN CLUSTER

11 FOOT 06 INCH (138 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT

30 DEGREE CURVE BRIGHT UPPER STACK(S)
AND ELBOW(S)

RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP

13 GALLON DIESEL EXHAUST FLUID TANK
POLISHED ALUMINUM WST DIESEL EXHAUST
FLUID TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP

PERFORATED SINGLE STAINLESS STEEL
MUFFLER/TAILPIPE SHIELD WITH WESTERN
STAR LOGO

AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITH DASH
SWITCH AND INDICATOR LIGHT, NON ENGINE
MOUNTED

DETROIT FUEL/WATER SEPARATOR WITH
WATER IN FUEL SENSOR

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND
SILICATE FREE) EXTENDED LIFE COOLANT

GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT

RADIATOR DRAIN VALVE

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

LOWER RADIATOR GUARD
NO REPTO, EXTENDED FLYWHEEL HOUSING,
CUML9 REQUIRED FOR PACKAGING
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK
HEATER
PHILLIPS-TEMRO 300 WATT/115 VOLT OIL
PREHEATER
CHROME ENGINE HEATER RECEPTACLE
MOUNTED UNDER LH DOOR
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH
THERMAL PROTECTION AND INTEGRATED
MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV
ALLISON VOCATIONAL RATING FOR CONCRETE
MIXER APPLICATIONS ONLY AVAILABLE WITH
3000 PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE
PRIMARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
QUICKFIT BODY LIGHTING CONNECTOR UNDER
CAB, WITH CAP
ELECTRONIC TRANSMISSION WIRING TO
CUSTOMER INTERFACE CONNECTOR

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

CUSTOMER INSTALLED CHELSEA 489 SERIES
PTO
PTO MOUNTING, BOTTOM OF MAIN
TRANSMISSION DETROIT & EATON FULLER
TRANSMISSION
MAGNETIC PLUGS, ENGINE DRAIN,
TRANSMISSION DRAIN, AXLE(S) FILL AND
DRAIN
HEAVY DUTY ELECTRONIC TRANSMISSION
SHIFT CONTROL, COLUMN MOUNTED
WATER TO OIL TRANSMISSION COOLER
TRANSMISSION OIL CHECK AND FILL WITH
ELECTRONIC OIL LEVEL CHECK
SYNTHETIC TRANSMISSION FLUID (TES-295
COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74
DROP SINGLE FRONT AXLE
CONMET PRESET PLUS PREMIUM IRON FRONT
HUBS
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT
BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW,
CENTER AND SIDE PLUGS - OIL
MERITOR AUTOMATIC FRONT SLACK
ADJUSTERS
SINGLE HIGH CAPACITY POWER STEERING
GEAR, BENDIX, 14.6-18K
2 QUART SEE THROUGH POWER STEERING
RESERVOIR
CURRENT AVAILABLE SYNTHETIC 75W-90
FRONT AXLE LUBE

Front Suspension

14,600# TAPERLEAF FRONT SUSPENSION
MAINTENANCE FREE RUBBER BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE
CONMET PRESET PLUS PREMIUM IRON REAR HUBS
3.90 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING
SPL170 XL DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES
SPL170 XL DANA SPICER INTERAXLE DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DIFFERENTIAL LOCKOUT SWITCH
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS REAR BRAKE LINING
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)
GUNITE CAST IRON REAR BRAKE DRUMS
NO REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension

TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION
9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)
AXLE CLAMPING GROUP
55 INCH AXLE SPACING
FORE/AFT AND TRANSVERSE CONTROL RODS

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

REAR SHOCK ABSORBERS - ONE AXLE

Brake System

WABCO 4S/4M ABS WITH TRACTION CONTROL
WITH ATC SHUT OFF SWITCH
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER HP WITH INTEGRAL
AIR GOVERNOR AND HEATER
AIR DRYER MOUNTED INBOARD ON LH RAIL
STEEL AIR BRAKE RESERVOIRS
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME

Wheelbase & Frame

5390MM (212 INCH) WHEELBASE, SFA ONLY
9.5MM X 89.0MM X 304.0MM STEEL FRAME
(0.37X3.50X11.97 INCH) 120 KSI
2025MM (80 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 71 INCH TO 80
INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
130.71 in
CALC'D FRAME LENGTH - OVERALL : 320.72 in
FRAME HEIGHT TOP FRONT UNLADEN : 43.74 in
FRAME HEIGHT TOP FRONT LADEN : 40.83 in
FRAME HEIGHT TOP REAR UNLADEN : 43.21 in
FRAME HEIGHT TOP REAR LADEN : 41.05 in
SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CAST ALUMINUM CROSSMEMBER
BACK OF TRANSMISSION
STANDARD CAST ALUMINUM MIDSHIP
STANDARD CAST ALUMINUM REARMOST
CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

CAST ALUMINUM REAR SUSPENSION
CROSSMEMBER

Chassis Equipment

POLISHED ALUMINUM WST EQUIPMENT
COVERS
PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL
BUMPER
REMOVABLE FRONT TOW/RECOVERY
DEVICE, STORED ON CHASSIS FRAME
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
CLASS 10.9 THREADED METRIC FASTENERS;
REAR SUSPENSION HANGER TO BE HUCK-SPIN
EXTERIOR HARNESSSES WRAPPED IN
ABRASION TAPE
LEFT HAND SIDE HEAVY DUTY BRACKETS
REQUIRED
RIGHT HAND SIDE HEAVY DUTY BRACKETS
REQUIRED

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK -
LH
25 INCH DIAMETER FUEL TANK(S)
POLISHING OF FUEL/HYDRAULIC TANK(S) WITH
PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
CHROME FUEL TANK CAP(S)
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON
FUEL LINE

Tires

CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY
RADIAL FRONT TIRES
CONTINENTAL HDC3 11R22.5 16 PLY RADIAL
REAR TIRES

Wheels

ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25
INSET 5-HAND STEEL DISC FRONT WHEELS
MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT
5-HAND STEEL DISC REAR WHEELS
FRONT WHEEL MOUNTING NUTS

Prepared for:
 Laura
 Bybee
 STATE OF OKLAHOMA
 200 NE 21ST ST
 OKLAHOMA CITY, OK 73105
 Phone: 405 000 0000

Prepared by:
 Mike Sartin
 PREMIER TRUCK GROUP OF
 TULSA
 5104 W. 60TH STREET
 TULSA, OK 74107
 Phone: 918-445-5300 ext 4061

Description

REAR WHEEL MOUNTING NUTS

Cab Exterior

111.6 INCH BBC CONVENTIONAL ALUMINUM CAB
 STAINLESS STEEL CAB ACCENT MOLDING
 FRONT FENDERS
 BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS
 INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES
 BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS
 X-SERIES STEEL REINFORCED ALUMINUM CAB
 X-SERIES VOCATIONAL HOOD
 HOOD OPENING ASSIST WITH LOCKING STRUT
 WESTERN STAR NAMEPLATES
 DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS
 SINGLE ELECTRIC HORN
 REAR LICENSE PLATE MOUNT END OF FRAME SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS, FOR LH & RH BACK OF CAB ROOF MOUNTING
 DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM
 ROOF MOUNTED LED MARKER LIGHTS
 DAYTIME RUNNING LIGHTS
 INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
 LED SIDE TURN SIGNAL
 C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR
 102 INCH EQUIPMENT WIDTH
 LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS
 RH DOWN VIEW MIRROR
 STANDARD SIDE/REAR REFLECTORS
 REAR REFLECTIVE DEVICE
 POLISHED ALUMINUM WST AFTERTREATMENT SYSTEM COVER

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

SINGLE SOLAR TINTED REAR WINDOW, (1) 31
INCH X 20 INCH
1-PIECE ROPED-IN SOLAR GREEN GLASS
WINDSHIELD
8 LITER (2 GAL) WINDSHIELD WASHER
RESERVOIR, CAB MOUNTED, WITH FLUID
LEVEL INDICATOR

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL
PACKAGE
CHARCOAL BLACK VINYL BASE LEVEL
INTERIOR
CARBON WITH BASE BLACK ACCENT
BLACK MATS WITH ADDED FLOOR HEAT AND
NOISE INSULATION
(2) DASH MOUNTED POWER OUTLETS AND
COIN TRAY
FORWARD ROOF MOUNTED CONSOLE
LH AND RH DOOR STORAGE POCKETS
INTEGRATED INTO MOLDED DOOR PANELS
(2) COAT HOOKS ON BACKWALL OF CAB
DIGITAL ALARM CLOCK IN DRIVER DISPLAY
2-1/2 LB. FIRE EXTINGUISHER MOUNTED
INBOARD OF DRIVER SEAT
STANDARD HEATER PLUMBING WITH BALL
SHUTOFF VALVES AT SUPPLY LINES ONLY
RADIATOR MOUNTED AIR CONDITIONER
CONDENSER
STANDARD INSULATION
STANDARD LED CAB LIGHTING
REMOTE KEYLESS ENTRY AND 2
TRANSMITTERS
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME
KEY QUANTITY OF 4
LH AND RH ELECTRIC DOOR LOCKS WITH
AUTO UNLOCK FEATURE WHEN DOOR IS SET
FROM OPEN TO CLOSED POSITION
BRIGHT DOOR HANDLES
TRIANGULAR REFLECTORS WITHOUT FLARES
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
DRIVER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

PREMIUM 2.0 HIGH BACK AIR SUSPENSION
PASSENGER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
DUAL DRIVER SEAT ARMRESTS, NO
PASSENGER SEAT ARMRESTS
BLACK VINYL DRIVER SEAT COVER WITH NO
LOGO
BLACK VINYL PASSENGER SEAT COVER WITH
NO LOGO
3 POINT HIGH VISIBILITY ORANGE ADJUSTABLE
D-RING RETRACTOR DRIVER AND FIXED D-RING
RETRACTOR PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING
WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

STOCK TRUCK/UPFIT PACKAGE LVL 1
STANDARD FOOT PEDAL SYSTEM
ELECTRONIC ACCELERATOR CONTROL
ENGINE REMOTE INTERFACE WITH PARK
BRAKE INTERLOCK
BLACK GAUGE BEZELS
STANDARD CENTER INSTRUMENT PANEL
DUAL NEEDLE PRIMARY AND SECONDARY AIR
PRESSURE GAUGE
INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
ELECTRONIC CRUISE CONTROL WITH
CONTROLS ON STEERING WHEEL SPOKES
KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY
PREMIUM INSTRUMENT CLUSTER WITH 5.0
INCH TFT COLOR DISPLAY
DIGITAL PANEL LAMP DIMMER SWITCH IN
DRIVER DISPLAY
HEAVY DUTY ONBOARD DIAGNOSTICS
INTERFACE CONNECTOR WITH DUST CAP
LOCATED BELOW LH DASH
2 INCH ELECTRIC FUEL GAUGE

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

ENGINE REMOTE INTERFACE WITH MULTIPLE SET SPEEDS
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE
NO ENGINE OIL TEMPERATURE GAUGE
ELECTRIC ENGINE OIL PRESSURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE
ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER
ENGINE, TRIP AND PTO HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY
PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE
NO OBSTACLE DETECTION SYSTEM
NO VEHICLE STABILITY ADVISOR OR CONTROL
NO LANE DEPARTURE WARNING SYSTEM
TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL
TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE
AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939
DASH MOUNTED RADIO
STANDARD SPEAKER SYSTEM
NO AM/FM RADIO ANTENNA
POWER AND GROUND WIRING PROVISION OVERHEAD
ROOF/OVERHEAD CONSOLE CB RADIO PROVISION
SINGLE REMOTE SPEAKER WITH LEAD FOR 2-WAY RADIO
SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD
HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER
ELECTRONIC 2500 RPM TACHOMETER

Prepared for:
Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

DETROIT CONNECT PLATFORM HARDWARE
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH,
ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #3, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #4, ON/OFF LATCHING, 10
AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR
EXTERIOR LAMPS ONLY
REAR SPRING LOADED HAND CONTROL BRAKE
VALVE
2 INCH TURBO AIR PRESSURE GAUGE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT
FOR OPTIONAL FOG/ROAD LAMPS
ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR
SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, HEADLAMP FLASH,
WASH/WIPE/INTERMITTENT
QUICKFIT POWERTRAIN INTERFACE
CONNECTOR UNDER CAB WITH BLUNTCUTS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT
POWDER WHITE (N0006EA) FRONT
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
POWDER WHITE (N0006EA) REAR
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

Prepared for:

Laura
Bybee
STATE OF OKLAHOMA
200 NE 21ST ST
OKLAHOMA CITY, OK 73105
Phone: 405 000 0000

Prepared by:

Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.