

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

15-3/4 ton

**HEAVY DUTY SPREADER
HOPPER TYPE
FOR DUMP BED MOUNTING**

GENERAL: Completely self-contained, ultra durable spreader unit designed for ice and snow control. The design allows for use with salt, sand and other materials. The complete assembly mounts easily on pickup, dump and platform trucks making it ideal for municipalities, shopping malls, industries, hospitals and private contractors. This spreader must be completely assembled, serviced and ready to operate when it is installed in a State owned dump truck. **This spreader must be new and the manufacturer's latest current model complete with all standard accessories and warranty for the make and model indicated below.**

For Comparison Only: Buyers 1400601SS Electric Powered Pintle chain & Spinner

FILL IN ALL SPACES SHOWING SPECIFIC INFORMATION.

For info: snowex.com

[SnowEx](http://SnowEx.com)

SUPPLIER'S PROPOSED SPREADER: MAKE: _____ MODEL: [Renegade S150A](http://RenegadeS150A.com) BASE PRICE: \$7017.00

	<u>MINIMUM REQUIREMENTS</u>	<u>SUPPLIER'S PROPOSAL</u>
<u>HOPPER BODY:</u>	"V" Type Box, all Welded 304	<u>Comply</u>
	113", approx. 1.8 cubic yards capacity	<u>Comply, 1.5 cubic yard</u>
<u>SECUREMENT:</u>	4 – 2" ratchet straps	<u>Comply</u>
<u>DISCHARGE CHUTE:</u>	304 stainless steel, rearward end mounts. Adjustable height extension with SS bolts	<u>Comply</u>
<u>COMPONENTS:</u>	All necessary hardware to be stainless steel	<u>Comply</u>
<u>OVER-ALL-HEIGHT:</u>	33 " above truck bed floor	<u>33.5"</u>

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

15-3/4 ton

	<u>MINIMUM REQUIREMENTS</u>	<u>SUPPLIER'S PROPOSAL</u>
<u>OUTSIDE WIDTH:</u>	47" maximum	<u>50"</u>
<u>DRIVE MOTORS:</u>	Two ultra-quiet 12-volt DC direct-drive motors power the conveyor and spinner, and are encased in a heavy-duty housing. The wiring harness is constructed of 10-gauge automotive wire with non-combustible sheathing (-50°C to -105°C). An in-cab console features independent controls for the conveyor and spinner.	<u>Comply</u>
<u>SILLS:</u>	304 stainless steel	<u>Comply</u>
<u>FRONT & REAR:</u>	Rollover lips	<u>Comply</u>
<u>WIPERS:</u>	Front & rear required	<u>Comply</u>
<u>CROSS SILLS:</u>	304 stainless steel welded to sills and side supports	<u>Comply</u>
<u>SIDE SUPPORTS:</u>	304 stainless steel welded to sides, sills and cross sills	<u>Comply</u>
<u>SIDES:</u>	304 stainless steel 45°	<u>Comply</u>
<u>LIFTING LOOPS:</u>	4 each, 1 near each outside corner	<u>Comply</u>
<u>FEED GATE ASSEMBLY:</u>	304 stainless steel Lever operated with a friction lock for	<u>Comply</u>

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

15-3/4 ton

	<u>MINIMUM REQUIREMENTS</u>	<u>SUPPLIER'S PROPOSAL</u>
	accurate adjustment.	_____
Feed Gate Opening	Maximum 12" high by 18" wide	<u>Comply</u>
Controlled Spread	From 2' to 30'	<u>Comply</u>
Disc	An 11.5" polymer disc with four fins is connected to a 3/4" diameter shaft secured on the pillow block and motor bearing.	<u>Comply</u>
Screens:	1/4" black powder coated steel top screen	<u>Comply</u>
<u>Warranty:</u>	Manufacturer's standard with coverage complete on all components.	<u>comply</u>
<u>OPTION 1:</u> Installation	In the state of <u>Oklahoma</u> by a <u>qualified up fitter</u> .	\$ <u>1,052.00</u>
<u>OPTION 2:</u>	Variation to larger or smaller Spreader	%Off List <u>-10% from List</u>
<u>OPTION 3:</u>	Different Hopper Material	%Off List <u>-10% from List</u>
<u>OPTION 4:</u>	Gas Powered Units	%Off List <u>not available</u>
Total weight of this complete unit: 1000 lbs. (approximate)		<u>530 lbs</u>

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

15-3/4 ton

Supplier must furnish this unit complete with all components including necessary hardware, etc.

NOTE:

Inspection and/or correction of items listed on the inspection and pre-delivery form are considered a part of this specification; also considered part of selling dealer's new equipment preparation and handling cost, if he contracts the new equipment pre-delivery service inspection out to another authorized dealer, the selling dealer is still liable to all terms of the specification and purchase order except for those corrective operations previously established as eligible for warranty reimbursement according to the current warranty and policy procedure manual.

Special Requirements:

The supplier shall provide to the receiving division, factory spreader specifications and dimensions and request bed dimensions prior to ordering spreaders.

PAINT: (Non Stainless Components Only)

All exposed metal shall be Powder Coated.

Specify color used BLACK

WARRANTY: One Year / from date of delivery.

SERVICE AND PARTS:

Supplier shall furnish upon request, a list of established manufacturer's authorized locations within the State Of Oklahoma where an adequate stock of current parts and service are available.

MANUALS AND PARTS BOOK:

Supplier shall furnish one (1) Operators Instruction Manual for each machine. In addition, one (1) Parts Book and one (1) Repair manual shall be furnished to each Division purchasing one or more machines.

SPECIFICATIONS:

Each supplier shall submit complete manufacturer's specification in duplicate and shall submit all other data to show that his proposal meets these specifications.

COMPLIANCE:

Supplier shall furnish a statement in writing on the bid or by attached letter, and in the Supplier's Statement below, if his equipment proposed strictly meets these specifications. If not, he shall list each variation thereof.

SUPPLIER'S STATEMENT (EQUIPMENT PROPOSED COMPLIES): YES: X NO: _____

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

15-3/4 ton

DEALER: GRAND TRUCK EQUIPMENT CO. LLC PHONE: 918-264-0224

SIGNATURE: *Jeff Hankins* DATE: 8-18-23

ADDRESS: 451527 Sparrow Hawk Circle, Afton, OK 74331

Please use a different sheet for each Brand and Model bid on.

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

78-¾ Ton

**SNOW PLOW
FRONT MOUNTED REVERSIBLE
WITH SAFETY TRIP
¾ Ton & 1 Ton Trucks**

GENERAL: This snow plow shall be adequate for a single or dual axle truck and must be new and the manufacturer's latest current model complete with all standard accessories and warranty for the make and model indicated below.

For Comparison Only: Buyers EX75 w/Plow Hitch, Truck Portion Hitch & Light Adapter

FILL IN ALL SPACES SHOWING SPECIFIC INFORMATION.

For info: snowex.com

[SnowEx 7600HD](#)

SUPPLIER'S PROPOSED SNOW PLOW: MAKE: MODEL: Base Price: \$ 6,768.00

	<u>MINIMUM REQUIREMENTS</u>	<u>SUPPLIER'S PROPOSAL</u>
<u>Plow:</u>	.105 gauge Stainless Steel Moldboard 31" x 7'6"	31"x7'6" powder coated steel
	9 each 1/4" Laser cut steel ribs	Comply
	Integral Snow shield	Comply
	Blade size ½" x 6" x 7'6"	Comply
	70% Attack angle/cutting width 78"	Comply
	4 Stress-optimized trip springs	Comply
	Plow Markers at each end	comply
	Covered power unit and hydraulics	Comply

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

78-¾ Ton

	<u>MINIMUM REQUIREMENTS</u>	<u>SUPPLIER'S PROPOSAL</u>
<u>LIFT FRAME:</u>		
	Lift Arm - 35 degree travel provides exceptional snow stacking	<u>Comply</u>
	Quick attach/detach mounting	<u>Comply</u>
	powerful, dual beam halogen plow lights with secure double post mounts	<u>Comply</u>
	Adjustable/removable jack stand	<u>Comply</u>
<u>TRUCK PORTION HITCH:</u>		
	End user will provide Make & Model of Vehicle to be installed on	<u>Comply</u>
	When Plow removed lights and lift frame are <u>NOT</u> on truck	<u>Comply</u>
<u>LIGHT ADAPTERS:</u>	End user will provide Make & Model of Vehicle to be installed on	<u>Comply</u>
<u>CONTROLLER:</u>	Hand Held Remote control	<u>Comply</u>
Weight of Moldboard & Lift frame	745 lbs	<u>Comply</u>
Capacity:	Adequate for 8500-10,000 lbs.,	<u>comply</u>

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

78-¾ Ton

	<u>MINIMUM REQUIREMENTS</u>	<u>SUPPLIER'S PROPOSAL</u>
	GVWR truck	
Pushframe & Hitch	Show make	SnowEx
	Show Model	SnowEx 7600HD
Misc. Parts & Instructions for Assembly & Mounting	Each snow plow unit must be complete with all necessary hardware, fittings and instructions with drawings for proper assembly and truck installation	Comply
<u>OPTION 1:</u> Installation	In the state of Oklahoma by a qualified up fitter.	\$ 1,800.00
<u>OPTION 2:</u> Accessories or	Variation to larger or smaller plows	\$ -10% from List

PAINT:

All exposed Metal shall be black powder coat unless it is Stainless

INSPECTION AND DELIVERY OF EQUIPMENT TO COMPLY WITH SUPPLIER'S INSTRUCTION SHEET.

MANUALS & PARTS BOOKS:

Supplier shall furnish one (1) Operators Instruction Manual for each plow. In addition, one (1) Parts Book and one (1) Illustrated Repair Manual shall be furnished to each Division purchasing one or more plows.

SERVICE POLICY:

Manufacturer's Standard Service Policy shall be furnished, complete and unaltered with each unit delivered.

**OFFICE OF MANAGEMENT & ENTERPRISE SERVICES
EXHIBIT 1**

EQUIPMENT SPECIFICATION

78-¾ Ton

SPECIFICATIONS:

Each supplier shall submit complete manufacturer's specification in duplicate and shall submit all other data to show that his proposal meets these specifications.

SERVICE AND PARTS:

Supplier shall furnish upon request, a list of established manufacturer's authorized locations within the State Of Oklahoma where an adequate stock of current parts and service are available.

COMPLIANCE:

Supplier shall furnish a statement in writing on the Bid, in the Supplier's Statement below, or by an attached letter stating the Equipment proposed strictly meets these Specifications. If not, he shall list each variation thereof.

SUPPLIER'S STATEMENT (EQUIPMENT PROPOSED COMPLIES): YES: X NO: _____

DEALER: GRAND TRUCK EQUIPMENT CO. LLC DATE: 8-18-23

SIGNATURE: *Jeff Hankins* PHONE: 918-264-0224

ADDRESS: 451527 Sparrow Hawk Circle, Afton, OK 74331

Please use a separate sheet for each brand and model bid.