

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

S P E C I F I C A T I O N P R O P O S A L

Description

Price Level

WST 47X/49X PRL-28X (EFF:MY25 ORDERS)

Data Version

SPECPRO21 DATA RELEASE VER 013

Vehicle Configuration

WESTERN STAR 47X
2025 MODEL YEAR SPECIFIED
SET FORWARD AXLE - TRUCK
TRAILER TOWING PROVISION AT END OF
FRAME WITH SAE J560, WITHOUT END OF
FRAME AIR CONNECTIONS
LH PRIMARY STEERING LOCATION

General Service

TRUCK CONFIGURATION
DOMICILED, USA (EXCLUDING CALIFORNIA AND
CARB OPT-IN STATES)
EPA EMISSIONS CERTIFICATION FOR
REGISTRATION OUTSIDE CARB STATES - EPA
CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON
LOWER FORWARD OF DRIVER DOOR)
NO STATE/PROVINCE INITIAL REGISTRATION
SELECTED
CONSTRUCTION SERVICE
CONSTRUCTION BUSINESS SEGMENT
DIRT/SAND/ROCK COMMODITY
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN
TRANSIT, IS SPENT ON PAVED ROADS
MAXIMUM 8% EXPECTED GRADE

Prepared for:
 CINI
 ZACHARIA
 OKLAHOMA STATE OF
 5005 N LINCOLN
 BLVD
 OKLAHOMA CITY, OK 73105
 Phone: 405-521-2116

Prepared by:
 Mike Sartin
 PREMIER TRUCK GROUP OF
 TULSA
 5104 W. 60TH STREET
 TULSA, OK 74107
 Phone: 918-445-5300 ext 4061

Description

SMOOTH CONCRETE OR ASPHALT PAVEMENT -
 MOST SEVERE IN-TRANSIT (BETWEEN SITES)
 ROAD SURFACE
 WESTERN STAR VOCATIONAL WARRANTY
 EXPECTED FRONT AXLE(S) LOAD : 14000.0 lbs
 EXPECTED REAR DRIVE AXLE(S) LOAD :
 40000.0 lbs
 EXPECTED GROSS VEHICLE WEIGHT CAPACITY
 : 54000.0 lbs

Truck Service

DURACCLASS (TBEI)

Engine

CUM L9 260 HP @ 2200 RPM; 2200 GOV RPM,
 860 LB-FT @ 1200 RPM

Electronic Parameters

75 MPH ROAD SPEED LIMIT
 PTO MODE ENGINE RPM LIMIT - 1600 RPM
 PTO RPM WITH CRUISE SET SWITCH - 700 RPM
 PTO RPM WITH CRUISE RESUME SWITCH - 700
 RPM
 ONE DASH MOUNTED PTO SPEED WITH PTO
 SWITCH ENGAGEMENT
 PTO SPEED 1 SETTING - 700 RPM
 PTO MINIMUM RPM - 700
 PTO 1, DASH SWITCH, ENGAGE BEFORE
 DRIVING

Engine Equipment

EPA 2010/GHG 2024 CONFIGURATION
 STANDARD OIL PAN
 ENGINE MOUNTED OIL CHECK AND FILL
 SIDE OF HOOD AIR INTAKE WITH ENGINE
 MOUNTED AIR CLEANER
 DR 12V 160 AMP 28-SI QUADRAMOUNT PAD
 ALTERNATOR WITH REMOTE BATTERY VOLT
 SENSE
 (3) DTNA GENUINE, FLOODED STARTING, MIN
 300CCA, 555RC, THREADED STUD BATTERIES
 BATTERY BOX WITH ALUMINUM COVER
 MOUNTED SHORT SIDE TO RAIL
 SINGLE BATTERY BOX FRAME MOUNTED LH
 SIDE BACK OF CAB

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
POLISHED ALUMINUM WST BATTERY BOX
COVER
POSITIVE LOAD DISCONNECT WITH CAB
MOUNTED CONTROL SWITCH MOUNTED
OUTBOARD DRIVER SEAT
POSITIVE AND NEGATIVE POSTS FOR
JUMPSTART LOCATED ON FRAME NEXT TO
STARTER
CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE
ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM
C-BRAKE BY JACOBS WITH LOW/OFF/HIGH
BRAKING DASH SWITCH
RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE
ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND VIRTUAL REGENERATION REQUEST
SWITCH IN CLUSTER
11 FOOT 06 INCH (138 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT
30 DEGREE CURVE BRIGHT UPPER STACK(S)
AND ELBOW(S)
RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP
13 GALLON DIESEL EXHAUST FLUID TANK
POLISHED ALUMINUM WST DIESEL EXHAUST
FLUID TANK COVER
LH HEAVY DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION
STANDARD DIESEL EXHAUST FLUID TANK CAP
PERFORATED SINGLE STAINLESS STEEL
MUFFLER/TAILPIPE SHIELD WITH WESTERN
STAR LOGO
AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITH DASH
SWITCH AND INDICATOR LIGHT, NON ENGINE
MOUNTED
DETROIT FUEL/WATER SEPARATOR WITH
WATER IN FUEL SENSOR

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

CUMMINS SPIN ON FUEL FILTER
FULL FLOW OIL FILTER
1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND
SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
NO REPTO, EXTENDED FLYWHEEL HOUSING,
CUML9 REQUIRED FOR PACKAGING
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK
HEATER
PHILLIPS-TEMRO 300 WATT/115 VOLT OIL
PREHEATER
CHROME ENGINE HEATER RECEPTACLE
MOUNTED UNDER LH DOOR
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH
THERMAL PROTECTION AND INTEGRATED
MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV
ALLISON VOCATIONAL RATING FOR CONCRETE
MIXER APPLICATIONS ONLY AVAILABLE WITH
3000 PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP

ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR

CUSTOMER INSTALLED CHELSEA 489 SERIES PTO

PTO MOUNTING, BOTTOM OF MAIN TRANSMISSION DETROIT & EATON FULLER TRANSMISSION

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN

HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED

WATER TO OIL TRANSMISSION COOLER

TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE

CONMET PRESET PLUS PREMIUM IRON FRONT HUBS

MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

MERITOR AUTOMATIC FRONT SLACK ADJUSTERS

SINGLE HIGH CAPACITY POWER STEERING GEAR, BENDIX, 14.6-18K

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

2 QUART SEE THROUGH POWER STEERING
RESERVOIR
CURRENT AVAILABLE SYNTHETIC 75W-90
FRONT AXLE LUBE

Front Suspension

14,600# TAPERLEAF FRONT SUSPENSION
MAINTENANCE FREE RUBBER BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

MT-40-14X 40,000# R-SERIES TANDEM REAR
AXLE
CONMET PRESET PLUS PREMIUM IRON REAR
HUBS
3.90 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH OPTIONAL
HEAVY DUTY AXLE HOUSING
SPL170 XL DANA SPICER MAIN DRIVELINE WITH
HALF ROUND YOKES
SPL170 XL DANA SPICER INTERAXLE
DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER
CONTROLLED DIFFERENTIAL LOCK FORWARD-
REAR AND REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE
LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DIFFERENTIAL
LOCKOUT SWITCH
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM
REAR BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS REAR BRAKE LINING
BRAKE CAMS AND CHAMBERS ON FORWARD
SIDE OF DRIVE AXLE(S)
GUNITE CAST IRON REAR BRAKE DRUMS
NO REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE
AXLE SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

CURRENT AVAILABLE SYNTHETIC 75W-90 REAR
AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension

TUFTRAC GEN2 40,000# REAR SPRING
SUSPENSION
9.5 INCH NOMINAL RIDE HEIGHT (460MM
GLOBAL REFERENCE HEIGHT)
AXLE CLAMPING GROUP
55 INCH AXLE SPACING
FORE/AFT AND TRANSVERSE CONTROL RODS
REAR SHOCK ABSORBERS - ONE AXLE

Brake System

WABCO 4S/4M ABS WITH TRACTION CONTROL
WITH ATC SHUT OFF SWITCH
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER HP WITH INTEGRAL
AIR GOVERNOR AND HEATER
AIR DRYER MOUNTED INBOARD ON LH RAIL
STEEL AIR BRAKE RESERVOIRS
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME

Wheelbase & Frame

5390MM (212 INCH) WHEELBASE, SFA ONLY
9.0MM X 83.0MM X 283.0MM STEEL FRAME
(0.35X3.35X11.14 INCH) 120 KSI
2025MM (80 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 71 INCH TO 80
INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
130.71 in
CALC'D FRAME LENGTH - OVERALL : 320.72 in
FRAME HEIGHT TOP FRONT UNLADEN : 43.73 in

Prepared for:
 CINI
 ZACHARIA
 OKLAHOMA STATE OF
 5005 N LINCOLN
 BLVD
 OKLAHOMA CITY, OK 73105
 Phone: 405-521-2116

Prepared by:
 Mike Sartin
 PREMIER TRUCK GROUP OF
 TULSA
 5104 W. 60TH STREET
 TULSA, OK 74107
 Phone: 918-445-5300 ext 4061

Description

FRAME HEIGHT TOP FRONT LADEN : 40.79 in
 FRAME HEIGHT TOP REAR UNLADEN : 42.79 in
 FRAME HEIGHT TOP REAR LADEN : 40.63 in
 SQUARE END OF FRAME
 STANDARD WEIGHT ENGINE CROSSMEMBER
 STANDARD CAST ALUMINUM CROSSMEMBER
 BACK OF TRANSMISSION
 STANDARD CAST ALUMINUM MIDSHIP
 STANDARD CAST ALUMINUM REARMOST
 CROSSMEMBER
 STANDARD SUSPENSION CROSSMEMBER
 CAST ALUMINUM REAR SUSPENSION
 CROSSMEMBER

Chassis Equipment

POLISHED ALUMINUM WST EQUIPMENT
 COVERS
 PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL
 BUMPER
 REMOVABLE FRONT TOW/RECOVERY
 DEVICE, STORED ON CHASSIS FRAME
 BUMPER MOUNTING FOR SINGLE LICENSE
 PLATE
 CLASS 10.9 THREADED METRIC FASTENERS
 EXTERIOR HARNESSSES WRAPPED IN
 ABRASION TAPE
 LEFT HAND SIDE HEAVY DUTY BRACKETS
 REQUIRED
 RIGHT HAND SIDE HEAVY DUTY BRACKETS
 REQUIRED

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK -
 LH
 25 INCH DIAMETER FUEL TANK(S)
 POLISHING OF FUEL/HYDRAULIC TANK(S) WITH
 PAINTED BANDS
 FUEL TANK(S) FORWARD
 PLAIN STEP FINISH
 CHROME FUEL TANK CAP(S)
 EQUIFLO INBOARD FUEL SYSTEM
 HIGH TEMPERATURE REINFORCED NYLON
 FUEL LINE

Prepared for:
 CINI
 ZACHARIA
 OKLAHOMA STATE OF
 5005 N LINCOLN
 BLVD
 OKLAHOMA CITY, OK 73105
 Phone: 405-521-2116

Prepared by:
 Mike Sartin
 PREMIER TRUCK GROUP OF
 TULSA
 5104 W. 60TH STREET
 TULSA, OK 74107
 Phone: 918-445-5300 ext 4061

Description

Tires

CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY
 RADIAL FRONT TIRES
 CONTINENTAL HDC3 11R22.5 16 PLY RADIAL
 REAR TIRES

Wheels

ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25
 INSET 5-HAND STEEL DISC FRONT WHEELS
 MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT
 5-HAND STEEL DISC REAR WHEELS
 NO FRONT AXLE WHEEL/HUB COVER
 NO WHEEL/HUB COVER-PUSHER/TAG
 FRONT WHEEL MOUNTING NUTS
 REAR WHEEL MOUNTING NUTS

Cab Exterior

111.6 INCH BBC CONVENTIONAL ALUMINUM
 CAB
 STAINLESS STEEL CAB ACCENT MOLDING
 FRONT FENDERS
 BOLT-ON MOLDED FLEXIBLE FENDER
 EXTENSIONS
 INTERIOR GRAB HANDLES WITH ADDED
 LOWER LH AND RH A PILLAR GRAB HANDLES
 AND LH AND RH EXTERIOR NON-SLIP GRAB
 HANDLES
 BRIGHT HOOD MOUNTED AIR INTAKE GRILLE,
 BLACK SCREEN, WITH LED ACCENT LIGHTS
 X-SERIES STEEL REINFORCED ALUMINUM CAB
 X-SERIES VOCATIONAL HOOD
 HOOD OPENING ASSIST WITH LOCKING STRUT
 WESTERN STAR NAMEPLATES
 DUAL HADLEY SD-978 26 INCH RECTANGULAR
 AIR HORNS
 SINGLE ELECTRIC HORN
 REAR LICENSE PLATE MOUNT END OF FRAME
 SWITCH, INDICATOR LIGHT AND WIRING FOR
 (2) CUSTOMER FURNISHED BEACONS
 DUAL STAGE INTELLIGENT LED HEADLIGHTS
 WITH HEATED LENS SYSTEM
 ROOF MOUNTED LED MARKER LIGHTS
 DAYTIME RUNNING LIGHTS

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

INTEGRAL LED STOP/TAIL/BACKUP LIGHTS
LED SIDE TURN SIGNAL
C-BAR MIRROR SYSTEM WITH DUAL HEATED
MIRRORS WITH INTEGRAL HEATED CONVEX,
DUAL REMOTE, STAINLESS STEEL BACK
COVER, AND BLACK C-BAR
102 INCH EQUIPMENT WIDTH
LH AND RH CONVEX MIRRORS INTEGRAL WITH
PRIMARY MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
REAR REFLECTIVE DEVICE
POLISHED ALUMINUM WST AFTERTREATMENT
SYSTEM COVER
SINGLE SOLAR TINTED REAR WINDOW, (1) 31
INCH X 20 INCH
1-PIECE ROPED-IN SOLAR GREEN GLASS
WINDSHIELD
8 LITER (2 GAL) WINDSHIELD WASHER
RESERVOIR, CAB MOUNTED, WITH FLUID
LEVEL INDICATOR

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL
PACKAGE
CHARCOAL BLACK VINYL BASE LEVEL
INTERIOR
CARBON WITH BASE BLACK ACCENT
BLACK MATS WITH ADDED FLOOR HEAT AND
NOISE INSULATION
(2) DASH MOUNTED POWER OUTLETS AND
COIN TRAY
FORWARD ROOF MOUNTED CONSOLE
LH AND RH DOOR STORAGE POCKETS
INTEGRATED INTO MOLDED DOOR PANELS
(2) COAT HOOKS ON BACKWALL OF CAB
DIGITAL ALARM CLOCK IN DRIVER DISPLAY
2-1/2 LB. FIRE EXTINGUISHER MOUNTED
INBOARD OF DRIVER SEAT
STANDARD HEATER PLUMBING WITH BALL
SHUTOFF VALVES AT SUPPLY LINES ONLY
RADIATOR MOUNTED AIR CONDITIONER
CONDENSER
STANDARD INSULATION

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

STANDARD LED CAB LIGHTING
REMOTE KEYLESS ENTRY AND 2
TRANSMITTERS
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME
KEY QUANTITY OF 4
LH AND RH ELECTRIC DOOR LOCKS WITH
AUTO UNLOCK FEATURE WHEN DOOR IS SET
FROM OPEN TO CLOSED POSITION
BRIGHT DOOR HANDLES
TRIANGULAR REFLECTORS WITHOUT FLARES
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
DRIVER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
PASSENGER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
DUAL DRIVER SEAT ARMRESTS, NO
PASSENGER SEAT ARMRESTS
BLACK VINYL DRIVER SEAT COVER WITH NO
LOGO
BLACK VINYL PASSENGER SEAT COVER WITH
NO LOGO
3 POINT HIGH VISIBILITY ORANGE ADJUSTABLE
D-RING RETRACTOR DRIVER AND FIXED D-RING
RETRACTOR PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING
WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

STANDARD FOOT PEDAL SYSTEM
ELECTRONIC ACCELERATOR CONTROL
ENGINE REMOTE INTERFACE WITH PARK
BRAKE INTERLOCK
BLACK GAUGE BEZELS
STANDARD CENTER INSTRUMENT PANEL
DUAL NEEDLE PRIMARY AND SECONDARY AIR
PRESSURE GAUGE

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS

ELECTRONIC CRUISE CONTROL WITH
CONTROLS ON STEERING WHEEL SPOKES

KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0
INCH TFT COLOR DISPLAY

DIGITAL PANEL LAMP DIMMER SWITCH IN
DRIVER DISPLAY

HEAVY DUTY ONBOARD DIAGNOSTICS
INTERFACE CONNECTOR WITH DUST CAP
LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

ENGINE REMOTE INTERFACE WITH ONE OR
MORE SET SPEEDS

ELECTRICAL ENGINE COOLANT TEMPERATURE
GAUGE

NO ENGINE OIL TEMPERATURE GAUGE

ELECTRIC ENGINE OIL PRESSURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE
GAUGE

ELECTRONIC OUTSIDE TEMPERATURE
SENSOR DISPLAY IN DRIVER MESSAGE
CENTER

ENGINE AND TRIP HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY

PTO CONTROLS FOR ENHANCED VEHICLE
ELECTRIC/ELECTRONIC ARCHITECTURE

NO OBSTACLE DETECTION SYSTEM

NO DR ASSIST SYSTEM

NO VEHICLE STABILITY ADVISOR OR CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR
LOCATED BEHIND PASSENGER SIDE
REMOVEABLE DASH PANEL

TOP OF DASH RAM MOUNT WITHOUT POWER
OR GROUND, FOR CUSTOMER FURNISHED
DEVICE

AM/FM/WB WORLD TUNER RADIO WITH
BLUETOOTH, USB AND AUXILIARY INPUTS,
J1939

DASH MOUNTED RADIO

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

STANDARD SPEAKER SYSTEM
NO AM/FM RADIO ANTENNA
POWER AND GROUND WIRING PROVISION
OVERHEAD
ROOF/OVERHEAD CONSOLE CB RADIO
PROVISION
SINGLE REMOTE SPEAKER WITH LEAD FOR 2-
WAY RADIO
SINGLE FIBERGLASS LH MIRROR MOUNTED CB
ANTENNA WITH BRACKET AND LEAD
HEADLINER MULTI-BAND ANTENNA:
AM/FM/WEATHERBAND, WIFI/BLUETOOTH,
GNSS/GPS
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
ELECTRONIC 2500 RPM TACHOMETER
DETROIT CONNECT PLATFORM HARDWARE
5 YEARS DAIMLER CONNECTIVITY BASE
PACKAGE (FEATURES VARY BY MODEL)
POWERED BY DETROIT CONNECT
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH,
ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #3, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #4, ON/OFF LATCHING, 10
AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR
EXTERIOR LAMPS ONLY
REAR SPRING LOADED HAND CONTROL BRAKE
VALVE
2 INCH TURBO AIR PRESSURE GAUGE
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT
FOR OPTIONAL FOG/ROAD LAMPS
ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR

Prepared for:
CINI
ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN
BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, HEADLAMP FLASH,
WASH/WIPE/INTERMITTENT
QUICKFIT POWERTRAIN INTERFACE
CONNECTOR UNDER CAB WITH BLUNTCUTS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT
POWDER WHITE (N0006EA) FRONT
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
POWDER WHITE (N0006EA) REAR
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
BUMPER PAINTED SAME AS CHASSIS

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.