

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

SPECIFICATION PROPOSAL

Data Code	Description	Weight Front	Weight Rear
Price Level			
PRL-29D	SD PRL-29D (EFF:MY26 ORDERS)		
Data Version			
DRL-013	SPECPRO21 DATA RELEASE VER 013		
Vehicle Configuration			
001-177	114SD PLUS CONVENTIONAL CHASSIS	7,934	6,476
004-226	2026 MODEL YEAR SPECIFIED		
002-004	SET BACK AXLE - TRUCK	480	-480
019-004	STRAIGHT TRUCK PROVISION, NON-TOWING		
003-001	LH PRIMARY STEERING LOCATION		
General Service			
AA1-002	TRUCK CONFIGURATION		
AA6-002	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
99D-027	EPA EMISSIONS CERTIFICATION FOR REGISTRATION IN EPA OR ACT STATES - EPA CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD OF DRIVER DOOR)		
A85-010	UTILITY/REPAIR/MAINTENANCE SERVICE		
A84-1GM	GOVERNMENT BUSINESS SEGMENT		
AA4-006	HEAVY EQUIPMENT COMMODITY		
AA5-002	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
AB1-008	MAXIMUM 8% EXPECTED GRADE		
AB5-001	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
995-1AE	FREIGHTLINER LEVEL II WARRANTY		
A66-99D	EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs		



Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs		
A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 66000.0 lbs		

Truck Service

AA3-004	END DUMP BODY
* AF3-999	CUSTOM MFR'S/BODY TYPE IDENTIFICATION CUSTOMER WILL USE LOCAL COMPANY

Engine

101-3CV	DETROIT DD13 GEN 5 12.8L 370 HP @ 1625 RPM, 1900 GOV RPM, 1250 LB/FT @ 975 RPM
---------	---

Electronic Parameters

79A-065	65 MPH ROAD SPEED LIMIT
79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT
79F-013	FLEET MANAGEMENT - DAILY ENGINE USAGE ENABLED
79P-032	PTO RPM CONTROL WITH STEERING WHEEL SWITCHES
79T-001	PTO MODE RPM INCREMENT - 25 RPM
79U-001	PTO GOVERNOR RAMP RATE - 25 RPM PER SECOND
79W-001	ONE REMOTE PTO SPEED
79X-005	PTO SPEED 1 SETTING - 900 RPM
80G-001	PTO MINIMUM RPM - 600
80L-001	ENABLE AUTO ENGINE RPM ELEVATE FOR EXTENDED IDLE

Engine Equipment

99C-024	EPA 2010/GHG 2024 CONFIGURATION
13E-001	STANDARD OIL PAN
105-001	ENGINE MOUNTED OIL CHECK AND FILL
014-1B5	SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED
124-1D7	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
292-236	(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES
290-017	BATTERY BOX FRAME MOUNTED
281-001	STANDARD BATTERY JUMPERS

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
282-003	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB		
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
289-001	NON-POLISHED BATTERY BOX COVER		
293-058	NON-ESSENTIAL POSITIVE LOAD DISCONNECT, IN CAB CONTROL SWITCH MOUNTED OUTBOARD OF DRIVER SEAT	2	
295-029	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
306-015	PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS	2	
107-046	BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE		
152-041	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
128-002	JACOBS COMPRESSION BRAKE		
016-1C2	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25
28F-014	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER		
239-026	10 FOOT 06 INCH (126 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
237-1CR	RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
23U-001	6 GALLON DIESEL EXHAUST FLUID TANK	-35	-10
30N-003	100 PERCENT DIESEL EXHAUST FLUID FILL		
23Y-001	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
43X-002	LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
43Y-001	STANDARD DIESEL EXHAUST FLUID TANK CAP		
242-011	ALUMINUM AFTERTREATMENT DEVICE/MUFFLER/TAILOPIPE SHIELD(S)		
273-058	AIR POWERED ON/OFF ENGINE FAN CLUTCH		
276-001	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
110-068	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
118-001	FULL FLOW OIL FILTER		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
120-998	NO COOLANT FILTER	-10	
266-107	1400 SQUARE INCH VOCATIONAL RADIATOR		
103-039	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
171-007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
172-001	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
270-023	HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE		
155-075	MITSUBISHI 12V MOD 3.175-DP60 STARTER WITH INTEGRATED MAGNETIC SWITCH	-45	
Transmission			
342-1M3	ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	260	100
Transmission Equipment			
343-339	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV		
84B-012	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES		
84C-023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
84D-023	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY		
84E-000	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
84F-000	SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
84G-000	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
84H-000	SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
84K-002	2ND GEAR ENGINE BRAKE ALTERNATE PRESELECT WITH MODERATE DOWNSHIFT STRATEGY		
N 84N-200	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
84U-000	DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
84V-001	DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS		
85T-998	NO AMT HOLD MODE		
353-075	QUICKFIT BODY LIGHTING CONNECTOR AT END OF FRAME, WITH CAP		
34C-011	ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
345-003	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
97G-004	TRANSMISSION PROGNOSTICS - ENABLED 2013		
370-011	WATER TO OIL TRANSMISSION COOLER, FRAME MOUNTED		
346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

Front Axle and Equipment

400-1BB	DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	190
402-030	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	10
403-002	NON-ASBESTOS FRONT BRAKE LINING	
419-001	CAST IRON OUTBOARD FRONT BRAKE DRUMS	
409-006	FRONT OIL SEALS	
408-001	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL	
416-022	STANDARD SPINDLE NUTS FOR ALL AXLES	
405-002	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS	
406-001	STANDARD KING PIN BUSHINGS	
536-055	TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	130
539-003	POWER STEERING PUMP	
534-003	4 QUART POWER STEERING RESERVOIR	
533-001	OIL/AIR POWER STEERING COOLER	
40T-001	MINERAL SAE 80/90 FRONT AXLE LUBE	

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
Front Suspension			
620-025	20,000# TAPERLEAF FRONT SUSPENSION	200	
619-005	MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
410-001	FRONT SHOCK ABSORBERS		
Rear Axle and Equipment			
420-103	MERITOR RT-46-160 46,000# R-SERIES TANDEM REAR AXLE		420
421-358	3.58 REAR AXLE RATIO		
424-001	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
386-075	MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	-10	-10
388-073	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES		
878-045	(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES		
87A-005	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH		
423-019	MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
433-002	NON-ASBESTOS REAR BRAKE LINING		
434-019	ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY		
451-023	CONMET CAST IRON REAR BRAKE DRUMS		
440-006	REAR OIL SEALS		
426-101	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS		
428-003	HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
41T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
42T-001	STANDARD REAR AXLE BREATHER(S)		
Rear Suspension			
622-1CJ	HENDRICKSON RT463 @46,000# REAR SUSPENSION		750
621-016	HENDRICKSON RT/RTE - 7.19" SADDLE		
431-001	STANDARD AXLE SEATS IN AXLE CLAMP GROUP		
624-011	52 INCH AXLE SPACING		
628-005	STEEL BEAMS AND BRONZE CENTER BUSHINGS WITH BAR PIN ADJUSTABLE END CONNECTIONS		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
623-005	FORE/AFT CONTROL RODS		
Pusher / Tag Equipment			
429-998	NO PUSHER/TAG BRAKE DUST SHIELDS		
Brake System			
490-121	WABCO 4S/4M ABS WITH TRACTION CONTROL		
871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
904-001	FIBER BRAID PARKING BRAKE HOSE		
412-001	STANDARD BRAKE SYSTEM VALVES		
46D-002	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
413-002	STD U.S. FRONT BRAKE VALVE		
432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
480-088	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER		
479-015	AIR DRYER FRAME MOUNTED		
460-001	STEEL AIR BRAKE RESERVOIRS		
477-001	PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS		
Trailer Connections			
481-998	NO TRAILER AIR HOSE		
476-998	NO AIR HOSE HANGER		
919-063	(1) QUICKFIT PROGRAMMABLE SOLENOID W/STATE RETENTION PLUMBED TO BACK OF CAB		
310-998	NO TRAILER ELECTRICAL CABLE		
Wheelbase & Frame			
545-667	6675MM (263 INCH) WHEELBASE		
546-101	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	630	-50
547-001	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT	260	440
552-012	1450MM (57 INCH) REAR FRAME OVERHANG		
55W-005	FRAME OVERHANG RANGE: 51 INCH TO 60 INCH	20	-70
549-002	24 INCH INTEGRAL FRONT FRAME EXTENSION	115	-20
AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 197.24 in		
AE8-99D	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 183.46 in		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
AE4-99D	CALC'D FRAME LENGTH - OVERALL : 389.49 in		
FSS-0LH	CALCULATED FRAME SPACE LH SIDE : 107.49 in		
FSS-0RH	CALCULATED FRAME SPACE RH SIDE : 89.15 in		
AM6-99D	CALC'D SPACE AVAILABLE FOR DECKPLATE : 0.0 in		
553-001	SQUARE END OF FRAME		
550-001	FRONT CLOSING CROSSMEMBER		
559-001	STANDARD WEIGHT ENGINE CROSSMEMBER		
562-001	STANDARD MIDSHIP #1 CROSSMEMBER(S)		
572-001	STANDARD REARMOST CROSSMEMBER		
565-001	STANDARD SUSPENSION CROSSMEMBER		
Chassis Equipment			
556-1E5	14 INCH PAINTED STEEL BUMPER	20	
574-001	BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
585-998	NO MUDFLAP BRACKETS		
590-998	NO REAR MUDFLAPS		
551-007	GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
44Z-002	EXTERIOR HARNESSSES WRAPPED IN ABRASION TAPE		
607-001	CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		
Fifth Wheel			
578-998	NO FIFTH WHEEL		
Fuel Tanks			
206-192	50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - RH	20	15
204-215	50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH	-10	
218-005	RECTANGULAR FUEL TANK(S)		
215-005	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
212-014	LH FUEL TANK MOUNTED FORWARD, RH FUEL TANK MOUNTED AFT		
664-001	PLAIN STEP FINISH		
205-001	FUEL TANK CAP(S)		
122-1K4	DAVCO 487 FUEL/WATER SEPARATOR WITH ESOC AND 12 VOLT PREHEATER	15	

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
216-020	EQUIFLO INBOARD FUEL SYSTEM		
202-016	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires			
093-2CC	MICHELIN XZU-S2 315/80R22.5 20 PLY RADIAL FRONT TIRES	100	
094-0GP	MICHELIN XDN2 11R22.5 16 PLY RADIAL REAR TIRES		160
Hubs			
418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS		
450-060	CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
Wheels			
502-433	ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS	66	
505-428	ACCURIDE 28828 22.5X8.25 10-HUB PILOT 2- HAND HD STEEL DISC REAR WHEELS		104
496-011	FRONT WHEEL MOUNTING NUTS		
497-011	REAR WHEEL MOUNTING NUTS		
Cab Exterior			
829-1A2	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
650-008	AIR CAB MOUNTING		
648-002	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
667-004	FRONT FENDERS SET-BACK AXLE		
678-001	LH AND RH GRAB HANDLES		
645-002	BRIGHT FINISH RADIATOR SHELL/HOOD BEZEL		
646-042	STATIONARY BLACK GRILLE WITH BRIGHT ACCENTS		
65X-003	CHROME HOOD MOUNTED AIR INTAKE GRILLE		
644-004	FIBERGLASS HOOD		
690-002	TUNNEL/FIREWALL LINER		
727-1AF	SINGLE 14 INCH ROUND HADLEY AIR HORN UNDER LH DECK		
726-002	DUAL ELECTRIC HORNS		
575-001	REAR LICENSE PLATE MOUNT END OF FRAME		
312-067	HALOGEN COMPOSITE HEADLAMPS WITH BRIGHT BEZELS		
302-047	LED AERODYNAMIC MARKER LIGHTS		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
311-001	DAYTIME RUNNING LIGHTS		
294-001	INTEGRAL STOP/TAIL/BACKUP LIGHTS		
300-015	STANDARD FRONT TURN SIGNAL LAMPS		
744-1BC	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
797-001	DOOR MOUNTED MIRRORS		
796-001	102 INCH EQUIPMENT WIDTH		
743-204	LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
729-001	STANDARD SIDE/REAR REFLECTORS		
677-053	RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN SHIELDING		
768-043	63X14 INCH TINTED REAR WINDOW		
661-004	TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS		
654-011	RH AND LH ELECTRIC POWERED WINDOWS		
663-013	1-PIECE SOLAR GREEN GLASS WINDSHIELD		
659-007	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITHOUT FLUID LEVEL INDICATOR		

Cab Interior

055-019	RUGGED TRIM PACKAGE		
707-107	GRAY & CARBON VINYL INTERIOR "RUGGED"		
70K-020	CARBON WITH PREMIUM GUNMETAL ACCENT (RUGGED)		
706-013	MOLDED PLASTIC DOOR PANEL		
708-013	MOLDED PLASTIC DOOR PANEL		
772-006	BLACK MATS WITH SINGLE INSULATION		
785-034	ASH CUP AND (1)LIGHTER, (1)12V POWER OUTLET, (1)DASH MTD DUAL USB-C OUTLET		
691-001	FORWARD ROOF MOUNTED CONSOLE		
693-019	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
738-021	DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
742-007	(2) CUP HOLDERS LH AND RH DASH		
680-029	M2/SD DASH		
720-003	5 LB. FIRE EXTINGUISHER	10	
714-001	FIRST AID KIT	2	
700-002	HEATER, DEFROSTER AND AIR CONDITIONER		
701-001	STANDARD HVAC DUCTING		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
703-005	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
170-015	STANDARD HEATER PLUMBING		
130-041	VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR		
702-002	BINARY CONTROL, R-134A		
739-033	STANDARD INSULATION		
285-013	SOLID-STATE CIRCUIT PROTECTION AND FUSES		
280-007	12V NEGATIVE GROUND ELECTRICAL SYSTEM		
324-1B3	STANDARD LED CAB LIGHTING		
787-004	REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS	2	
657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
78G-004	KEY QUANTITY OF 4		
655-005	LH AND RH ELECTRIC DOOR LOCKS		
740-998	NO MATTRESS	-20	-15
722-002	TRIANGULAR REFLECTORS WITHOUT FLARES	10	
756-338	BASIC ISRINGHAUSEN HIGH BACK AIR SUSPENSION DRIVERS SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	30	
760-338	BASIC ISRINGHAUSEN HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	25	10
759-005	DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
711-004	LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
758-1AK	BLACK VINYL DRIVER SEAT COVER		
761-1AK	BLACK VINYL PASSENGER SEAT COVER		
763-101	BLACK SEAT BELTS		
532-002	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
540-070	4-SPOKE 18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL WITH CHROME SWITCH BEZELS		
765-002	DRIVER AND PASSENGER INTERIOR SUN VISORS		

Instruments & Controls

4CH-008	8 EXTRA PROGRAMMABLE SWITCHES/INDICATORS
---------	--

Prepared for:
 OKLAHOMA STATE OF
 2401 N Lincoln
 Oklahoma City, OK 73105
 Phone: 405-521-2479

Prepared by:
 Jane Kirton
 PREMIER TRUCK GROUP OF
 OKLAHOMA CITY
 5301 I-40 WEST
 OKLAHOMA CITY, OK 73128
 Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
106-002	ELECTRONIC ACCELERATOR CONTROL		
732-998	NO INSTRUMENT PANEL-DRIVER		
734-022	FULLY CONFIGURABLE CENTER INSTRUMENT PANELS		
870-002	BRIGHT ARGENT FINISH GAUGE BEZELS		
486-001	LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
840-001	DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
198-025	INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
149-015	ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
156-007	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
157-004	MANUAL REMOTE ENGINE STOP/START		
811-044	PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
81B-003	DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
160-038	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
844-001	2 INCH ELECTRIC FUEL GAUGE		
845-011	FUEL FILTER RESTRICTION INDICATOR		
148-072	ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
48H-003	QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH CAPS		
48C-003	QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH CAP		
163-014	ENGINE REMOTE INTERFACE CONNECTOR AT POWERTRAIN INTERFACE CONNECTOR		
856-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
854-008	DIGITAL ENGINE OIL TEMPERATURE IN DRIVER DISPLAY		
852-002	ELECTRIC ENGINE OIL PRESSURE GAUGE		
864-022	DIGITAL TRANSMISSION OIL TEMPERATURE IN DRIVER DISPLAY		
867-004	ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

	Data Code	Description	Weight Front	Weight Rear
	830-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
	33A-051	PRE-WIRE; DASH TO ROOF FOR LIGHTBAR/STROBE/BEACON: TWO 30AMP WIRES & TWELVE 10AMP WIRES		
N	372-123	PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
	736-998	NO OBSTACLE DETECTION SYSTEM		
	72J-998	NO DR ASSIST SYSTEM		
	49B-998	NO VEHICLE STABILITY ADVISOR OR CONTROL		
	73B-998	NO LANE DEPARTURE WARNING SYSTEM		
	72K-998	NO REVERSE PROXIMITY SENSOR		
	679-998	NO OVERHEAD INSTRUMENT PANEL		
	35M-010	1 QUICKFIT PROGRAMABLE MODULE (QPM/XMC)	10	
	1U1-002	TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE		
N	746-137	AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939		
	747-001	DASH MOUNTED RADIO		
	750-002	(2) RADIO SPEAKERS IN CAB		
	753-001	AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF	2	
	748-006	POWER AND GROUND WIRING PROVISION OVERHEAD		
	749-001	ROOF/OVERHEAD CONSOLE CB RADIO PROVISION		
	75W-998	NO MULTIBAND ANTENNA		
	78C-998	NO DIGITAL SATELLITE AUDIO RECEIVER ANTENNA		
	810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
	817-001	STANDARD VEHICLE SPEED SENSOR		
	812-001	ELECTRONIC 3000 RPM TACHOMETER		
	813-1C8	DETROIT CONNECT PLATFORM HARDWARE		
	8D1-213	3 YEARS DETROIT CONNECT BASE PACKAGE(FEATURES VARY BY MODEL) DETROIT CONNECT PLATFORM		
	8DE-998	NO ASE DATA SVCE EXTENSION		
	RDE-998	NO EXTENSIONS		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
6TS-008	(2) TMC RP1226 ACCESSORY CONNECTORS: (1) LOCATED BEHIND PASSENGER SIDE REMOVABLE DASH PANEL (1) CENTER OF OVERHEAD CONSOLE		
162-002	IGNITION SWITCH CONTROLLED ENGINE STOP		
329-113	FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO UNDER CAB, CAPPED		
4C1-005	HARDWIRE SWITCH #1, ON/OFF MOMENTARY, 20 AMPS IGNITION POWER		
4C2-005	HARDWIRE SWITCH #2, ON/OFF MOMENTARY, 20 AMPS IGNITION POWER		
4C3-005	HARDWIRE SWITCH #3, ON/OFF MOMENTARY, 20 AMPS IGNITION POWER		
4C4-005	HARDWIRE SWITCH #4, ON/OFF MOMENTARY, 20 AMPS IGNITION POWER		
264-030	(1) OVERHEAD MOUNTED LANYARD CONTROL FOR DRIVER AIR HORN		
883-998	NO TRAILER HAND CONTROL BRAKE VALVE		
836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
660-008	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
304-030	ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
882-009	ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
299-020	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
298-046	INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		
87T-998	NO WRG/SW-OPTL #2, CHAS, AIR		

Design

065-000	PAINT: ONE SOLID COLOR
---------	------------------------

Color

980-5F6	CAB COLOR A: L0006EY WHITE ELITE EY
986-020	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT
962-972	POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
966-972	POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
964-020	STANDARD BLACK BUMPER PAINT		
963-003	STANDARD E COAT/UNDERCOATING		

Certification / Compliance

996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

Sales Programs

NO SALES PROGRAMS HAVE BEEN SELECTED

TOTAL VEHICLE SUMMARY

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	10455 lbs	7845 lbs	18300 lbs
Total Weight ⁺	10455 lbs	7845 lbs	18300 lbs

Extended Warranty

WAG-075 TOWING: 2 YEARS/UNLIMITED MILES/KM EXTENDED TOWING
COVERAGE \$750 CAP FEX APPLIES

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.