

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

5 4 - 6 6 G V W C H A S S I S S P E C S

Description
Price Level
WST 47X/49X PRL-29X (EFF:MY26 ORDERS)
Data Version
SPECPRO21 DATA RELEASE VER 008
Vehicle Configuration
WESTERN STAR 47X 2026 MODEL YEAR SPECIFIED SET FORWARD AXLE - TRUCK TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560, WITHOUT END OF FRAME AIR CONNECTIONS LH PRIMARY STEERING LOCATION
General Service
TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) EPA EMISSIONS CERTIFICATION FOR REGISTRATION IN EPA OR ACT STATES - EPA CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD OF DRIVER DOOR) CONSTRUCTION SERVICE CONSTRUCTION BUSINESS SEGMENT DIRT/SAND/ROCK COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE WESTERN STAR VOCATIONAL WARRANTY

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD :
46000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY
: 66000.0 lbs

Truck Service

3-V DISTRIBUTING INC

Engine

CUM X12 410V HP @ 1900 RPM, 1450 LB-FT @
1000 RPM, 2000 GOV RPM, VOC

Electronic Parameters

65 MPH ROAD SPEED LIMIT
PTO MODE ENGINE RPM LIMIT - 1400 RPM
PTO RPM CONTROL WITH STEERING WHEEL
SWITCHES
CRUISE CONTROL BUTTON PTO CONTROL
PTO SPEED 1 SETTING - 600 RPM
PTO 1, DASH SWITCH, ENGAGE BEFORE
DRIVING
ENGINE MOUNT PTO, DASH SWITCH ENGAGES
PTO MODE, STATIONARY OPERATION

Engine Equipment

EPA 2010/GHG 2024 CONFIGURATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
SIDE OF HOOD AIR INTAKE WITH ENGINE
MOUNTED AIR CLEANER
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD
ALTERNATOR WITH REMOTE BATTERY VOLT
SENSE
(3) DTNA GENUINE, FLOODED STARTING, MIN
3000CCA, 555RC, THREADED STUD BATTERIES
BATTERY BOX WITH ALUMINUM COVER
MOUNTED SHORT SIDE TO RAIL
SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
UNPOLISHED ALUMINUM WST BATTERY BOX
COVER

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

NON-ESSENTIAL POSITIVE LOAD DISCONNECT,
IN CAB CONTROL SWITCH MOUNTED
OUTBOARD OF DRIVER SEAT

POSITIVE AND NEGATIVE POSTS FOR
JUMPSTART LOCATED ON FRAME NEXT TO
STARTER

CUMMINS NATURALLY ASPIRATED 25.9 CFM
AIR COMPRESSOR WITH INTERNAL SAFETY
VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM

CUMMINS INTEBRAKE BRAKE WITH HIGH MED
LOW BRAKE

RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND VIRTUAL REGENERATION REQUEST
SWITCH IN CLUSTER

11 FOOT 06 INCH (138 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT

30 DEGREE CURVE BRIGHT UPPER STACK(S)
AND ELBOW(S)

RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP

13 GALLON DIESEL EXHAUST FLUID TANK
UNPOLISHED ALUMINUM WST DIESEL
EXHAUST FLUID TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP

PERFORATED SINGLE STAINLESS STEEL
MUFFLER/TAILPIPE SHIELD WITH WESTERN
STAR LOGO

ELECTRONICALLY CONTROLLED VARIABLE
SPEED VISCOUS FAN DRIVE

AUTOMATIC FAN CONTROL WITH DASH
SWITCH AND INDICATOR LIGHT, NON ENGINE
MOUNTED

DETROIT FUEL/WATER SEPARATOR WITH
WATER IN FUEL SENSOR

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

1400 SQUARE INCH VOCATIONAL RADIATOR
WITH PROTECTION PACKAGE
ANTIFREEZE TO -34F, OAT (NITRITE AND
SILICATE FREE) EXTENDED LIFE COOLANT
GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT
STANDARD CHARGE AIR COOLER PLUMBING
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK
HEATER
CHROME ENGINE HEATER RECEPTACLE
MOUNTED UNDER LH DOOR
NO AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH
THERMAL PROTECTION AND INTEGRATED
MAGNETIC SWITCH

Transmission

ALLISON 4500 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV
ALLISON VOCATIONAL RATING FOR ON/OFF
HIGHWAY APPLICATIONS AVAILABLE WITH ALL
PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE
PRIMARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

NEUTRAL AT STOP ENABLED
QUICKFIT BODY LIGHTING CONNECTOR UNDER
CAB, WITH CAP
ELECTRONIC TRANSMISSION WIRING TO
CUSTOMER INTERFACE CONNECTOR
CUSTOMER INSTALLED CHELSEA 280 SERIES
PTO
PTO MOUNTING, LH SIDE OF MAIN
TRANSMISSION ALLISON
MAGNETIC PLUGS, ENGINE DRAIN,
TRANSMISSION DRAIN, AXLE(S) FILL AND
DRAIN
HEAVY DUTY ELECTRONIC TRANSMISSION
SHIFT CONTROL, COLUMN MOUNTED
WATER TO OIL TRANSMISSION COOLER
TRANSMISSION OIL CHECK AND FILL WITH
ELECTRONIC OIL LEVEL CHECK
SYNTHETIC TRANSMISSION FLUID (TES-295
COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-20.0-5 20,000# FL1 71.0 KPI/3.74
DROP SINGLE FRONT AXLE
CONMET PRESET PLUS PREMIUM IRON FRONT
HUBS
MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT
BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW,
CENTER AND SIDE PLUGS - OIL
GUNITE AUTOMATIC FRONT SLACK
ADJUSTERS
DUAL POWER STEERING GEARS, BENDIX 16-
20K
4 QUART POWER STEERING RESERVOIR
OIL/AIR POWER STEERING COOLER
CURRENT AVAILABLE SYNTHETIC 75W-90
FRONT AXLE LUBE

Front Suspension

20,000# TAPERLEAF FRONT SUSPENSION

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

MAINTENANCE FREE RUBBER BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

MERITOR RT-46-160 46,000# R-SERIES TANDEM
REAR AXLE
CONMET PRESET PLUS PREMIUM IRON REAR
HUBS
4.56 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH STANDARD
AXLE HOUSING
MXL 18T MERITOR EXTENDED LUBE MAIN
DRIVELINE WITH HALF ROUND YOKES
MXL 17T MERITOR EXTENDED LUBE INTERAXLE
DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER
CONTROLLED DIFFERENTIAL LOCK FORWARD-
REAR AND REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE
LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DIFFERENTIAL
LOCKOUT SWITCH
MERITOR 16.5X8.62 Q+ CAST SPIDER HEAVY
DUTY CAM REAR BRAKES, DOUBLE ANCHOR,
FABRICATED SHOES
NON-ASBESTOS REAR BRAKE LINING
STANDARD BRAKE CHAMBER LOCATION
GUNITE CAST IRON REAR BRAKE DRUMS
NO REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE
AXLE SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR
AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension

HENDRICKSON HAULMAAX EX 46,000# REAR
SUSPENSION
9.5 INCH NOMINAL RIDE HEIGHT (460MM
GLOBAL REFERENCE HEIGHT)

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

54 INCH AXLE SPACING
HENDRICKSON HN, HAULMAAX AND ULTIMAAX
SERIES STEEL BEAMS WITH BAR PIN
STANDARD DUTY FORE/AFT AND HEAVY DUTY
TRANSVERSE CONTROL RODS
DOUBLE REBOUND STRAP - INBOARD AND
OUTBOARD
REAR SHOCK ABSORBERS - TWO AXLES
(TANDEM)

Pusher / Tag Equipment

NO PUSHER/TAG BRAKE DUST SHIELDS

Brake System

WABCO 4S/4M ABS WITH TRACTION CONTROL
WITH ATC SHUT OFF SWITCH
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER HP WITH INTEGRAL
AIR GOVERNOR AND HEATER
AIR DRYER FRAME MOUNTED
STEEL AIR BRAKE RESERVOIRS
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME
NO TRAILER ELECTRICAL CABLE

Wheelbase & Frame

7090MM (279 INCH) WHEELBASE, SFA ONLY
15.0MM X 89.0MM X 315.0MM STEEL FRAME
(0.59X3.5X12.4 INCH) 120 KSI
1750MM (69 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 61 INCH TO 70
INCH
24 INCH INTEGRAL FRONT FRAME EXTENSION
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
197.64 in
CALC'D FRAME LENGTH - OVERALL : 400.63 in
FRAME HEIGHT TOP FRONT UNLADEN : 44.74 in

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

FRAME HEIGHT TOP FRONT LADEN : 41.26 in
FRAME HEIGHT TOP REAR UNLADEN : 43.55 in
FRAME HEIGHT TOP REAR LADEN : 41.26 in
SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CAST ALUMINUM CROSSMEMBER
BACK OF TRANSMISSION
STANDARD CAST ALUMINUM MIDSHIP
STANDARD CAST ALUMINUM REARMOST
CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER
HEAVY DUTY REAR SUSPENSION
CROSSMEMBER

Chassis Equipment

UNPOLISHED ALUMINUM WST EQUIPMENT
COVERS
PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL
BUMPER
FRONT TOW HOOKS - FRONT FRAME
EXTENSION MOUNTED
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
BETTS B-83 PAINTED COILED SPRING HEAVY
DUTY MUDFLAP BRACKETS
CLASS 10.9 THREADED METRIC FASTENERS
EXTERIOR HARNESSSES WRAPPED IN
ABRASION TAPE
UPFIT ROUTING AND CLIPPING BRACKET, LH,
BOC TO SUSPENSION, UPPER & LOWER
SUPPORTS
UPFIT ROUTING AND CLIPPING BRACKET, RH,
BOC TO SUSPENSION, UPPER & LOWER
SUPPORTS

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK -
LH
25 INCH DIAMETER FUEL TANK(S)
POLISHING OF FUEL/HYDRAULIC TANK(S) WITH
PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
CHROME FUEL TANK CAP(S)
EQUIFLO INBOARD FUEL SYSTEM

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description	
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
Tires	
	CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY RADIAL FRONT TIRES CONTINENTAL INTELLIGENT HDC3 11R22.5 16 PLY RADIAL REAR TIRES
Wheels	
	ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS
Cab Exterior	
	111.6 INCH BBC CONVENTIONAL ALUMINUM CAB STAINLESS STEEL CAB ACCENT MOLDING FRONT FENDERS BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS X-SERIES STEEL REINFORCED ALUMINUM CAB X-SERIES VOCATIONAL HOOD HOOD OPENING ASSIST WITH LOCKING STRUT WESTERN STAR NAMEPLATES DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS SINGLE ELECTRIC HORN REAR LICENSE PLATE MOUNT END OF FRAME SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM ROOF MOUNTED LED MARKER LIGHTS DAYTIME RUNNING LIGHTS INTEGRAL LED STOP/TAIL/BACKUP LIGHTS

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

LED SIDE TURN SIGNAL
C-BAR MIRROR SYSTEM WITH DUAL HEATED
MIRRORS WITH INTEGRAL HEATED CONVEX,
DUAL REMOTE, STAINLESS STEEL BACK
COVER, AND BLACK C-BAR
102 INCH EQUIPMENT WIDTH
LH AND RH CONVEX MIRRORS INTEGRAL WITH
PRIMARY MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
REAR REFLECTIVE DEVICE
UNPOLISHED ALUMINUM WST
AFTERTREATMENT SYSTEM COVER
NO SLEEPER VENT
SINGLE SOLAR TINTED REAR WINDOW, (1) 31
INCH X 20 INCH
1-PIECE ROPED-IN SOLAR GREEN GLASS
WINDSHIELD
8 LITER (2 GAL) WINDSHIELD WASHER
RESERVOIR, CAB MOUNTED, WITH FLUID
LEVEL INDICATOR

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL
PACKAGE
CHARCOAL BLACK VINYL BASE LEVEL
INTERIOR
CARBON WITH BASE BLACK ACCENT
BLACK MATS WITH ADDED FLOOR HEAT AND
NOISE INSULATION
(2) DASH MOUNTED POWER OUTLETS AND
COIN TRAY
FORWARD ROOF MOUNTED CONSOLE
LH AND RH DOOR STORAGE POCKETS
INTEGRATED INTO MOLDED DOOR PANELS
(2) COAT HOOKS ON BACKWALL OF CAB
NO UPPER BUNK
DIGITAL ALARM CLOCK IN DRIVER DISPLAY
2-1/2 LB. FIRE EXTINGUISHER MOUNTED
INBOARD OF DRIVER SEAT
STANDARD HEATER PLUMBING WITH BALL
SHUTOFF VALVES AT SUPPLY LINES ONLY
RADIATOR MOUNTED AIR CONDITIONER
CONDENSER

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

STANDARD INSULATION
STANDARD LED CAB LIGHTING
REMOTE KEYLESS ENTRY AND 2
TRANSMITTERS
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME
KEY QUANTITY OF 4
LH AND RH ELECTRIC DOOR LOCKS WITH
AUTO UNLOCK FEATURE WHEN DOOR IS SET
FROM OPEN TO CLOSED POSITION
BRIGHT DOOR HANDLES
NO MATTRESS
TRIANGULAR REFLECTORS WITHOUT FLARES
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
DRIVER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
PASSENGER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
DUAL DRIVER SEAT ARMRESTS, NO
PASSENGER SEAT ARMRESTS
BLACK VINYL DRIVER SEAT COVER WITH NO
LOGO
BLACK VINYL PASSENGER SEAT COVER WITH
NO LOGO
3 POINT HIGH VISIBILITY ORANGE ADJUSTABLE
D-RING RETRACTOR DRIVER AND FIXED D-RING
RETRACTOR PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING
WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

STANDARD FOOT PEDAL SYSTEM
ELECTRONIC ACCELERATOR CONTROL
BLACK GAUGE BEZELS
STANDARD CENTER INSTRUMENT PANEL
DUAL NEEDLE PRIMARY AND SECONDARY AIR
PRESSURE GAUGE

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
ELECTRONIC CRUISE CONTROL WITH
CONTROLS ON STEERING WHEEL SPOKES
KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY
PREMIUM INSTRUMENT CLUSTER WITH 5.0
INCH TFT COLOR DISPLAY
DIGITAL PANEL LAMP DIMMER SWITCH IN
DRIVER DISPLAY
HEAVY DUTY ONBOARD DIAGNOSTICS
INTERFACE CONNECTOR WITH DUST CAP
LOCATED BELOW LH DASH
2 INCH ELECTRIC FUEL GAUGE
ENGINE REMOTE INTERFACE NOT
CONFIGURED
ELECTRICAL ENGINE COOLANT TEMPERATURE
GAUGE
ENGINE OIL TEMPERATURE GAUGE
ELECTRIC ENGINE OIL PRESSURE GAUGE
2 INCH TRANSMISSION OIL TEMPERATURE
GAUGE
ELECTRONIC OUTSIDE TEMPERATURE
SENSOR DISPLAY IN DRIVER MESSAGE
CENTER
ENGINE AND TRIP HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY
PTO CONTROLS FOR ENHANCED VEHICLE
ELECTRIC/ELECTRONIC ARCHITECTURE
NO OBSTACLE DETECTION SYSTEM
NO DR ASSIST SYSTEM
ELECTRONIC STABILITY CONTROL
NO LANE DEPARTURE WARNING SYSTEM
TMC RP1226 ACCESSORY CONNECTOR
LOCATED BEHIND PASSENGER SIDE
REMOVEABLE DASH PANEL
TOP OF DASH RAM MOUNT WITHOUT POWER
OR GROUND, FOR CUSTOMER FURNISHED
DEVICE
7" B-PANEL INTERACTIVE TOUCHSCREEN
DISPLAY W/ USB-C, APPLE CARPLAY, ANDROID
AUTO, BLUETOOTH/AM/FM/SXM/WB,
MICROPHONE
DASH MOUNTED RADIO

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

STANDARD SPEAKER SYSTEM
NO AM/FM RADIO ANTENNA
POWER AND GROUND WIRING PROVISION
OVERHEAD
ROOF/OVERHEAD CONSOLE CB RADIO
PROVISION
SINGLE REMOTE SPEAKER WITH LEAD FOR 2-
WAY RADIO
SINGLE FIBERGLASS LH MIRROR MOUNTED CB
ANTENNA WITH BRACKET AND LEAD
HEADLINER MULTI-BAND ANTENNA:
AM/FM/WEATHERBAND, WIFI/BLUETOOTH,
GNSS/GPS
INTEROPERABLE SDAR ANTENNA
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
ELECTRONIC 2500 RPM TACHOMETER
DETROIT CONNECT PLATFORM HARDWARE
5 YEARS DAIMLER CONNECTIVITY BASE
PACKAGE (FEATURES VARY BY MODEL)
POWERED BY DETROIT CONNECT ON
CUMMINS ENGINES
NO ASE DATA SVCE EXTENSION
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH,
ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #3, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #4, ON/OFF LATCHING, 10
AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR
EXTERIOR LAMPS ONLY
REAR SPRING LOADED HAND CONTROL BRAKE
VALVE
DIGITAL TURBO AIR PRESSURE IN DRIVER
DISPLAY
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

ROTARY HEADLAMP SWITCH, MARKER
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT
FOR OPTIONAL FOG/ROAD LAMPS

ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR

SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, HEADLAMP FLASH,
WASH/WIPE/INTERMITTENT

QUICKFIT POWERTRAIN INTERFACE
CONNECTOR UNDER CAB WITH BLUNTCUTS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EY WHITE ELITE EY
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS
PAINT

POWDER WHITE (N0006EA) FRONT
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

POWDER WHITE (N0006EA) REAR
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)

BUMPER PAINTED SAME AS CHASSIS

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES
CABS AND GLIDER KITS

Extended Warranty

TOWING: 2 YEARS/UNLIMITED MILES/KM EXTENDED TOWING
COVERAGE \$750 CAP FEX APPLIES

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061