

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

SPECIFICATION PROPOSAL

Data Code	Description	Weight Front	Weight Rear
Price Level			
PRL-29D	SD PRL-29D (EFF:MY26 ORDERS)		
Data Version			
DRL-013	SPECPRO21 DATA RELEASE VER 013		
Vehicle Configuration			
001-177	114SD PLUS CONVENTIONAL CHASSIS	7,934	6,476
004-226	2026 MODEL YEAR SPECIFIED		
002-004	SET BACK AXLE - TRUCK	480	-480
019-004	STRAIGHT TRUCK PROVISION, NON-TOWING		
003-001	LH PRIMARY STEERING LOCATION		
General Service			
AA1-002	TRUCK CONFIGURATION		
AA6-002	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
99D-027	EPA EMISSIONS CERTIFICATION FOR REGISTRATION IN EPA OR ACT STATES - EPA CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD OF DRIVER DOOR)		
A85-010	UTILITY/REPAIR/MAINTENANCE SERVICE		
A84-1GM	GOVERNMENT BUSINESS SEGMENT		
AA4-010	DIRT/SAND/ROCK COMMODITY		
AA5-002	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
AB1-008	MAXIMUM 8% EXPECTED GRADE		
AB5-001	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
995-1AD	FREIGHTLINER LEVEL I WARRANTY		
A66-99D	EXPECTED FRONT AXLE(S) LOAD : 14000.0 lbs		



Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
A68-99D	EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs		
A63-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 54000.0 lbs		

Truck Service

AA3-004	END DUMP BODY
* AF3-999	CUSTOM MFR'S/BODY TYPE IDENTIFICATION WILL USE A LOCAL BODY COMPANY

Engine

101-3BN	CUM L9 300 HP @ 2200 RPM; 2200 GOV RPM, 860 LB-FT @ 1200 RPM	-850	-70
---------	---	------	-----

Electronic Parameters

79A-075	75 MPH ROAD SPEED LIMIT
79B-000	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT
79K-002	PTO MODE ENGINE RPM LIMIT - 700 RPM
79P-002	PTO RPM WITH CRUISE SET SWITCH - 700 RPM
79Q-002	PTO RPM WITH CRUISE RESUME SWITCH - 700 RPM
79S-001	PTO MODE CANCEL VEHICLE SPEED - 5 MPH
79U-007	PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND
80G-002	PTO MINIMUM RPM - 700
80J-002	REGEN INHIBIT SPEED THRESHOLD - 5 MPH
80V-100	PTO MODE SPEED CONTROL ACTIVATION REQUEST FOR REMOTE ENGINE INTERFACE

Engine Equipment

99C-024	EPA 2010/GHG 2024 CONFIGURATION
13E-001	STANDARD OIL PAN
105-001	ENGINE MOUNTED OIL CHECK AND FILL
014-1B5	SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED
124-1D7	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE
292-236	(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES
290-017	BATTERY BOX FRAME MOUNTED
281-001	STANDARD BATTERY JUMPERS

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
282-001	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
289-001	NON-POLISHED BATTERY BOX COVER		
293-060	NON-ESSENTIAL POSITIVE LOAD DISCONNECT, LOCKING IN CAB CONTROL SWITCH MOUNTED OUTBOARD OF DRIVER SEAT	2	
295-029	POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER	2	
306-015	PROGRESSIVE LOW VOLTAGE DISCONNECT AT 12.3 VOLTS FOR DESIGNATED CIRCUITS	2	
107-032	CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
152-041	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
128-076	CUMMINS ENGINE INTEGRAL BRAKE WITH VARIABLE GEOMETRY TURBO ON/OFF	20	
016-1C2	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE	30	25
28F-014	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER		
239-026	10 FOOT 06 INCH (126 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
237-1CR	RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
23U-002	13 GALLON DIESEL EXHAUST FLUID TANK		
30N-003	100 PERCENT DIESEL EXHAUST FLUID FILL		
23Y-001	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
43X-005	LH UNDER CAB DIESEL EXHAUST FLUID TANK LOCATION		
43Y-001	STANDARD DIESEL EXHAUST FLUID TANK CAP		
242-011	ALUMINUM AFTERTREATMENT DEVICE/MUFFLER/TAILOPIPE SHIELD(S)		
273-058	AIR POWERED ON/OFF ENGINE FAN CLUTCH		
276-001	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
110-003	CUMMINS SPIN ON FUEL FILTER		
118-008	COMBINATION FULL FLOW/BYPASS OIL FILTER		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
120-998	NO COOLANT FILTER	-10	
266-017	1300 SQUARE INCH ALUMINUM RADIATOR	-50	
103-039	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
171-007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
172-001	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
270-016	RADIATOR DRAIN VALVE		
360-016	1310 ADAPTER FLANGE FOR FRONT PTO PROVISION	10	
138-011	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4	
140-053	BLACK PLASTIC ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
132-004	ELECTRIC GRID AIR INTAKE WARMER		
155-058	DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH	-35	

Transmission

342-582	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION
---------	--

Transmission Equipment

343-339	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV
84B-012	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES
84C-023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
84D-023	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY
84E-000	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE
84F-000	SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE
84G-000	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

	Data Code	Description	Weight Front	Weight Rear
	84H-000	SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE		
	84K-002	2ND GEAR ENGINE BRAKE ALTERNATE PRESELECT WITH MODERATE DOWNSHIFT STRATEGY		
N	84N-200	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED		
	84U-000	DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES		
	84V-001	DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS		
	85T-998	NO AMT HOLD MODE		
	353-075	QUICKFIT BODY LIGHTING CONNECTOR AT END OF FRAME, WITH CAP		
	34C-011	ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR		
	341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
	345-078	HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED		
	97G-004	TRANSMISSION PROGNOSTICS - ENABLED 2013		
	370-015	WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK	-15	
	346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
	35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		

Front Axle and Equipment

400-1A8	DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE	10
402-049	MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	
403-002	NON-ASBESTOS FRONT BRAKE LINING	
419-001	CAST IRON OUTBOARD FRONT BRAKE DRUMS	
427-001	FRONT BRAKE DUST SHIELDS	5
409-006	FRONT OIL SEALS	
408-001	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL	
416-022	STANDARD SPINDLE NUTS FOR ALL AXLES	
405-002	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS	



Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
406-001	STANDARD KING PIN BUSHINGS		
536-012	TRW TAS-85 POWER STEERING	40	
539-003	POWER STEERING PUMP		
534-003	4 QUART POWER STEERING RESERVOIR	5	
40T-001	MINERAL SAE 80/90 FRONT AXLE LUBE		
Front Suspension			
620-010	14,600# TAPERLEAF FRONT SUSPENSION	170	
619-005	MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
410-001	FRONT SHOCK ABSORBERS		
Rear Axle and Equipment			
420-1K3	MERITOR MT-40-14X 40,000# R-SERIES TANDEM REAR AXLE		-40
421-529	5.29 REAR AXLE RATIO		
424-003	IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING		40
386-073	MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES		
388-073	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES		
878-045	(1) INTERAXLE LOCK VALVE FOR TANDEM DRIVE AXLES		
87A-019	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH, DISENGAGE INTERAXLE LOCK WITH ABS EVENT OR IGNITION OFF		
423-020	MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
433-002	NON-ASBESTOS REAR BRAKE LINING		
434-019	ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY		
451-001	CAST IRON OUTBOARD REAR BRAKE DRUMS		-20
425-002	REAR BRAKE DUST SHIELDS		10
440-006	REAR OIL SEALS		
426-101	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS		
428-003	HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
41T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE		
42T-001	STANDARD REAR AXLE BREATHER(S)		
Rear Suspension			

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
622-297	TUFTRAC GEN2 40,000# REAR SPRING SUSPENSION		275
621-108	9.5 INCH NOMINAL RIDE HEIGHT (460MM GLOBAL REFERENCE HEIGHT)		
431-003	AXLE CLAMPING GROUP		
624-025	55 INCH AXLE SPACING		
623-006	FORE/AFT AND TRANSVERSE CONTROL RODS		
439-001	REAR SHOCK ABSORBERS - ONE AXLE		
Pusher / Tag Equipment			
429-998	NO PUSHER/TAG BRAKE DUST SHIELDS		
Brake System			
490-121	WABCO 4S/4M ABS WITH TRACTION CONTROL		
871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES		
904-001	FIBER BRAID PARKING BRAKE HOSE		
412-001	STANDARD BRAKE SYSTEM VALVES		
46D-002	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM		
413-002	STD U.S. FRONT BRAKE VALVE		
432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE		
480-088	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER		
479-015	AIR DRYER FRAME MOUNTED		
460-001	STEEL AIR BRAKE RESERVOIRS		
477-001	PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS		
Trailer Connections			
481-998	NO TRAILER AIR HOSE		
476-998	NO AIR HOSE HANGER		
919-063	(1) QUICKFIT PROGRAMMABLE SOLENOID W/STATE RETENTION PLUMBED TO BACK OF CAB		
310-998	NO TRAILER ELECTRICAL CABLE		
Wheelbase & Frame			
545-457	4575MM (180 INCH) WHEELBASE		
546-101	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI	100	20
547-001	1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT	160	350
552-028	1525MM (60 INCH) REAR FRAME OVERHANG		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
55W-005	FRAME OVERHANG RANGE: 51 INCH TO 60 INCH	20	-70
549-002	24 INCH INTEGRAL FRONT FRAME EXTENSION	115	-20
AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 114.57 in		
AE8-99D	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 111.57 in		
AE4-99D	CALC'D FRAME LENGTH - OVERALL : 309.72 in		
FSS-0LH	CALCULATED FRAME SPACE LH SIDE : 19.38 in		
FSS-0RH	CALCULATED FRAME SPACE RH SIDE : 60.37 in		
AM6-99D	CALC'D SPACE AVAILABLE FOR DECKPLATE : 0.0 in		
553-001	SQUARE END OF FRAME		
550-001	FRONT CLOSING CROSSMEMBER		
559-001	STANDARD WEIGHT ENGINE CROSSMEMBER		
562-001	STANDARD MIDSHIP #1 CROSSMEMBER(S)		
572-001	STANDARD REARMOST CROSSMEMBER		
565-002	HEAVY DUTY SUSPENSION CROSSMEMBER		30

Chassis Equipment

556-1E5	14 INCH PAINTED STEEL BUMPER	20	
574-001	BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
585-998	NO MUDFLAP BRACKETS		
590-998	NO REAR MUDFLAPS		
551-007	GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
44Z-002	EXTERIOR HARNESSSES WRAPPED IN ABRASION TAPE		
607-001	CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		

Fifth Wheel

578-998	NO FIFTH WHEEL		
---------	----------------	--	--

Fuel Tanks

204-156	100 GALLON/378 LITER ALUMINUM FUEL TANK - LH	20	
218-006	25 INCH DIAMETER FUEL TANK(S)		
215-005	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
212-007	FUEL TANK(S) FORWARD		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
664-001	PLAIN STEP FINISH		
205-001	FUEL TANK CAP(S)		
122-1H3	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR	10	
216-020	EQUIFLO INBOARD FUEL SYSTEM		
202-016	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
Tires			
093-994	MICHELIN XZE 12R22.5 16 PLY RADIAL FRONT TIRES	50	
094-2DE	MICHELIN X MULTI ENERGY D 11R22.5 14 PLY RADIAL REAR TIRES		160
Hubs			
418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS		
450-060	CONMET PRESET PLUS PREMIUM IRON REAR HUBS		
Wheels			
502-428	ACCURIDE 28828 22.5X8.25 10-HUB PILOT 6.18 INSET 2-HAND HD STEEL DISC FRONT WHEELS	26	
505-428	ACCURIDE 28828 22.5X8.25 10-HUB PILOT 2- HAND HD STEEL DISC REAR WHEELS		104
496-011	FRONT WHEEL MOUNTING NUTS		
497-011	REAR WHEEL MOUNTING NUTS		
Cab Exterior			
829-1A2	114 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB		
650-008	AIR CAB MOUNTING		
648-002	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
667-004	FRONT FENDERS SET-BACK AXLE		
678-001	LH AND RH GRAB HANDLES		
646-041	STATIONARY BLACK GRILLE		
65X-004	BLACK HOOD MOUNTED AIR INTAKE GRILLE		
644-004	FIBERGLASS HOOD		
690-017	HOOD LINER, ADDED FIREWALL AND FLOOR HEAT INSULATION	5	
727-1AH	SINGLE 14 INCH ROUND POLISHED AIR HORN ROOF MOUNTED		
726-001	SINGLE ELECTRIC HORN		
728-001	SINGLE HORN SHIELD		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
575-001	REAR LICENSE PLATE MOUNT END OF FRAME		
312-068	HALOGEN COMPOSITE HEADLAMPS WITH BLACK BEZELS		
302-047	LED AERODYNAMIC MARKER LIGHTS		
311-001	DAYTIME RUNNING LIGHTS		
294-001	INTEGRAL STOP/TAIL/BACKUP LIGHTS		
300-015	STANDARD FRONT TURN SIGNAL LAMPS		
744-1BC	DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE		
797-001	DOOR MOUNTED MIRRORS		
796-001	102 INCH EQUIPMENT WIDTH		
743-204	LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS		
729-001	STANDARD SIDE/REAR REFLECTORS		
677-055	RH AFTERTREATMENT SYSTEM CAB ACCESS WITH POLISHED DIAMOND PLATE COVER		
768-043	63X14 INCH TINTED REAR WINDOW		
661-003	TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
654-011	RH AND LH ELECTRIC POWERED WINDOWS		
663-013	1-PIECE SOLAR GREEN GLASS WINDSHIELD		
659-019	2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		
647-001	WHITE WINTERFRONT	2	
Cab Interior			
055-019	RUGGED TRIM PACKAGE		
707-107	GRAY & CARBON VINYL INTERIOR "RUGGED"		
70K-020	CARBON WITH PREMIUM GUNMETAL ACCENT (RUGGED)		
706-013	MOLDED PLASTIC DOOR PANEL		
708-013	MOLDED PLASTIC DOOR PANEL		
772-006	BLACK MATS WITH SINGLE INSULATION		
785-025	(1) 12V DASH MOUNTED POWER OUTLET		
691-001	FORWARD ROOF MOUNTED CONSOLE		
693-019	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS		
738-021	DIGITAL ALARM CLOCK IN DRIVER DISPLAY		
742-007	(2) CUP HOLDERS LH AND RH DASH		
680-029	M2/SD DASH		

Prepared for:
 OKLAHOMA STATE OF
 2401 N Lincoln
 Oklahoma City, OK 73105
 Phone: 405-521-2479

Prepared by:
 Jane Kirton
 PREMIER TRUCK GROUP OF
 OKLAHOMA CITY
 5301 I-40 WEST
 OKLAHOMA CITY, OK 73128
 Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
700-002	HEATER, DEFROSTER AND AIR CONDITIONER		
701-001	STANDARD HVAC DUCTING		
703-005	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
170-015	STANDARD HEATER PLUMBING		
130-041	VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR		
702-002	BINARY CONTROL, R-134A		
739-034	PREMIUM INSULATION		
285-013	SOLID-STATE CIRCUIT PROTECTION AND FUSES		
280-007	12V NEGATIVE GROUND ELECTRICAL SYSTEM		
324-1B3	STANDARD LED CAB LIGHTING		
787-004	REMOTE KEYLESS ENTRY AND 2 TRANSMITTERS	2	
657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME		
78G-004	KEY QUANTITY OF 4		
655-005	LH AND RH ELECTRIC DOOR LOCKS		
740-998	NO MATTRESS	-20	-15
722-002	TRIANGULAR REFLECTORS WITHOUT FLARES	10	
756-338	BASIC ISRINGHAUSEN HIGH BACK AIR SUSPENSION DRIVERS SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	30	
760-338	BASIC ISRINGHAUSEN HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH MECHANICAL LUMBAR AND INTEGRATED CUSHION EXTENSION	25	10
759-005	DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8	
711-004	LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
758-1AK	BLACK VINYL DRIVER SEAT COVER		
761-1AK	BLACK VINYL PASSENGER SEAT COVER		
763-102	HIGH VISIBILITY ORANGE SEAT BELTS		
532-002	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
540-070	4-SPOKE 18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL WITH CHROME SWITCH BEZELS		
765-002	DRIVER AND PASSENGER INTERIOR SUN VISORS		

Instruments & Controls



Prepared for:
 OKLAHOMA STATE OF
 2401 N Lincoln
 Oklahoma City, OK 73105
 Phone: 405-521-2479

Prepared by:
 Jane Kirton
 PREMIER TRUCK GROUP OF
 OKLAHOMA CITY
 5301 I-40 WEST
 OKLAHOMA CITY, OK 73128
 Phone: 405-945-3577

	Data Code	Description	Weight Front	Weight Rear
*	4CH-003	3 EXTRA PROGRAMMABLE SWITCHES/INDICATORS \$B5N5012ZZ,B5H5007ZZ,B5B5001ZZ		
	106-002	ELECTRONIC ACCELERATOR CONTROL		
	732-998	NO INSTRUMENT PANEL-DRIVER		
	734-022	FULLY CONFIGURABLE CENTER INSTRUMENT PANELS		
	87L-001	ENGINE REMOTE INTERFACE WITH PARK BRAKE INTERLOCK		
	870-002	BRIGHT ARGENT FINISH GAUGE BEZELS		
	486-001	LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
	840-001	DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE		
	198-025	INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
	721-001	97 DB BACKUP ALARM		3
	149-015	ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES		
	156-007	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
	157-004	MANUAL REMOTE ENGINE STOP/START		
	811-044	PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY		
	81B-003	DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY		
	160-038	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
	844-001	2 INCH ELECTRIC FUEL GAUGE		
	148-072	ENGINE REMOTE INTERFACE WITH ONE OR MORE SET SPEEDS		
	48H-003	QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH CAPS		
	48C-005	QUICKFIT PROGRAMMABLE INTERFACE CONNECTORS 1 & 2 BETWEEN SEATS WITH CAP		
	163-014	ENGINE REMOTE INTERFACE CONNECTOR AT POWERTRAIN INTERFACE CONNECTOR		
	856-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
	852-002	ELECTRIC ENGINE OIL PRESSURE GAUGE		
	864-022	DIGITAL TRANSMISSION OIL TEMPERATURE IN DRIVER DISPLAY		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

	Data Code	Description	Weight Front	Weight Rear
	867-004	ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER		
	830-017	ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
	372-123	PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE		
	736-998	NO OBSTACLE DETECTION SYSTEM		
	72J-998	NO DR ASSIST SYSTEM		
	49B-004	ELECTRONIC STABILITY CONTROL		
	73B-998	NO LANE DEPARTURE WARNING SYSTEM		
	72K-998	NO REVERSE PROXIMITY SENSOR		
	679-998	NO OVERHEAD INSTRUMENT PANEL		
	35M-013	2 QUIKFIT PROGRAMABLE MODULES (QPM/XMC)	20	
	1U1-002	TOP OF DASH RAM MOUNT WITHOUT POWER OR GROUND, FOR CUSTOMER FURNISHED DEVICE		
N	746-137	AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH, USB AND AUXILIARY INPUTS, J1939		
	747-001	DASH MOUNTED RADIO		
	750-002	(2) RADIO SPEAKERS IN CAB		
	753-001	AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF	2	
	748-006	POWER AND GROUND WIRING PROVISION OVERHEAD		
	749-001	ROOF/OVERHEAD CONSOLE CB RADIO PROVISION		
	75W-998	NO MULTIBAND ANTENNA		
	78C-998	NO DIGITAL SATELLITE AUDIO RECEIVER ANTENNA		
	810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
	817-001	STANDARD VEHICLE SPEED SENSOR		
	812-001	ELECTRONIC 3000 RPM TACHOMETER		
	813-1C8	DETROIT CONNECT PLATFORM HARDWARE		
	8D1-313	3 YEARS DAIMLER CONNECTIVITY BASE PACKAGE ON (FEATURES VARY BY MODEL) POWERED BY DETROIT CONNECT ON CUMMINS ENGINES		
	8DE-998	NO ASE DATA SVCE EXTENSION		
	RDE-998	NO EXTENSIONS		

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
6TS-008	(2) TMC RP1226 ACCESSORY CONNECTORS: (1) LOCATED BEHIND PASSENGER SIDE REMOVABLE DASH PANEL (1) CENTER OF OVERHEAD CONSOLE		
162-002	IGNITION SWITCH CONTROLLED ENGINE STOP		
4C1-998	NO HARDWIRE SWITCH #1		
4C2-998	NO HARDWIRE SWITCH #2		
4C3-998	NO HARDWIRE SWITCH #3		
264-030	(1) OVERHEAD MOUNTED LANYARD CONTROL FOR DRIVER AIR HORN		
883-998	NO TRAILER HAND CONTROL BRAKE VALVE		
836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
660-008	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
304-030	ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS		
27D-013	ALTERNATING FLASHING HEADLAMP SYSTEM WITH DASH SWITCH AND NO PARK BRAKE INTERLOCK		
882-009	ONE VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
299-020	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT		
298-046	INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH 40 AMP (20 AMP PER SIDE) TRAILER LAMP CAPACITY		
87T-998	NO WRG/SW-OPTL #2, CHAS, AIR		

Design

065-000	PAINT: ONE SOLID COLOR
---------	------------------------

Color

980-5F6	CAB COLOR A: L0006EY WHITE ELITE EY
986-020	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT
962-972	POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
966-972	POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)
964-020	STANDARD BLACK BUMPER PAINT
963-003	STANDARD E COAT/UNDERCOATING

Certification / Compliance

Application Version 12.0.009
Data Version PRL-29D.013
OK STATE 2026 114SD L9 54K
SW035T



10/15/2024 1:57 PM

Page 14 of 15

Prepared for:
OKLAHOMA STATE OF
2401 N Lincoln
Oklahoma City, OK 73105
Phone: 405-521-2479

Prepared by:
Jane Kirton
PREMIER TRUCK GROUP OF
OKLAHOMA CITY
5301 I-40 WEST
OKLAHOMA CITY, OK 73128
Phone: 405-945-3577

Data Code	Description	Weight Front	Weight Rear
996-001	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS		

Sales Programs

NO SALES PROGRAMS HAVE BEEN SELECTED

TOTAL VEHICLE SUMMARY

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	8359 lbs	6788 lbs	15147 lbs
Total Weight ⁺	8359 lbs	6788 lbs	15147 lbs

Extended Warranty

WAG-075 TOWING: 2 YEARS/UNLIMITED MILES/KM EXTENDED TOWING
COVERAGE \$750 CAP FEX APPLIES

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.